

1. Product Overview

The input level/water level transmitter uses a diffusion silicon chip to encapsulate the diffusion silicone

oil-filled core in a stainless-steel housing. The front-end protective cap functions as a protective sensor

diaphragm, and also allows the liquid to smoothly contact the diaphragm. Wire and housing are sealed

and connected. The vent pipe is connected to the outside in the cable. The internal structure is designed

to prevent condensation. Built-in micro signal processing circuit can be used for remote transmission. It

has good stability and reliability.

2. Application range

Widely used in water plants, sewage treatment plants, urban water supply, high-rise pools, wells, mines,

industrial pools, water tanks, oil pools, hydrogeology, reservoirs, rivers, oceans and other places

3. Technical parameters

◆ fully enclosed circuit, with moisture, condensation, anti-leakage function

◆ Range: 0~600 meters

◆ One-piece

◆ Accuracy: 0.5%FS

◆ . Technical parameters:

◆ Measurement form and range: 0~1~600mH₂O

◆ Allow overload 2 times full scale pressure

◆ Working temperature: -20~40°C

◆ Temperature compensation: -10~40°C

◆ Storage temperature: -40~80°C

◆ Output signal: 4-20mA

◆ Power supply: 12~24 VDC (standard voltage 24VDC)

◆ Shell Material 304 Stainless Steel

◆ Cable waterproof breathable cable

◆ Protection class: IP68