




Parallel Program Design Patterns and Strategies

Mike Bailey

mjb@cs.oregonstate.edu

Oregon State University




Oregon State University
Computer Graphics

parallel.design.pptx

mjb - March 13, 2015

Data Decomposition

Suppose you are doing image processing operations on a grid of pixels using 4 cores. Each pixel needs to see its neighboring pixels to get the job done. How would you distribute the pixels among the 4 cores?



How we distribute data and then communicate among the distributions is called a **Design Pattern**.



Oregon State University
Computer Graphics

mjb - March 13, 2015

Foster's Methodology: PCAM(R)

Partition the Problem

Think about how to break the problem up into its fundamental units of computing

Examine the Required Communication

Local: each task communicates with other tasks within a core – hopefully often

Global: each task communicates with a large number of other tasks between cores – hopefully seldom

Agglomerate (or Aggregate)

Combine the small partitioned tasks into larger tasks

Map

Assign the larger tasks to cores or threads

Reduce

Combine multi-results into one result






Oregon State University
Computer Graphics

Reference: Ian Foster, *Designing and Building Parallel Programs*, Addison-Wesley, 1995

mjb – March 13, 2015

Types of Parallel Communications



Oregon State University
Computer Graphics

mjb – March 13, 2015

PCAMR Rules of Thumb

1. Focus effort on the most time-consuming computation
2. Focus effort on whatever data is accessed most frequently
3. Focus effort on maximizing the *Compute : Communicate Ratio*
4. Use agglomeration to reduce communication by increasing locality
5. If agglomeration replicates data, be sure this does not affect the scalability of the algorithm by restricting the range of problem sizes and processor costs
6. Does the number of tasks scale with the problem size? (Not the size of each task!)
7. Place tasks that can execute concurrently on different cores
8. Place tasks that communicate frequently on the same core to increase locality
9. Be sure the Manager is not a bottleneck
10. If you are using cyclic or probabilistic load balancing, be sure you have enough tasks to keep everyone busy




Oregon State University
Computer Graphics

mjb - March 13, 2015

Paradigms for Task Scheduling / Mapping

Decentralized (Peer)



"Peer-threads"




Oregon State University
Computer Graphics

mjb - March 13, 2015

Paradigms for Task Scheduling / Mapping

Manager / workers




Oregon State University
Computer Graphics

mjb - March 13, 2015

Paradigms for Task Scheduling / Mapping

Map-Reduce




Oregon State University
Computer Graphics

mjb - March 13, 2015

Paradigms for Task Scheduling / Mapping

Pipeline



```
graph LR; Input --> S1[ ]; S1 --> S2[ ]; S2 --> S3[ ]; S3 --> S4[ ]; S4 --> Output;
```


Input → [] → [] → [] → [] → Output

Requires some sort of queue between the stages

OSU Oregon State University Computer Graphics mjb – March 13, 2015


Load Balancing Strategies: Assigning Portions of the Overall Task to the Threads

Recursive Equal Bisection



Recursive Unequal Bisection

Subdivisions don't necessarily have to be equal in size



Local algorithms

Each core checks its load against its neighboring cores and adjusts what it is handling

OSU Oregon State University
Computer Graphics

mjb – March 13, 2015

Load Balancing Strategies: Assigning Portions of the Overall Task to the Threads

Cyclic mappings

If there are N cores, allocate every N th task to a particular core. This is like using **chunksize** in *omp parallel for*.

Probabilistic methods

Allocate each task to a randomly-chosen core.



Oregon State University
Computer Graphics

mjb - March 13, 2015


Design Patterns

1. Replicating computation
2. Red / Black (Even / Odd)
3. Divide-and-Conquer (Reduction)
4. Block Scheduling



Oregon State University
Computer Graphics

mjb - March 13, 2015



Red/Black or Even/Odd

```
#include <algorithm>
...
for( int i = 0; i < NUMN; i++ )
{
    int first = i % 2;    // 0 if i is 0, 2, 4, ...
                        // 1 if i is 1, 3, 5, ...

    #pragma omp parallel for default(none),shared(A,first)

    for( int j = first; j < NUMN-1; j += 2 )
    {
        if( A[ j ] > A[ j+1 ] )
        {
            std::swap( A[ j ], A[ j+1 ] );
        }
    }
}
```

NUMN = 6

original	Step #					
	0	1	2	3	4	5
6	5	5	3	3	1	1
5	6	3	5	1	3	2
4	3	6	1	5	2	3
3	4	1	6	2	5	4
2	1	4	2	6	4	5
1	2	2	4	4	6	6




Oregon State University
Computer Graphics

mjb - March 13, 2015

Design Patterns: Divide and Conquer

$$\sum_{i=0}^{2^N-1} = \sum_{i=0}^{2^{N-1}-1} + \sum_{i=2^{N-1}}^{2^N-1}$$



Oregon State University
Computer Graphics

mjb - March 13, 2015

Design Patterns: Block Scheduling

Example: A diagonally-dominant matrix solution

- Break the problem into blocks
- Solve within the block
- Handle borders separately after a Barrier

$$\begin{bmatrix} \text{red} & 0 & 0 \\ 0 & \text{green} & 0 \\ 0 & 0 & \text{blue} \end{bmatrix} * \begin{Bmatrix} ? \\ ? \\ ? \end{Bmatrix} = \begin{Bmatrix} \text{red} \\ \text{green} \\ \text{blue} \end{Bmatrix}$$

$$\begin{aligned} \begin{bmatrix} \text{red} \end{bmatrix} * \begin{Bmatrix} ? \end{Bmatrix} &= \begin{Bmatrix} \text{red} \end{Bmatrix} \\ \begin{bmatrix} \text{green} \end{bmatrix} * \begin{Bmatrix} ? \end{Bmatrix} &= \begin{Bmatrix} \text{green} \end{Bmatrix} \\ \begin{bmatrix} \text{blue} \end{bmatrix} * \begin{Bmatrix} ? \end{Bmatrix} &= \begin{Bmatrix} \text{blue} \end{Bmatrix} \end{aligned}$$

Barrier

Share results across boundaries




Oregon State University
Computer Graphics

mjb - March 13, 2015

Another Block Schedule Example: 1D Heat Transfer Equation

$$\rho C \frac{\partial T}{\partial t} = k \left(\frac{\partial^2 T}{\partial x^2} \right)$$


$$\frac{\Delta T}{\Delta t} = \frac{k}{\rho C} \left(\frac{\Delta^2 T}{\Delta x^2} \right) \longrightarrow \Delta T_i = \left(\frac{k}{\rho C} \right) \left(\frac{T_{i-1} - 2T_i + T_{i+1}}{(\Delta x)^2} \right) \Delta t$$




Oregon State University
Computer Graphics

mjb - March 13, 2015


Partition: 1D Domain (Data) Decomposition



1D Block



1D Cyclic




1D Cyclic



Oregon State University
Computer Graphics

mjb - March 13, 2015

Communication, Agglomeration, Mapping: 1D Compute-to-Communicate Ratio



Intracore computing



Intercore communication

Compute : Communicate ratio = $N : 2$


where N is the number of compute cells per core




Oregon State University
Computer Graphics

mjb - March 13, 2015


1D Domain (Data) Decomposition



Compute : Communicate = 4 : 2



Compute : Communicate ratio = 2 : 2




Compute : Communicate ratio = 1 : 2



Oregon State University
Computer Graphics



mjb - March 13, 2015

Performance as a Function of Number of Nodes




Oregon State University
Computer Graphics


mjb - March 13, 2015




2D Domain (Data) Decomposition




2D *,Block




2D Block,*




2D Block,Block



2D *,Cyclic



2D Cyclic,*



2D Cyclic,Cyclic




Oregon State University
Computer Graphics

mjb - March 13, 2015

The Decomposition Order Matters (think cache)

float Array[A][B];



In 2D problems, this is often (but not always) thought of as:

float Array[NY][NX];

```

0  0
0  1
0  2
0  3
0  ...
0  B-1
1  0
1  1
1  2
1  3
1  ...
1  B-1

```

```

.  .  .
A-1  0
A-1  1
A-1  2
A-1  3
A-1  ...
A-1  B-1


```



Oregon State University
Computer Graphics

mjb - March 13, 2015

2D Compute-to-Communicate Ratio



$$\text{Compute : Communicate ratio} = N^2 : 4N = N : 4$$

where N is the dimension of compute cells per core

The 2D Compute : Communicate ratio is sometimes referred to as
Area-to-Perimeter

Computer Graphics


mjb - March 13, 2015

3D Heat Transfer Equation

$$\rho C \frac{\partial T}{\partial t} = k \left(\frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} + \frac{\partial^2 T}{\partial z^2} \right)$$

$$\Delta T_{i,j,k} = \left(\frac{k}{\rho C} \right) \left(\frac{T_{i-1,j,k} - 2T_{i,j,k} + T_{i+1,j,k}}{(\Delta x)^2} + \frac{T_{i,j-1,k} - 2T_{i,j,k} + T_{i,j+1,k}}{(\Delta y)^2} + \frac{T_{i,j,k-1} - 2T_{i,j,k} + T_{i,j,k+1}}{(\Delta z)^2} \right) \Delta t$$



$$\frac{\Delta T}{\Delta t} = \frac{k}{\rho C} \left(\frac{\Delta^2 T}{\Delta x^2} + \frac{\Delta^2 T}{\Delta y^2} + \frac{\Delta^2 T}{\Delta z^2} \right)$$



OSU


Oregon State University
Computer Graphics

mjb - March 13, 2015



The Decomposition Order Matters (think cache)

```
float Array[A][B][C];
```



In 3D problems, this is often (but not always) thought of as:

```
float Array[NZ][NY][NX];
```



Oregon State University
Computer Graphics

mjb - March 13, 2015

3D Compute-to-Communicate Ratio

Compute : Communicate ratio = $N^3 : 6N^2 = N : 6$



where N is the dimension of compute cells per core

**In 3D the Compute : Communicate ratio is sometimes referred to as
*Volume-to-Surface***




Oregon State University
Computer Graphics

mjb - March 13, 2015



Matrix Multiply

The usual approach is multiplying the entire A row * entire B column
This is equivalent to computing a single dot product



```
for( i = 0; i < SIZE; i++ )
  for( j = 0; j < SIZE; j++ )
    for( k = 0; k < SIZE; k++ )
```

$$\sum A[i][k] * B[k][j] \xrightarrow{\text{Sum and store}} C[i][j]$$




Oregon State University
Computer Graphics

Problem: Column j of the B matrix is not doing a unit stride

mjb - March 13, 2015

Matrix Multiply

Scalable Universal Matrix Multiply Algorithm (SUMMA)
Entire A row * one element of B row
Equivalent to computing one item in many separate dot products



```
for( i = 0; i < SIZE; i++ )
  for( k = 0; k < SIZE; k++ )
    for( j = 0; j < SIZE; j++ )
```


$$A[i][k] * B[k][j] \xrightarrow{\text{Add to}} C[i][j]$$




Oregon State University
Computer Graphics

mjb - March 13, 2015


Performance vs. Number of Threads (MegaMultiplies / Sec)



$i-k-j$




$j-k-i$



$k-i-j$


mjb - March 13, 2015

Performance vs. Matrix Size (MegaMultiplies / Sec)




$i-j-k$

$i-k-j$



$j-k-i$

$j-i-k$



$k-i-j$

$k-j-i$

mjb - March 13, 2015