# Numerical ODE group/population integrators in Torsten

Yi Zhang

July 30, 2019

# ODE group integrators

## Single ODE system

```
pmx_integrate_ode_rk45
pmx_integrate_ode_bdf
pmx_integrate_ode_adams
```

#### ODE group

```
pmx_integrate_ode_group_rk45
pmx_integrate_ode_group_bdf
pmx_integrate_ode_group_adams
```

## Single ODE system

```
real[,]
pmx_integrate_ode_xxx(
          f,
          real[] y0, real t0,
          real[] ts,
          real[] theta,
          real[] x_r, int[] x_i,
          ...);
```

## ODE group

```
matrix
pmx_integrate_ode_group_xxx(
    f,
    real[ , ] y0, real t0,
    int[] len, real[] ts,
    real[ , ] theta,
    real[ , ] x_r, int[ , ] x_i,
    ...);
```

# ODE group integrators

# Single ODE system

```
real[ , ]
pmx_integrate_ode_xxx(
          f,
          real[] y0, real t0,
          real[] ts,
          real[] theta,
          real[] x_r, int[] x_i,
          ...);
```

# ODE group

```
matrix
pmx_integrate_ode_group_xxx(
    f,
    real[ , ] y0, real t0,
    int[] len, real[] ts,
    real[ , ] theta,
    real[ , ] x_r, int[ , ] x_i,
    ...);
```

- len specifies the length of data for each subject within the above ragged arrays, and the size of len is the size of the population.
- ► The group integrators return a single matrix ragged column-wise. The number of rows equals to the size of ODE system.

#### Exercise

## autocatalytic reaction model: ODE group version

- Change the loop with the numerical integrator to use group integrator.
- Edit/Add cmdstan/make/local

Build in cmdstan

make ../example-models/ttpn2/ttpn2\_group

Run

### Exercise

- What does output say?
- ► How many cores can you use until performance saturates? Why?
- ► Can you do it using Stan's map\_rect? Is there a difference in style, output, and performance?