

# Namespace: v0\_11\_0

## Interfaces

- [AppDataRootSchema](#)
- [CoWHook](#)
- [Metadata](#)
- [OrderClass](#)
- [OrderInteractionHooks](#)
- [Quote](#)
- [Referrer](#)
- [UTMCodes](#)
- [Widget](#)

## Type Aliases

### AppCode

TAppCode :string

The code identifying the CLI, UI, service generating the order.

#### Defined in

generatedTypes/v0.11.0.ts:15

### AppCode1

TAppCode1 :string

The code identifying the UI powering the widget

#### Defined in

generatedTypes/v0.11.0.ts:80

### Environment

TEnvironment :string

Environment from which the order came from.

#### Defined in

generatedTypes/v0.11.0.ts:19

### Environment1

TEnvironment1 :string

Environment from which the order came from.

#### Defined in

generatedTypes/v0.11.0.ts:84

### HookCallData

THookCallData :string

The calldata to use when calling the hook

#### Defined in

generatedTypes/v0.11.0.ts:64

## HookGasLimit

THookGasLimit :string

The gas limit (in gas units) for the hook

### Defined in

generatedTypes/v0.11.0.ts:68

## HookTarget

THookTarget :string

The contract to call for the hook

### Defined in

generatedTypes/v0.11.0.ts:60

## OrderClass1

TOrderClass1 : "market" | "limit" | "liquidity" | "twap"

Indicator of the order class.

### Defined in

generatedTypes/v0.11.0.ts:52

## PostHooks

TPostHooks : [CoWHook](#) []

CoW Hooks to call after an order executes

### Defined in

generatedTypes/v0.11.0.ts:76

## PreHooks

TPreHooks : [CoWHook](#) []

CoW Hooks to call before an order executes

### Defined in

generatedTypes/v0.11.0.ts:72

## ReferrerAddress

TReferrerAddress :string

### Defined in

generatedTypes/v0.11.0.ts:24

## Signer

TSigner :string

The address of the trader who signs the CoW Swap order. This field should normally be omitted; it is recommended to use it if the signer is a smart-contract wallet using EIP-1271 signatures.

### Defined in

generatedTypes/v0.11.0.ts:23

## **SlippageBips**

TSlippageBips :string

Slippage tolerance that was applied to the order to get the limit price. Expressed in Basis Points (BPS)

### **Defined in**

generatedTypes/v0.11.0.ts:48

## **UTMCampaign**

TUTMCampaign :string

Track the performance of a specific campaign

### **Defined in**

generatedTypes/v0.11.0.ts:36

## **UTMContent**

TUTMContent :string

Track which link was clicked

### **Defined in**

generatedTypes/v0.11.0.ts:40

## **UTMKeywordTerm**

TUTMKeywordTerm :string

Track which keyword term a website visitor came from

### **Defined in**

generatedTypes/v0.11.0.ts:44

## **UTMMedium**

TUTMMedium :string

Tracks in which medium the traffic originated from (mail, CPC, social, etc.)

### **Defined in**

generatedTypes/v0.11.0.ts:32

## **UTMSource**

TUTMSource :string

Tracks in which medium the traffic originated from (twitter, facebook, etc.)

### **Defined in**

generatedTypes/v0.11.0.ts:28

## **Version**

TVersion :string

Semantic versioning of document.

**Defined in**

generatedTypes/v0.11.0.ts:11

**Version1**

TVersion1 :string

Semantic versioning of document.

**Defined in**

generatedTypes/v0.11.0.ts:56 [Previous v0\\_10\\_0](#) [Next v0\\_1\\_0](#)