

# zks\_getL2ToL1MsgProof

Returns the proof for a message sent through the L1Messenger system contract, given a block, sender, message, and an optional message log index containing the L1 to L2 message.

## Parameters

- block
  - : (integer) [Required
  - ] Block where the message was emitted.
- sender
  - : (string) [Required
  - ] The sender (account) of the message.
- msg
  - : [Required
  - ] The keccak256 hash of the sent message.
- l2\_log\_position
  - : The index in the block of the event that was emitted by the L1Messenger
  - when submitting this message. If it is omitted, the proof for the first message is returned.

## Response

- id
  - - The position of the leaf in the Merkle tree of L2 to L1 messages for the block.
- proof
  - - The Merkle proof for the message.
- root
  - - The root hash representing the Merkle tree root at the time the log was generated.

## Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#).

### Request

- cURL
- WSS

```
curl https://zksync-mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc": "2.0", "id": 1, "method": "zks_getL2ToL1MsgProof", "params": [5187, "0x87869cb87c4Fa78ca278dF358E890FF73B42a39E", "0x22de7debaa98758afdae89f447ff43bab5da3de6acca7528b281cc2f1be2ee9"]}' wscat -c wss://zksync-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc": "2.0", "id": 1, "method": "zks_getL2ToL1MsgProof", "params": [5187, "0x87869cb87c4Fa78ca278dF358E890FF73B42a39E", "0x22de7debaa98758afdae89f447ff43bab5da3de6acca7528b281cc2f1be2ee9"]}'
```

### Response

- JSON

```
{ "jsonrpc": "2.0", "result": "0x25f64db", "id": 2 }
```

Last updated on Nov 5, 2024 [Previous zks\\_getL2ToL1LogProof](#) [Next zks\\_getMainContract](#)