

RPC Key Differences

In order to keep some data in transactions confidential, SUAVE JSON-RPC extends the usual Ethereum JSOPN-RPC methods. Some methods in the `theeth_` namespace are overloaded to support confidential compute requests.

- ### 1. eth_sendRawTransaction

Creates a new message call transaction or a contract creation for any signedConfidentialComputeRequest .

- ### 1. eth_call

Executes a new message call immediately without creating a transaction on the block chain. It follows the same format as the `defaulteth_` call with two extra parameters:

- IsConfidential
- : Set to true to execute as a confidential request and access the [MEVM](#)
- methods.
- ExecutionAddress
- :address
- - (optional) The execution address that performs the execution.
- eth_kettleAddress

Returns the list of available addresses in the Kettle to execute the confidential compute request.

Testing the RPC

The easiest way to test your connection to an RPC endpoint is via a simple curl command.

Remote curl request

```
curl
-X POST \-H
"Content-Type: application/json"
\ --data
{"jsonrpc":"2.0","method":"eth_kettleAddress","params":[],"id":1}
https://rpc.rigil.suave.flashbots.net
```

Local curl request

```
curl
-X POST \-H
"Content-Type: application/json"
--data
{"jsonrpc":"2.0","method":"eth_kettleAddress","params":[],"id":1}
http://localhost:8545
```

Expected Response

If your connection is working properly you should get a response such as:

{ "jsonrpc": "2.0", "result": "0x30870", "id": 1 } Note that the only difference between these two is the URL at the end of the curl request.

SUAVE Transactions

The example above follows the [exact same API interface](#) as the original go-ethereum client. However, if we grab a random transaction hash from the [Rigil Explorer](#), we can see the core difference with the SUAVE Rigil RPC: a new SUAVE transaction type.

Remote curl request

```
curl
-X POST \-H
"Content-Type: application/json"
--data
'{"jsonrpc": "2.0", "method": "eth_getTransactionByHash", "params": [ "0x294b510e4fd257dec3d27b051f157489446c38828f5f6b8d8c194797c6ddaab" ], "id": 1 }'
https://rpc.rigil.suave.flashbots.net
```

Response

[illegible]

```
{ ... }, "s" :
```

```
"0x765917eb8554a00d43162f9b9fff8646e8a7ce1756855d84f7627ec9571689d1" , "to" :
```

```
"0xa60f1b5cb70c0523a086bbcbe132c8679085ea0e" , "transactionIndex" :
```

```
"0x0" , "type" :
```

```
"0x50" , "v" :
```

```
"0x1" , "value" :
```

```
"0x0" } , "id" :
```

1 } This response has a couple fields that aren't in your traditional Ethereum transaction type, namely:

- confidentialComputeResult
- executionNode
- requestRecord

To dive deeper into these differences checkout the [SUAVE chain specs](#) . [Edit this page](#) [Previous MEV Supply Chain Interface](#) [Next Tools](#)