eth_getUserOperationReceipt

This method fetches the receipt of a user operation, given the userOpHash . If the receipt is not available, it will return null .

Request

```
{ "jsonrpc":"2.0", "method":"eth_getUserOperationReceipt", "params": ["0xa5a579c6fd86c2d8a4d27f5bb22796614d3a31bbccaba8f3019ec001e001b95f"], "id":1 }
```

Response

```
{ "jsonrpc":"2.0", "id":1, "result": { "userOpHash":"0xa5a579c6fd86c2d8a4d27f5bb22796614d3a31bbccaba8f3019ec001e001b95f", "sender":"0x8C6bdb488F664EB98E12cB2671fE2389Cc227D33",
"nonce":"0x18554d9a95404c5e8ac591f8608a18f80000000000000000", "actualGasUsed":"0x7f550", "actualGasCost":"0x4b3b147f788710", "success":true, "logs": [ // ... ], "receipt": {
"transactionHash":"0x57465d20d6344421008a167cfcfcde94847dba9d6b5d3652b071d4b84e5ce74ff", "transactionIndex":"0x20",
"blockHash":"0xeaeec1eff4095bdcae44d86574cf1bf08b14b26be571b7c2290f32f9f250c103", "blockNumber":"0x31de70e", "from":"0x43370996A3Aff7B66B3AC7676dD973d01Ecec039",
"to":"0x5FF137D4b0FDCD49DcA30c7CF57E578a026d2789", "cumulativeGasUsed":"0x4724c3", "gasUsed":"0x7ff5a", "contractAddress":null, "logs": [ // ... ],
"logsBloom":"0x01000400080002000000004000000000000000400000000000000010000004000000080000010000002128411000000000410800000000000020000240000000000080000000220010004000
"status":"0x1", "effectiveGasPrice":"0x89b098f46" } } }
```