

Sample Queries

Below are some sample queries you can use to gather information from the Connex contracts.

You can build your own queries using a [GraphQL Explorer](#) and enter your endpoint to limit the data to exactly what you need.

Get origin domain details of an xcall

...

Copy queryOriginTransfer{ originTransfers(where: {

Query by the transaction hash of the xcall

transactionHash:""

Or by the xcall's transfer ID

transferId:"" }) {

Meta Data

chainId nonce transferId to delegate receiveLocal callData slippage originSender originDomain destinationDomain
transactionHash bridgedAmt status timestamp normalizedIn

Asset Data

asset { id adoptedAsset canonicalId canonicalDomain } } }

...

Get destination domain details of an xcall

...

Copy queryDestinationTransfer{ destinationTransfers(where: {transferId:""}) {

Meta Data

chainId nonce transferId to callData originDomain destinationDomain delegate

Asset Data

asset { id } bridgedAmt

Executed event Data

status routers { id } originSender

Executed Transaction

executedCaller executedTransactionHash executedTimestamp executedGasPrice executedGasLimit executedBlockNumber

Reconciled Transaction

reconciledCaller reconciledTransactionHash reconciledTimestamp reconciledGasPrice reconciledGasLimit

reconciledBlockNumber routersFee slippage } }

...

[Previous Entities](#) [Next Subgraph Resources](#) On this page * [Get origin domain details of an xcall](#) * [Get destination domain details of an xcall](#)

[Edit on GitHub](#)