

commands.models

module commands.models

Global Variables

- API_HOST
-

function get

...

Copy get(model_id: int=typer.Option(..., "--model-id", "-m", help="Model id to retrieve information from"), debug: Optional[bool]=DEBUG_OPTION)→None

...

Command to create a user. Asks for the new users information and validates the input, then sends the information to the API

Args:

- debug
- (Optional[bool], optional): Whether to add debug information, will show requests, extra logs and traceback if there is an Exception. Defaults to DEBUG_OPTION (False).
-

Raises:

- ValidationError
- : input fields are validated, if these are not suitable the exception is raised
- HTTPError
- : request error to the API, 4XX or 5XX
-

function list

...

Copy list(debug: Optional[bool]=DEBUG_OPTION)→None

...

Command to list all models.

Args:

- debug
- (Optional[bool], optional): Whether to add debug information, will show requests, extra logs and traceback if there is an Exception. Defaults to DEBUG_OPTION (False).
-

Raises:

- ValidationError
- : input fields are validated, if these are not suitable the exception is raised
- HTTPError
- : request error to the API, 4XX or 5XX
-

function create

...

Copy create(name: str=typer.Option(..., "--name", "-n", help="Name of the model to be created"), description: str=typer.Option(None, "--description", "-d", help="Description of the model to be created"), debug: Optional[bool]=**DEBUG_OPTION**)→None

...

Command to create a model. Asks for the new model's information and validates the input, then sends the information to the API

Args:

- debug
- (Optional[bool], optional): Whether to add debug information, will show requests, extra logs and traceback if there is an Exception. Defaults to DEBUG_OPTION (False).
-

Raises:

- ValidationError
- : input fields are validated, if these are not suitable the exception is raised
- HTTPError
- : request error to the API, 4XX or 5XX
-

[Previous commands.deploy](#) [Next commands.prove](#)

Last updated 1 month ago