

trace_call

Executes the given call and returns a number of possible traces for it. Use this API to retrieve detailed information about the transaction execution, including state changes and logs generated during the process.

Parameters

- transaction call object
- `[Required]`
- with the following keys and their values:
 - `from`
 - : 20 bytes. The address the transaction is sent from.
 - `to`
 - : 20 bytes. The address the transaction is directed to.
 - `gas`
 - `[optional]`
 - The hexadecimal value of the gas provided for the transaction execution.
 - `gasPrice`
 - `[optional]`
 - The hexadecimal value of the gasPrice used for each paid gas.
 - `maxPriorityFeePerGas`
 - `[optional]`
 - Maximum fee, in Wei, the sender is willing to pay per gas above the base fee.
 - See [EIP-1559 transactions](#)
 - `.`
 - `maxFeePerGas`
 - `[optional]`
 - Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas.
 - See [EIP-1559 transactions](#)
 - `.`
 - `value`
 - `[optional]`
 - The hexadecimal equivalent of the value sent with this transaction.
 - `data`
 - `[optional]`
 - The hash of the method signature and encoded parameters. See the [Ethereum contract ABI specification](#)
 - `.`
 - `block parameter`
 - `[Required]`
 - The hexadecimal block number, or the string `latest`
 - `, earliest`
 - `, or pending`
 - See the [default block parameter](#)
 - `.`
 - `options`
 - : A list of tracing options. Tracing options are [trace](#)
 - and [stateDiff](#)
 - `.`

Returns

- result
- : A trace object that includes the [trace](#)
- and [stateDiff](#)
- .

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#).

Request

- cURL
- WSS

[illegible]

Response

- JSON

[illegible]

Last updated on Apr 19, 2024 [Previous trace block](#) [Next trace call](#) Many