

Slope Adapter

[@web3auth/slope-adapter](#)

[â](#)

Slope adapter allows you to connect with slope wallet. You can read more about slope wallet here. (<https://developers.slope.so/>).

Basic Details[â](#)

Adapter Name:slope

[â](#)

Package Name:[@web3auth/slope-adapter](#)

[â](#)

authMode:DAPP

[â](#)

chainNamespace:SOLANA

[â](#)

Default:YES

[â](#)

Installation[â](#)

- npm
- Yarn
- pnpm

npm install --save @web3auth/slope-adapter yarn add @web3auth/slope-adapter pnpm add @web3auth/slope-adapter

Arguments[â](#)

- Table
- Interface

Parameter type chainConfig? CustomChainConfig clientId? string sessionTime? number web3AuthNetwork? OPENLOGIN_NETWORK_TYPE interface

SlopeAdapterOptions

{ chainConfig ? :

CustomChainConfig ; clientId ? :

string ; sessionTime ? :

number ; web3AuthNetwork ? :

OPENLOGIN_NETWORK_TYPE ; }

Custom Chain Config[â](#)

chainConfig

[â](#)

warning While you can pass yourchainConfig , it is not required since you can directly pass it over to theWeb3Auth /Web3AuthNoModal configuration while instantiating it.

Read more about it in their respective sections:

- [web3auth/modal](#)
- [web3auth/no-modal](#) warning If you do passchainConfig in an Adapter, it overwrites thechainConfig passed over to theWeb3Auth /Web3AuthNoModal constructor.

Change Adapter Settings

You can change the adapter settings by calling thesetAdapterSettings() function on the adapter instance.

Arguments

- Table
- Interface

Parameter type clientId? string sessionTime? number chainConfig? CustomChainConfig web3AuthNetwork? OPENLOGIN_NETWORK_TYPE interface

BaseAdapterSettings

{ clientId ? :

string ; sessionTime ? :

number ; chainConfig ? :

CustomChainConfig ; web3AuthNetwork ? :

OPENLOGIN_NETWORK_TYPE ; }

Example

```
import
```

```
{
```

```
SlopeAdapter
```

```
}
```

```
from
```

```
"@web3auth/slope-adapter" ; const slopeAdapter =
```

```
new
```

```
SlopeAdapter ( { clientId :
```

```
"BPi5PB_UiIZ-cPz1GtV5i1I2iOSOHuimiXBI0e-Oe_u6X3oVAbCiAZOTEBtTXw4tsluTITPqA8zMsfxIKMjiqNQ" , sessionTime :
```

```
3600 ,
```

```
// 1 hour in seconds chainConfig :
```

```
{ chainNamespace :
```

```
CHAIN_NAMESPACES . SOLANA , chainId :
```

```
"0x1" , rpcTarget :
```

```
"https://rpc.ankr.com/solana" ,
```

```
// This is the public RPC we have added, please pass on your own endpoint while creating an app } , web3AuthNetwork :
```

```
"sapphire_mainnet" , } ) ; web3auth . configureAdapter ( slopeAdapter ) ;
```

```
// You can also change the adapter settings by calling the setAdapterSettings() function on the adapter instance.
```

```
slopeAdapter . setAdapterSettings ( { sessionTime :
```

86400 ,

// 1 day in seconds chainConfig :

{ chainNamespace :

CHAIN_NAMESPACES . SOLANA , chainId :

"0x1" , rpcTarget :

"https://rpc.ankr.com/solana" ,

// This is the public RPC we have added, please pass on your own endpoint while creating an app } , web3AuthNetwork :

"sapphire_mainnet" , }) ;[Edit this page](#) [Previous Coinbase Wallet](#) [Next Solflare Wallet](#)