

Quick start

Installation

npm install @1inch/limit-order-protocol-utils

or

yarn add @1inch/limit-order-protocol-utils

@1inch/limit-order-protocol package is now used for smart contract distribution and no longer contains this library.

Example on how to create and fill a limit order

```
import Web3 from
```

```
'web3' ; import
```

```
{ limitOrderProtocolAddresses , seriesNonceManagerContractAddresses , ChainId , Erc20Facade , LimitOrderBuilder ,  
LimitOrderProtocolFacade , LimitOrderPredicateBuilder , NonceSeriesV2 , SeriesNonceManagerFacade ,  
SeriesNonceManagerPredicateBuilder , Web3ProviderConnector }
```

```
from
```

```
'@1inch/limit-order-protocol-utils' ;
```

```
const chainId = ChainId . ethereumMainnet ;
```

```
// suggested, or use your own number const connector =
```

```
new
```

```
Web3ProviderConnector ( new
```

```
Web3 ( '...' ) ) ; const contractAddress = limitOrderProtocolAddresses [ chainId ] ; const seriesContractAddress =  
seriesNonceManagerContractAddresses [ chainId ] ;
```

```
const limitOrderProtocolFacade =
```

```
new
```

```
LimitOrderProtocolFacade ( contractAddress , chainId , connector ) ; const seriesNonceManagerFacade =
```

```
new
```

```
SeriesNonceManagerFacade ( seriesContractAddress , chainId , connector ) ; ] const seriesNonceManagerPredicateBuilder  
=
```

```
new
```

```
SeriesNonceManagerPredicateBuilder ( seriesContractAddress , chainId , connector ) ; const erc20Facade =
```

```
new
```

```
Erc20Facade ( connector ) ;
```

```
const expiration =
```

```
54444440000 ;
```

```
// Some moment in future const nonce = seriesNonceManagerFacade . nonce ( NonceSeriesV2 . LimitOrderV3 ,  
walletAddress ) ;
```

```
// Creates predicate that restricts Limit Order invalidation conditions // Because timestampBelowAndNonceEquals is method  
of another contract arbitraryStaticCall() is necessary const simpleLimitOrderPredicate : LimitOrderPredicateCallData =
```

```
arbitraryStaticCall ( seriesNonceManagerPredicateBuilder . facade , seriesNonceManagerPredicateBuilder .  
timestampBelowAndNonceEquals ( NonceSeriesV2 . LimitOrderV3 , expiration , nonce , walletAddress , ) , ) ;
```

```

// Create a limit order and it's signature const limitOrder = limitOrderBuilder . buildLimitOrder ( { makerAssetAddress :
'0xbb4cddb9cbd36b01bd1cbaebf2de08d9173bc095c' , takerAssetAddress :
'0x111111111117dc0aa78b770fa6a738034120c302' , makerAddress : walletAddress , makerAmount :
'100' , takerAmount :
'200' , predicate : simpleLimitOrderPredicate , // permit = '0x' , // receiver = ZERO_ADDRESS , // allowedSender =
ZERO_ADDRESS , // getMakingAmount = ZERO_ADDRESS , // getTakingAmount = ZERO_ADDRESS , // preInteraction =
'0x' , // postInteraction = '0x' , // eg Wrapped to native unwrapper } ) ;

const limitOrderTypedData = limitOrderBuilder . buildLimitOrderTypedData ( limitOrder , ) ; const limitOrderSignature =
limitOrderBuilder . buildOrderSignature ( walletAddress , limitOrderTypedData , ) ;

// Create a call data for fill the limit order const callData = limitOrderProtocolFacade . fillLimitOrder ( { order : limitOrder ,
signature : limitOrderSignature , makingAmount :
'100' , takingAmount :
'0' , thresholdAmount :
'50' } ) ;

// Send transaction for the order filling // Must be implemented sendTransaction ( { from : walletAddress , gas :
210_000 ,
// Set your gas limit gasPrice :
40000 ,
// Set your gas price to : contractAddress , data : callData , } ) ; Note: you can use any implementation for the provider. Just
implement theProviderConnector interface:

class
MyProviderConnector
implements
ProviderConnector

{ //... } Edit this page Previous About Next Create a limit order

```