eth_estimateGas

Generates and returns an estimate of how much gas is necessary to allow the transaction to complete. The transaction will not be added to the blockchain. Note that the estimate may be significantly more than the amount of gas actually used by the transaction, for a variety of reasons including EVM mechanics and node performance.

Gas parameter is capped To prevent abuse of the API, thegas parameter in thiseth_estimateGas method and ieth_call is capped at 10x (1000%) the current block gas limit. You can recreate this behavior in your local test environment (besu, geth, or other client) via therec.gascap command-line option.

Parameters

• TRANSACTION CALL OBJECT [required] o 20 Bytes - The address the transaction is sent from. • : 20 Bytes - The address the transaction is directed to das :[optional] · Hexadecimal value of the gas provided for the transaction execution.eth estimateGas consumes · zero gas, but this parameter may be needed by some executions. gasPrice Hexadecimal value of the gas price used for each paid gas. maxPriorityFeePerGas • Maximum fee, in Wei, the sender is willing to pay per gas above the base fee • SeeEIP-1559 transactions maxFeePerGas :[optional] • Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas. See<u>EIP-1559 transactions</u> value Hexadecimal value of the value sent with this transaction. · :[optional] Hash of the method signature and encoded parameters. See th€thereum contract ABI specification block number :[required] A string representing a block number, or one of the string tagslatest .earliest ,pending safe • , orfinalized See the<u>default block parameter</u>

If no gas limit is specified, geth uses the block gas limit from the pending block as an upper bound. As a result the returned estimate might not be enough to executed the call/transaction when the amount of gas is higher than the pending block gas limit.

Returns

A hexadecimal of the estimate of the gas for the given transaction.

If this call causes the EVM to execute aREVERT operation, an error response of the following form is returned, with the revert reason pre-decoded as a string:

ReplaceYOUR-API-KEY with an API key from your dashboard.

Request

• cURL

Response

JSON

{ "jsonrpc" :

"2.0" , "id" :

1 , "result" :

"0x5cec" }

Last updatedonApr 19, 2024 Previous eth_chainId Next eth_feeHistory