# eth\_estimateGas

Generates and returns an estimate of how much gas is necessary to allow the transaction to complete. The transaction will not be added to the blockchain. Note that the estimate may be significantly more than the amount of gas actually used by the transaction, for a variety of reasons including EVM mechanics and node performance.

Gas parameter is capped To prevent abuse of the API, thegas parameter in thiseth\_estimateGas method and inth\_call is capped at 10x (1000%) the current block gas limit. You can recreate this behavior in your local test environment (besu, geth, or other client) via the roc.gascap command-line option.

#### **Parameters**

	ANSACTION CALL OBJECT quired]	
•	• from	
•	· :[optional]	
•	20 Bytes - The address the transaction is sent from.	
•	o to	
•	20 Bytes - The address the transaction is directed to.	
•	o gas	
•	· :[optional]	
•	Hexadecimal value of the gas provided for the transaction execution.eth_estimateGas	
•	o consumes	
•	<ul> <li>zero gas, but this parameter may be needed by some executions.</li> </ul>	
•	gasPrice	
•	· :[optional]	
•	Hexadecimal value of the gas price used for each paid gas.	
•	• maxPriorityFeePerGas	
•	。:[optional]	
•	Maximum fee, in Wei, the sender is willing to pay per gas	
•	above the base fee.	
•	See <u>EIP-1559 transactions</u>	
•	• .	
•	• maxFeePerGas	
•	· :[optional]	
•	Maximum total fee (base fee + priority fee), in Wei, the sender is	
•	willing to pay per gas.	
•	• See <u>EIP-1559 transactions</u>	
•	• .	
•	o value	
•	。:[optional]	
•	Hexadecimal value of the value sent with this transaction.	
•	o data	
•	。:[optional]	
•	Hash of the method signature and encoded parameters. See th€thereum contract ABI specification	
•	• .	
•	blockParameter	
•	。: (string) [required	
•	] A hexadecimal block number, or one of the tagslatest	
•	• ,earliest	
•	· ,pending	
•	orfinalized	
•	See thedefault block parameter	
•	• .	
•	• warning	
•	o safe	
•	o isn't supported. Usefinalized	
•	• instead.	

If no gas limit is specified, geth uses the block gas limit from the pending block as an upper bound. As a result the returned estimate might not be enough to executed the call/transaction when the amount of gas is higher than the pending block gas limit.

## Returns

A hexadecimal of the estimate of the gas for the given transaction.

If this call causes the EVM to execute aREVERT operation, an error response of the following form is returned, with the revert reason pre-decoded as a string:

# Example

ReplaceYOUR-API-KEY with an API key from yourInfura dashboard .

## Request

- cURL WSS

 $curl \ https://scroll-mainnet.infura.io/v3/ \ -X \ POST \ -H \ "Content-Type: application/json" \ -d \ "["jsonrpc": "2.0", "method": "eth_estimateGas", "params": [["from": "0x9cE564c7d09f88E7d8233Cdd3Add7AC42aBFf3aC", "to": "0x46e8dd67c5d32be8058bb8eb970870f07244567", "value": "0x9184e72a"]], "id": 1]' wscat -c wss://scroll-mainnet.infura.io/ws/v3/ -x \ "["jsonrpc": "2.0", "method": "eth_estimateGas", "params": [["from": "0x9cE564c7d09f88E7d8233Cdd3Add7AC42aBFf3aC", "to": "0xd46e8dd67c5d32be8058bb8eb970870f07244567", "value": "0x9184e72a"]], "id": 1]' \ "0x9184e72a"]], "id": 1]' \ "0x9184e72a"]], "id": 1]' \ "0x9184e72a"], "id": 1]$ 

### Response

• JSON

{ "jsonrpc" :

"2.0", "id":

1 , "result" :

"0x5cec" }

Last updatedonNov 5, 2024 Previous eth\_chainId Next eth\_feeHistory