

useCreateSession

[@biconomy/use-aa](#) • Hook

[@biconomy/use-aa](#) / useCreateSession

Description

Creates a session to be used when submitting tx in the context of a users smart account.

Parameters

```
type
SessionEpoch
=
{ /* The time at which the session is no longer valid/ validUntil ? :
number ; /* The time at which the session becomes valid/ validAfter ? :
number ; } ;
type
Policy
=
{ / The address of the contract to be included in the policy */ contractAddress : Hex ; The address of the sessionKey
upon which the policy is to be imparted / sessionKeyAddress : Hex ; /The specific function selector from the contract to be
included in the policy / functionSelector :
string
| AbiFunction ; /The rules to be included in the policy */ rules : Rule [ ] ; / The time interval within which the session is
valid. If left unset the session will remain invalid indefinitely / interval ? : SessionEpoch ; /The maximum value that can be
transferred in a single transaction / valueLimit : bigint ; } ;
type
UseCreateSessionProps
=
{ / The array of policy elements to be applied to the session. */ policy : Policy [ ] ; The BuildUserOpOptions options.
See https://bcnmy.github.io/biconomy-client-sdk/types/BuildUserOpOptions.html for further detail */ options ? :
BuildUserOpOptions ; } ;
```

Returns

[userOpReceipt](#)

```
type
UserOpResponse
=
{ userOpHash :
string ; wait ( _confirmations ? :
number ) :
Promise < UserOpReceipt
; waitForTxHash ( ) :
```

Promise < UserOpStatus

; };

Example

```
import
{ useCreateSession , useUserOpWait ,
Options
}
from
"@biconomy/useAA" ; import
{ polygonAmoy }
from
"viem/chains" ; import
{ encodeFunctionData , parseAbi }
from
"wagmi" ;
const
CreateSession
=
( { userSmartAccountAddress } )
=>
{ const policy =
[ { contractAddress :
"0x1758f42Af7026fBbB559Dc60EcE0De3ef81f665e" , functionSelector :
"safeMint(address)" , rules :
[ { offset :
0 , condition :
0 , referenceValue : userSmartAccountAddress , } , ] , interval :
{ validUntil :
0 , validAfter :
0 , } , valueLimit :
0n , } , ] ;
const
{ mutate , data : userOpResponse , error , isPending }
=
useCreateSession ( ) ;
const
{ isLoading : waitIsLoading , isSuccess : waitIsSuccess , error : waitError , data : waitData , }
```

```

=
useUserOpWait ( userOpResponse ) ;
useEffect ( ( )
=>
{ if
( waitIsSuccess && waitData ?. success ===
"true" )
{ console . log ( "Successful mint: "
+ { polygonAmoy . blockExplorers . default . url } /tx/ { waitData ?. receipt ?. transactionHash } ) ; } } ,
[ waitIsSuccess ] ) ;
const
createSessionHandler
=
( )
=> mutate ( { policy , options :
Options . Sponsored , } ) ;
return
( < ErrorGuard

```

errors

```

{ [ error , waitError ] }

< Button title = " Create a session " onClickFunc = { createSessionHandler } isLoading = { isPending ||
waitIsLoading } /> </ ErrorGuard

) ; } ;

```

Source

[hooks/useCreateSession.ts:97](#) [Previous useCreateBatchSession](#) [Next useDeploySmartAccount](#)