

Namespace: v0_10_0

Interfaces

- [AppDataRootSchema](#)
- [CoWHook](#)
- [Metadata](#)
- [OrderClass](#)
- [OrderInteractionHooks](#)
- [Quote](#)
- [Referrer](#)
- [UTMCodes](#)

Type Aliases

AppCode

TAppCode :string

The code identifying the CLI, UI, service generating the order.

Defined in

generatedTypes/v0.10.0.ts:15

Environment

TEnvironment :string

Environment from which the order came from.

Defined in

generatedTypes/v0.10.0.ts:19

HookCallData

THookCallData :string

The calldata to use when calling the hook

Defined in

generatedTypes/v0.10.0.ts:64

HookGasLimit

THookGasLimit :string

The gas limit (in gas units) for the hook

Defined in

generatedTypes/v0.10.0.ts:68

HookTarget

THookTarget :string

The contract to call for the hook

Defined in

generatedTypes/v0.10.0.ts:60

OrderClass1

TOrderClass1 : "market" | "limit" | "liquidity" | "twap"

Indicator of the order class.

Defined in

generatedTypes/v0.10.0.ts:52

PostHooks

TPostHooks : [CoWHook](#) []

CoW Hooks to call after an order executes

Defined in

generatedTypes/v0.10.0.ts:76

PreHooks

TPreHooks : [CoWHook](#) []

CoW Hooks to call before an order executes

Defined in

generatedTypes/v0.10.0.ts:72

ReferrerAddress

TReferrerAddress :string

Defined in

generatedTypes/v0.10.0.ts:24

Signer

TSigner :string

The address of the trader who signs the CoW Swap order. This field should normally be omitted; it is recommended to use it if the signer is a smart-contract wallet using EIP-1271 signatures.

Defined in

generatedTypes/v0.10.0.ts:23

SlippageBips

TSlippageBips :string

Slippage tolerance that was applied to the order to get the limit price. Expressed in Basis Points (BPS)

Defined in

generatedTypes/v0.10.0.ts:48

UTMCampaign

TUTMCampaign :string

Track the performance of a specific campaign

Defined in

generatedTypes/v0.10.0.ts:36

UTMContent

TUTMContent :string

Track which link was clicked

Defined in

generatedTypes/v0.10.0.ts:40

UTMKeywordTerm

TUTMKeywordTerm :string

Track which keyword term a website visitor came from

Defined in

generatedTypes/v0.10.0.ts:44

UTMMedium

TUTMMedium :string

Tracks in which medium the traffic originated from (mail, CPC, social, etc.)

Defined in

generatedTypes/v0.10.0.ts:32

UTMSource

TUTMSource :string

Tracks in which medium the traffic originated from (twitter, facebook, etc.)

Defined in

generatedTypes/v0.10.0.ts:28

Version

TVersion :string

Semantic versioning of document.

Defined in

generatedTypes/v0.10.0.ts:11

Version1

TVersion1 :string

Semantic versioning of document.

Defined in

generatedTypes/v0.10.0.ts:56 [Previous](#) [latest](#) [Next](#) [v0_11_0](#)