admin namespace

admin_addPeer

Adds given node.

- Parameters
- Request
- Response
- enode
- · :string
- addToStaticNodes
- :boolean curl localhost:8545 \ -X POST \ -H

```
"Content-Type: application/json"
\ --data

'{ "jsonrpc": "2.0", "id": 0, "method": "admin_addPeer", "params": [enode, addToStaticNo
```

```
'{ "jsonrpc": "2.0", "id": 0, "method": "admin_addPeer", "params": [enode, addToStaticNodes] }' Added node { "jsonrpc" : "2.0" , "id" : 0 , "result" : result } result : string
```

admin_nodeInfo

Displays relevant information about this node.

- Request
- Response

```
curl localhost:8545 \ -X POST \ -H
```

```
"Content-Type: application/json"
```

```
\ --data
```

```
'{ "jsonrpc": "2.0", "id": 0, "method": "admin_nodeInfo", "params": [] }' Information about this node { "jsonrpc" : "2.0" , "id" :
```

- 0 , "result" : result } result :object
 - enode
 - :string
 - id
 - · :string
 - ip
 - string
 - listenAddress
 - string
 - name
 - · :string
 - ports
 - · :object
 - •
- discovery
- :string
- - (hex integer)
- listener

- · :string (hex integer) protocols : map ofobject difficulty string • (hex integer) genesisHash · :string • (hash) headHash · :string • (hash) newtorkld string • (hex integer) admin_peers Displays a list of connected peers including information about them (clientId ,host ,port ,address ,isBootnode ,isStatic ,enode Parameters Request • Response · includeDetails • :boolean curl localhost:8545 \ -X POST \ -H "Content-Type: application/json" \ --data '{ "jsonrpc": "2.0", "id": 0, "method": "admin_peers", "params": [includeDetails] }' List of connected peers including information { "jsonrpc" : "2.0", "id": 0, "result": result } result: array ofobject address string · clientId · :string clientType · :string • enode
 - · :string host

).

· :string

· :string · ethDetails

isBootnode

- :boolean
- isStatic
- :boolean
- isTrusted
- :boolean
- lastSignal
- :string
- port
- · :string
- (hex integer)

admin_prune

Runs full pruning if enabled.

- Request
- Response

```
curl localhost:8545 \ -X POST \ -H
"Content-Type: application/json"
```

```
\ --data
'{ "jsonrpc": "2.0", "id": 0, "method": "admin_prune", "params": [] }' { "jsonrpc" : "2.0", "id" :
```

0 , "result" : result } result :integer

admin_removePeer

Removes given node.

- Parameters
- Request
- Response
- enode
- · :string
- removeFromStaticNodes
- :boolean curl localhost:8545 \ -X POST \ -H

```
"Content-Type: application/json"
```

```
\ --data
```

```
'{ "jsonrpc": "2.0", "id": 0, "method": "admin_removePeer", "params": [enode, removeFromStaticNodes] }' Removed node { "jsonrpc" : "2.0", "id" :
```

0, "result": result } result : stringEdit this page Last updatedonMar 26, 2024 Previous JSON-RPC server Next clique