

## seid tx gov submit-proposal

Submit a proposal along with an initial deposit. Proposal title, description, type and deposit can be given directly or through a proposal JSON file.

Example: `tx gov submit-proposal --proposal="path/to/proposal.json" --from mykey`

Where `proposal.json` contains:

```
{ "title": "Test Proposal", "description": "My awesome proposal", "is_expedited": false, "type": "Text", "deposit": "10test" }
```

Which is equivalent to:

```
tx gov submit-proposal --title="Test Proposal" --description="My awesome proposal" --type="Text" --deposit="10test" --is-expedited=false --from mykey
```

Usage: `seid tx gov submit-proposal [flags] seid tx gov submit-proposal [command]`

Available Commands: `cancel-software-upgrade` Cancel the current software upgrade proposal `clear-contract-admin` Submit a clear admin for a contract to prevent further migrations proposal `community-pool-spend` Submit a community pool spend proposal `execute-contract` Submit a execute wasm contract proposal (run by any address) `ibc-upgrade` Submit an IBC upgrade proposal `instantiate-contract` Submit an instantiate wasm contract proposal `migrate-contract` Submit a migrate wasm contract to a new code version proposal `param-change` Submit a parameter change proposal `pin-codes` Submit a pin code proposal for pinning a code to cache `set-contract-admin` Submit a new admin for a contract proposal `software-upgrade` Submit a software upgrade proposal `sudo-contract` Submit a sudo wasm contract proposal (to call privileged commands) `unpin-codes` Submit a unpin code proposal for unpinning a code to cache `update-client` Submit an update IBC client proposal `update-instantiate-config` Submit an update instantiate config proposal. `update-minter` Submit an UpdateMinter proposal `update-resource-dependency-mapping` Submit an UpdateResourceDependencyMapping proposal `wasm-store` Submit a wasm binary proposal

Flags: `-a, --account-number uint` The account number of the signing account (offline mode only) `-b, --broadcast-mode string` Transaction broadcasting mode (sync|async|block) (default "sync") `--deposit string` The proposal deposit `--description string` The proposal description `--dry-run` ignore the `--gas` flag and perform a simulation of a transaction, but don't broadcast it (when enabled, the local Keybase is not accessible) `--fee-account string` Fee account pays fees for the transaction instead of deducting from the signer `--fees string` Fees to pay along with transaction; eg: 10uatom `--from string` Name or address of private key with which to sign `--gas string` gas limit to set per-transaction; set to "auto" to calculate sufficient gas automatically (default 200000) `--gas-adjustment float` adjustment factor to be multiplied against the estimate returned by the tx simulation; if the gas limit is set manually this flag is ignored (default 1) `--gas-prices string` Gas prices in decimal format to determine the transaction fee (e.g. 0.1uatom) `--generate-only` Build an unsigned transaction and write it to STDOUT (when enabled, the local Keybase only accessed when providing a key name) `-h, --help` help for submit-proposal `--keyring-backend string` Select keyring's backend (os|file|kwallet|pass|test|memory) (default "os") `--keyring-dir string` The client Keyring directory; if omitted, the default 'home' directory will be used `--ledger` Use a connected Ledger device `--node string` : to tendermint rpc interface for this chain (default "tcp://localhost:26657") `--note string` Note to add a description to the transaction (previously `--memo`) `--offline` Offline mode (does not allow any online functionality) `-o, --output string` Output format (text|json) (default "json") `--proposal string` Proposal file path (if this path is given, other proposal flags are ignored) `-s, --sequence uint` The sequence number of the signing account (offline mode only) `--sign-mode string` Choose sign mode (direct|amino-json), this is an advanced feature `--timeout-height uint` Set a block timeout height to prevent the tx from being committed past a certain height `--title string` The proposal title `--type string` The proposal Type `-y, --yes` Skip tx broadcasting prompt confirmation

Global Flags: `--chain-id string` The network chain ID `--home string` directory for config and data (default "~/sei") `--log_format string` The logging format (json|plain) `--log_level string` The logging level (trace|debug|info|warn|error|fatal|panic) `--trace` print out full stack trace on errors

Use "`seid tx gov submit-proposal [command] --help`" for more information about a command. Last updated on July 1, 2024  
[deposit](#) [cancel-software-upgrade](#)