

## eth\_getUncleByBlockHashAndIndex

Returns information about a uncle of a block given the block hash and the uncle index position.

## Parameters

- block hash
- : [Required]
- ] A string representing the hash (32 bytes) of a block.
- uncle index position
- : [Required]
- ] A hexadecimal equivalent of the integer indicating the uncle's index position.

## Returns

A block object, or null when no block was found. The block object returned will consist of the following keys and their values:

- number
  - : The block number.Null
- when the returned block is the pending block.
- hash
  - : 32 bytes. Hash of the block.Null
- when its pending block.
- parentHash
  - : 32 bytes. Hash of the parent block.
- nonce
  - : 8 bytes. Hash of the generated proof-of-work.Null
- when the returned block is the pending block.
- sha3Uncles
  - : 32 bytes. The SHA3 of the uncles data in the block.
- logsBloom
  - : 256 bytes. The Bloom filter for the logs of the block.Null
- when the returned block is the pending block.
- transactionsRoot
  - : 32 bytes. The root of the transaction trie of the block.
- stateRoot
  - : 32 bytes. The root of the final state trie of the block.
- receiptsRoot
  - : 32 bytes. The root of the receipts trie of the block.
- miner
  - : 20 bytes. The address of the beneficiary to whom the mining rewards were given.
- difficulty
  - : The hexadecimal of the difficulty for this block.
- totalDifficulty
  - : The hexadecimal of the total difficulty of the chain until this block.
- extraData
  - : The "extra data" field of this block.
- size
  - : The hexadecimal of the size of this block in bytes.
- gasLimit
  - : Maximum gas allowed in this block.
- gasUsed
  - : Total used gas by all transactions in this block.
- timestamp
  - : The unix timestamp for when the block was collated.
- uncles
  - : (Array). An array of uncle hashes.

## Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#).

## Request

- cURL
- WSS

```
curl https://bsc-mainnet.infura.io/v3/YOUR-API-KEY-X POST -H 'Content-Type: application/json' -d '{"jsonrpc": "2.0", "method": "eth_getUncleByBlockHashAndIndex", "params": ["0xb3206248f0f8665d0d4688409e5cea4bd02700bf6e79e9384d7d6a5a35", "0x0"], "id": 1}' -wscat -c wss://bsc-mainnet.infura.io/ws/v3/YOUR-API-KEY-X '{"jsonrpc": "2.0", "method": "eth_getUncleByBlockHashAndIndex", "params": ["0xb3206248f0f8665d0d4688409e5cea4bd02700bf6e79e9384d7d6a5a35", "0x0"], "id": 1}'
```

## Response

- JSON

[illegible]

Last updated on Nov 5, 2024 [Previous](#) [eth\\_getTransactionReceipt](#) [Next](#) [eth\\_getUncleByBlockNumberAndIndex](#)