

# Rollup Configuration

New OP Stack blockchains are currently configured with a JSON file inside the Optimism repository. You can see example configurations in the [deploy-config directory\(opens in a new tab\)](#).

⚠ The Rollup configuration is an active work in progress and will likely evolve significantly as time goes on. If something isn't working about your configuration, you can refer to the [source code\(opens in a new tab\)](#). Standard configuration is the set of requirements for an OP Stack chain to be considered a Standard Chain within the superchain. These requirements are currently a draft, pending governance approval. For more details, please see this [governance thread\(opens in a new tab\)](#).

## Configuration Values

### Offset Values

These offset values determine when network upgrades (hardforks) activate on your blockchain.

#### L2GenesisRegolithTimeOffset

L2GenesisRegolithTimeOffset is the number of seconds after genesis block that Regolith hard fork activates. Set it to 0 to activate at genesis. Nil to disable Regolith.

- Type:
- Number of seconds
- Default:
- nil

#### L2GenesisCanyonTimeOffset

L2GenesisCanyonTimeOffset is the number of seconds after genesis block that Canyon hard fork activates. Set it to 0 to activate at genesis. Nil to disable Canyon.

- Type:
- Number of seconds
- Default:
- nil

#### L2GenesisDeltaTimeOffset

L2GenesisDeltaTimeOffset is the number of seconds after genesis block that Delta hard fork activates. Set it to 0 to activate at genesis. Nil to disable Delta.

- Type:
- Number of seconds
- Default:
- nil

#### L2GenesisEcotoneTimeOffset

L2GenesisEcotoneTimeOffset is the number of seconds after genesis block that Ecotone hard fork activates. Set it to 0 to activate at genesis. Nil to disable Ecotone.

- Type:
- Number of seconds
- Default:
- nil

#### L2GenesisFjordTimeOffset

L2GenesisFjordTimeOffset is the number of seconds after genesis block that Fjord hard fork activates. Set it to 0 to activate at genesis. Nil to disable Fjord.

- Type:
- Number of seconds
- Default:
- nil

## **L2GenesisInteropTimeOffset**

L2GenesisInteropTimeOffset is the number of seconds after genesis block that the Interop hard fork activates. Set it to 0 to activate at genesis. Nil to disable Interop.

- Type:
- Number of seconds
- Default:
- nil

## **L1CancunTimeOffset**

When Cancun activates. Relative to L1 genesis.

- Type:
- Number of seconds
- Default:
- None

## **Admin addresses**

### **finalSystemOwner**

FinalSystemOwner is the L1 system owner. It owns any ownable L1 contracts.

- Type:
- L1 Address
- Default value:
- None
- Recommended value:
- It is recommended to have a single admin address to retain a common security model.
- Notes:
- Must not beaddress(0)

### **proxyAdminOwner**

ProxyAdmin contract owner on the L2, which owns all of the Proxy contracts for every predeployed contract in the range 0x42...0000 to 0x42...2048 . This makes predeployed contracts easily upgradeable.

- Type:
- L2 Address
- Default value:
- None
- Recommended value:
- It is recommended to have a single admin address to retain a common security model.
- Notes:
- Must not beaddress(0)

## **Proxy Addresses**

### **L1StandardBridgeProxy**

L1StandardBridgeProxy represents the address of the L1StandardBridgeProxy on L1 and is used as part of building the L2 genesis state.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not beaddress(0)

### **L1CrossDomainMessengerProxy**

L1CrossDomainMessengerProxy represents the address of the L1CrossDomainMessengerProxy on L1 and is used as part of building the L2 genesis state.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not beaddress(0)

### **L1ERC721BridgeProxy**

L1ERC721BridgeProxy represents the address of the L1ERC721Bridge on L1 and is used as part of building the L2 genesis state.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not beaddress(0)

### **systemConfigProxy**

SystemConfigProxy represents the address of the SystemConfigProxy on L1 and is used as part of the derivation pipeline.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not beaddress(0)

### **optimismPortalProxy**

OptimismPortalProxy represents the address of the OptimismPortalProxy on L1 and is used as part of the derivation pipeline.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not beaddress(0)

## **Blocks**

These fields apply to L2 blocks: Their timing, when they need to be written to L1, and how they get written.

### **L2BlockTime**

Number of seconds between each L2 block. Must be  $\leq$  L1 block time (12 on mainnet and Sepolia).

- Type:
- Number of seconds
- Default value:
- None
- Notes:
- Must not be0
- . Must be less than the L1 blocktime and a whole number.
- Standard Config Requirement:
- 2 seconds. High security and interoperability compatibility requirement, until de-risked/solved at app layer.

### **maxSequencerDrift**

How far the L2 timestamp can differ from the actual L1 timestamp.

- Type:
- Number of seconds

- Default value:
- None
- Notes:
- Must not be 0
- . 1800 (30 minutes) is the constant that takes effect with the [Fjord activation](#)
- .

### **sequencerWindowSize**

Maximum number of L1 blocks that a Sequencer can wait to incorporate the information in a specific L1 block. For example, if the window is 10 then the information in L1 block n must be incorporated by L1 block n+10.

- Type:
- Number of blocks
- Default value:
- None
- \*Notes:
- Must not be 0
- . 3600 (12 hours) is suggested.
- Standard Config Requirement:
- 3\_600 base layer blocks (12 hours for an L2 on Ethereum, assuming 12 second L1 blocktime). This is an important value for constraining the sequencer's ability to re-order transactions; higher values would pose a risk to user protections.

### **channelTimeout**

Maximum number of L1 blocks that a transaction channel frame can be considered valid. A transaction channel frame is a chunk of a compressed batch of transactions. After the timeout, the frame is dropped.

- Type:
- Number of blocks
- Default value:
- None
- Notes:
- 300 (1 hour) is suggested

### **p2pSequencerAddress**

Address of the key that the Sequencer uses to sign blocks on the p2p network.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Sequencer, an address for which you own the private key

### **batchInboxAddress**

Address that Sequencer transaction batches are sent to on L1.

- Type:
- L1 Address
- Default value:
- None
- Standard Config Requirement:
- Current convention is 0xff000...000{chainId}
- .

### **batchSenderAddress**

Address that nodes will filter for when searching for Sequencer transaction batches being sent to the batchInboxAddress. Can be updated later via the SystemConfig contract on L1.

- Type:
- L1 Address

- Default value:
- Batchers, an address for which you own the private key.
- Notes:
- Must not be address(0)

## systemConfigStartBlock

SystemConfigStartBlock represents the block at which the op-node should start syncing from. It is an override to set this value on legacy networks where it is not set by default. It can be removed once all networks have this value set in their storage.

- Type:
- L2 Block Number
- Default value:
- None
- Standard Config Requirement:
- The block where the SystemConfig was initialized.

## Chain Information

### I1StartingBlockTag

Block tag for the L1 block where the L2 chain will begin syncing from. It is generally recommended to use a finalized block to avoid issues with reorgs.

- Type:
- Block hash
- Default value:
- None
- \*Notes:
- Must not be 0
- .

### I1ChainID

Chain ID of the L1 chain.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Must not be 0
- . 1 for L1 Ethereum mainnet, 11155111 for the Sepolia test network, and See [here\(opens in a new tab\)](#) for other blockchains.

### I2ChainID

Chain ID of the L2 chain.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Must not be 0
- . For security reasons, should be unique.
- Standard Config Requirement:
- Foundation-approved, globally unique value

### I2GenesisBlockExtraData

L2GenesisBlockExtraData is configurable extradata. Will default to []byte("BEDROCK") if left unspecified.

- Type:
- Number

- Default value:
- []byte("BEDROCK")

### **superchainConfigGuardian**

SuperchainConfigGuardian represents the GUARDIAN account in the SuperchainConfig. Has the ability to pause withdrawals.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not beaddress(0)

### **Gas**

- Standard Config Requirement:
- Set such that Fee Margin is between 0 and 50%.
- Standard Config Requirement:
- No higher than 200\_000\_000 gas. Chain operators are driven to maintain a stable and reliable chain. When considering a change to this value, careful deliberation is necessary.

### **eip1559Elasticity**

EIP1559Elasticity is the elasticity of the EIP1559 fee market.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Must not be0
- .

### **eip1559Denominator**

EIP1559Denominator is the denominator of EIP1559 base fee market.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Must not be0
- .

### **eip1559DenominatorCanyon**

EIP1559DenominatorCanyon is the denominator of EIP1559 base fee market when Canyon is active.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Must not be0
- if Canyon is activated.

### **gasPriceOracleBaseFeeScalar**

GasPriceOracleBaseFeeScalar represents the value of the base fee scalar used for fee calculations.

- Type:
- Number
- Default value:

- None
- \*Notes:
- Should not be 0
- .

### **gasPriceOracleBlobBaseFeeScalar**

GasPriceOracleBlobBaseFeeScalar represents the value of the blob base fee scalar used for fee calculations.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Should not be 0
- .

## **Proposal Fields**

These fields apply to output root proposals. The `I2OutputOracleSubmissionInterval` is configurable, see the section below for guidance.

### **I2OutputOracleStartingBlockNumber**

Block number of the first OP Stack block. Typically this should be zero, but this may be non-zero for networks that have been upgraded from a legacy system (like OP Mainnet). Will be removed with the addition of permissionless proposals.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Should be 0
- for new chains.

### **I2OutputOracleStartingTimestamp**

Timestamp of the first OP Stack block. This **MUST** be the timestamp corresponding to the block defined by the `I1StartingBlockTag`. Will be removed with the addition of permissionless proposals.

- Type:
- Number
- Default value:
- None
- \*Notes:
- This **MUST** be the timestamp corresponding to the block defined by
- the `I1StartingBlockTag`.

### **I2OutputOracleSubmissionInterval**

Number of blocks between proposals to the `L2OutputOracle`. Will be removed with the addition of permissionless proposals.

- Type:
- Number of blocks
- Default value:
- None
- \*Notes:
- Must not be 0
- . 120 (4 minutes) is suggested.

### **finalizationPeriodSeconds**

Number of seconds that a proposal must be available to challenge before it is considered finalized by the `OptimismPortal` contract.

- Type:
- Number of seconds
- Default value:

- None
- \*Notes:
- Must not be 0
- . Recommend 12 on test networks, seven days on production ones.
- Standard Config Requirement:
- 7 days. High security. Excessively safe
- upper bound that leaves enough time to consider social layer solutions to a
- hack if necessary. Allows enough time for other network participants to
- challenge the integrity of the corresponding output root.

### **L2OutputOracleProposer**

Address that is allowed to submit output proposals to the L2OutputOracle contract. Will be removed when the OP Stack has permissionless proposals.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not be address(0)

### **L2OutputOracleChallenger**

Address that is allowed to challenge output proposals submitted to the L2OutputOracle. Will be removed when the OP Stack has permissionless challenges.

- Type:
- L1 Address
- Default value:
- None
- Notes:
- Must not be address(0)
- . It is recommended to have a single admin
- address to retain a common security model.

## **Fee recipients**

### **baseFeeVaultRecipient**

BaseFeeVaultRecipient represents the recipient of fees accumulated in the BaseFeeVault. Can be an account on L1 or L2, depending on the BaseFeeVaultWithdrawalNetwork value.

- Type:
- L1 or L2 Address
- Default value:
- None
- Notes:
- Must not be address(0)
- . It is recommended to have a single admin
- address to retain a common security model.

### **L1FeeVaultRecipient**

L1FeeVaultRecipient represents the recipient of fees accumulated in the L1FeeVault. Can be an account on L1 or L2, depending on the L1FeeVaultWithdrawalNetwork value.

- Type:
- L1 or L2 Address
- Default value:
- None
- Notes:
- Must not be address(0)
- . It is recommended to have a single admin
- address to retain a common security model.

### **sequencerFeeVaultRecipient**



SequencerFeeVaultRecipient represents the recipient of fees accumulated in the SequencerFeeVault. Can be an account on L1 or L2, depending on the SequencerFeeVaultWithdrawalNetwork value.

- Type:
- L1 or L2 Address
- Default value:
- None
- Notes:
- Must not be address(0)
- . It is recommended to have a single admin
- address to retain a common security model.

## Minimum Fee Withdrawal Amounts

Withdrawals to L1 are expensive and the minimum fee is to prevent overhead costs of continuous tiny withdrawals. If the withdrawal execution costs more than the fee-reward, then the fee Must not be collected economically.

### baseFeeVaultMinimumWithdrawalAmount

BaseFeeVaultMinimumWithdrawalAmount represents the minimum withdrawal amount for the BaseFeeVault.

- Type:
- Number in wei
- Default value:
- None

### L1FeeVaultMinimumWithdrawalAmount

L1FeeVaultMinimumWithdrawalAmount represents the minimum withdrawal amount for the L1FeeVault.

- Type:
- Number in wei
- Default value:
- None

### sequencerFeeVaultWithdrawalAmount

SequencerFeeVaultMinimumWithdrawalAmount represents the minimum withdrawal amount for the SequencerFeeVault.

- Type:
- Number in wei
- Default value:
- None

## Withdrawal Network

### baseFeeVaultWithdrawalNetwork

BaseFeeVaultWithdrawalNetwork represents the withdrawal network for the BaseFeeVault. value of 0 will withdraw ETH to the recipient address on L1 and a value of 1 will withdraw ETH to the recipient address on L2.

- Type:
- Number representing network enum
- Default value:
- None
- Notes:
- Withdrawals to Ethereum are more expensive.

### L1FeeVaultWithdrawalNetwork

L1FeeVaultWithdrawalNetwork represents the withdrawal network for the L1FeeVault. A value of 0 will withdraw ETH to the recipient address on L1 and a value of 1 will withdraw ETH to the recipient address on L2.

- Type:
- Number representing network enum
- Default value:
- None
- Notes:

- Withdrawals to Ethereum are more expensive.

### **sequencerFeeVaultWithdrawalNetwork**

SequencerFeeVaultWithdrawalNetwork represents the withdrawal network for the SequencerFeeVault. A value of 0 will withdraw ETH to the recipient address on L1 and a value of 1 will withdraw ETH to the recipient address on L2.

- Type:
- Number representing network enum
- Default value:
- None
- Notes:
- Withdrawals to Ethereum are more expensive.

## **Fault Proofs**

### **faultGameAbsolutePrestate**

FaultGameAbsolutePrestate is the absolute prestate of Cannon. This is computed by generating a proof from the 0th -> 1st instruction and grabbing the prestate from the output JSON. All honest challengers should agree on the setup state of the program.

- Type:
- Hash
- Default value:
- None

### **faultGameMaxDepth**

FaultGameMaxDepth is the maximum depth of the position tree within the fault dispute game.  $2^{\text{FaultGameMaxDepth}}$  is how many instructions the execution trace bisection game supports. Ideally, this should be conservatively set so that there is always enough room for a full Cannon trace.

- Type:
- Number
- Default value:
- None

### **faultGameClockExtension**

FaultGameClockExtension is the amount of time that the dispute game will set the potential grandchild claim's, clock to, if the remaining time is less than this value at the time of a claim's creation.

- Type:
- Number
- Default value:
- None

### **faultGameMaxClockDuration**

FaultGameMaxClockDuration is the maximum amount of time that may accumulate on a team's chess clock before they may no longer respond.

- Type:
- Number
- Default value:
- None

### **faultGameGenesisBlock**

FaultGameGenesisBlock is the block number for genesis.

- Type:
- Number
- Default value:
- None

### **faultGameGenesisOutputRoot**

FaultGameGenesisOutputRoot is the output root for the genesis block.

- Type:
- Hash
- Default value:
- None

### **faultGameSplitDepth**

FaultGameSplitDepth is the depth at which the fault dispute game splits from output roots to execution trace claims.

- Type:
- Number
- Default value:
- None

### **faultGameWithdrawalDelay**

FaultGameWithdrawalDelay is the number of seconds that users must wait before withdrawing ETH from a fault game.

- Type:
- Number
- Default value:
- None

### **preimageOracleMinProposalSize**

PreimageOracleMinProposalSize is the minimum number of bytes that a large preimage oracle proposal can be.

- Type:
- Number
- Default value:
- None

### **preimageOracleChallengePeriod**

PreimageOracleChallengePeriod is the number of seconds that challengers have to challenge a large preimage proposal.

- Type:
- Number of Seconds
- Default value:
- None

### **proofMaturityDelaySeconds**

ProofMaturityDelaySeconds is the number of seconds that a proof must be mature before it can be used to finalize a withdrawal.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Should not be 0
- .

### **disputeGameFinalityDelaySeconds**

DisputeGameFinalityDelaySeconds is an additional number of seconds a dispute game must wait before it can be used to finalize a withdrawal.

- Type:
- Number
- Default value:
- None
- \*Notes:
- Should not be 0
- .

## **respectedGameType**

RespectedGameType is the dispute game type that the OptimismPortal contract will respect for finalizing withdrawals.

- Type:
- Number
- Default value:
- None

## **useFaultProofs**

UseFaultProofs is a flag that indicates if the system is using fault proofs instead of the older output oracle mechanism.

- Type:
- Boolean
- Default value:
- None
- \*Notes:
- You should understand the implications of running a Fault Proof chain.

## **Custom Gas Token**

### **useCustomGasToken**

UseCustomGasToken is a flag to indicate that a custom gas token should be used.

- Type:
- boolean
- Default value:
- None

### **customGasTokenAddress**

CustomGasTokenAddress is the address of the ERC20 token to be used to pay for gas on L2.

- Type:
- Address
- Default value:
- None
- Notes:
- Must not be address(0)
- .

## **Alt-DA Mode / Plasma Mode**

### **usePlasma**

UsePlasma is a flag that indicates if the system is using op-plasma

- Type:
- bool
- Default value:
- None
- Notes:

### **daCommitmentType**

DACommitmentType specifies the allowed commitment

- Type:
- string
- Default value:
- None
- Notes:
- DACommitmentType must be either KeccakCommitment or GenericCommitment

## **daChallengeWindow**

DACheckWindow represents the block interval during which the availability of a data commitment can be challenged.

- Type:
- Number
- Default value:
- None
- Notes:
- DACheckWindow must not be 0 when using plasma mode

## **daResolveWindow**

DAResolveWindow represents the block interval during which a data availability challenge can be resolved.

- Type:
- Number
- Default value:
- None
- Notes:
- DACheckWindow must no be 0 when using plasma mode

## **daBondSize**

DABondSize represents the required bond size to initiate a data availability challenge.

- Type:
- Number
- Default value:
- None

## **daResolverRefundPercentage**

DAResolverRefundPercentage represents the percentage of the resolving cost to be refunded to the resolver such as 100 means 100% refund.

- Type:
- Number
- Default value:
- None

## **daChallengeProxy**

DACheckProxy represents the L1 address of the DataAvailabilityChallenge contract.

- Type:
- Address
- Default value:
- None
- Notes:
- Must not be address(0) when using plasma mode

## **Interoperability**

### **useInterop**

UseInterop is a flag that indicates if the system is using interop.

- Type:
- boolean
- Default value:
- None

## **Governance**

### **enableGovernance**

EnableGovernance determines whether to include governance token predeploy.

- Type:
- boolean
- Default value:
- None

### **governanceTokenSymbol**

GovernanceTokenSymbol represents the ERC20 symbol of the GovernanceToken.

- Type
- : string
- Default value:
- None

### **governanceTokenName**

GovernanceTokenName represents the ERC20 name of the GovernanceToken

- Type
- : string
- Default value:
- None

### **governanceTokenOwner**

GovernanceTokenOwner represents the owner of the GovernanceToken. Has the ability to mint and burn tokens.

- Type
- : L2 Address
- Default value:
- None

## **Miscellaneous**

### **fundDevAccounts**

FundDevAccounts determines whether to fund the dev accounts. Should only be used during devnet deployments.

- Type
- : Boolean

### **requiredProtocolVersion**

RequiredProtocolVersion indicates the protocol version that nodes are recommended to adopt, to stay in sync with the network.

- Type
- : String

### **recommendedProtocolVersion**

RecommendedProtocolVersion indicates the protocol version that nodes are recommended to adopt, to stay in sync with the network.

- Type
- : String

## **Deprecated**

### **(DEPRECATED**

) gasPriceOracleScalar

GasPriceOracleScalar represents the initial value of the gas scalar in the GasPriceOracle predeploy. Deprecated: Since Ecotone, this field is superseded by GasPriceOracleBaseFeeScalar and GasPriceOracleBlobBaseFeeScalar.

### **(DEPRECATED**

) gasPriceOracleOverhead

GasPriceOracleOverhead represents the initial value of the gas overhead in the GasPriceOracle predeploy. Deprecated: Since Ecotone, this field is superseded by GasPriceOracleBaseFeeScalar and GasPriceOracleBlobBaseFeeScalar.

**(DEPRECATED)**

) deploymentWaitConfirmations

DeploymentWaitConfirmations is the number of confirmations to wait during deployment. This is DEPRECATED and should be removed in a future PR.

**(DEPRECATED)**

) numDeployConfirmations

Number of confirmations to wait when deploying smart contracts to L1.

[Overview](#) [Batcher Configuration](#)