

# eth\_getTransactionByBlockNumberAndIndex

Returns information about a transaction given block number and transaction index position.

## Parameters

- block parameter
  - : [Required
  - ] A hexadecimal block number, or one of the string tags `latest`
  - , `earliest`
  - , `pending`
  - , `safe`
  - , `or finalized`
  - . See the [default block parameter](#)
  - .
- transaction index position
  - : [Required
  - ] A hexadecimal of the integer representing the position in the block.

## Returns

A transaction object, or null when no transaction was found. The transaction object will consist of the following keys and their values:

- `accessList`
  - : [optional
  - ] A list of addresses and storage keys accessed by the transaction. See [access list transactions](#)
  - .
- `blockHash`
  - : 32 bytes. A hash of the block including this transaction. null
  - when it's pending.
- `blockNumber`
  - : The number of the block including this transaction. null
  - when it's pending.
- `chainID`
  - : [optional
  - ] chain ID specifying the network. Returned only for [EIP-1559 transactions](#)
  - .
- `from`
  - : 20 bytes. The address of the sender.
- `gas`
  - : Gas provided by the sender.
- `gasPrice`
  - : Gas price provided by the sender in Wei.
- `hash`
  - : 32 bytes. The hash of the transaction.
- `input`
  - : The data sent along with the transaction.
- `maxPriorityFeePerGas`
  - : [optional
  - ] Maximum fee, in Wei, the sender is willing to pay per gas above the base fee. See [EIP-1559 transactions](#)
  - .
- `maxFeePerGas`
  - : [optional
  - ] Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas. See [EIP-1559 transactions](#)
  - .
- `nonce`
  - : The number of transactions made by the sender prior to this one.
- `r`
  - : 32 bytes. The ECDSA signaturer
  - .
- `s`
  - : 32 bytes. The ECDSA signatures
  - .
- `to`
  - : 20 bytes. The address of the receiver. null

- when it's a contract creation transaction.
- transactionIndex
- : The transaction's index position in the block, in hexadecimal.null
- when it's pending.
- type
- : The [transaction type](#)
- .
- v
- : The ECDSA recovery ID.
- value
- : The value transferred in Wei.
- yParity
- : [optional
- ] Parity (0x0
- for even,0x1
- for odd) of the y-value of [secp256k1](#)
- signature.

## Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#) .

### Request

- cURL
- WSS

```
curl https://mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d
'{"jsonrpc":"2.0","method":"eth_getTransactionByBlockNumberAndIndex","params":["0x5BAD55","0x0"],"id":1}' wscat -c
wss://mainnet.infura.io/ws/v3/YOUR-API-KEY -x
'{"jsonrpc":"2.0","method":"eth_getTransactionByBlockNumberAndIndex","params":["0x5BAD55","0x0"],"id":1}'
```

### Response

- JSON

```
{ "id" : 1, "jsonrpc" : "2.0", "result" : { "accessList":[],
"blockHash":"0x1682216b3a937e57aeb8c7fc64a8851ac9a5dd2407f7a76e01aad1ccc0aee19",
"blockNumber":"0x11dca94", "chainId":"0x1", "from":"0x1f9090aae28b8a3dceadf281b0f12828e676c326", "gas":"0x565f",
"gasPrice":"0xef8230501", "hash":"0x140fc3229057d6a484227cbcae16331f586310f68f2095dbc75b3af53d4874bd",
"input":"0x", "maxFeePerGas":"0xef8230501", "maxPriorityFeePerGas":"0x0", "nonce":"0x63b1f",
"r":"0x483a889fdbe4bcebd02fcef8b0644dd710de2b2b2f36f4762b90738016e5c639",
"s":"0x39efb4a71072e6585223e9e77e63920fa65f3de5091d510667782d4cd34ce0a4",
"to":"0x388c818ca8b9251b393131c08a736a67ccb19297", "transactionIndex":"0xa4", "type":"0x2", "v":"0x1",
"value":"0x12ff2241f48fc83", "yParity":"0x1" } }
```

Last updated on Apr 19, 2024 [Previous eth\\_getTransactionByBlockHashAndIndex](#) [Next eth\\_getTransactionByHash](#)