

Client Library API Reference

Integrate Chainlink CCIP into your project

npm yarn foundry If you use [NPM](#), install the [@chainlink/contracts-ccip NPM package](#) and set it to the v1.4.0 release:

npm install @chainlink/ If you use [Yarn](#), install the [@chainlink/contracts-ccip NPM package](#) and set it to the v1.4.0 release:

yarn add @chainlink/ If you use [Foundry](#), install the v1.4.0 release:

forge install smartcontractkit/ccip@b06a3c2eecb9892ec6f76a015624413ffa1a122

CCIP senders and receivers use the CCIP Client Library to build CCIP messages.

```
import { Client } from "@chainlink/contracts-ccip/src/v0.8/ccip/libraries/Client.sol";
```

[Types and Constants](#)

[EVMTokenAmount](#)

Use this solidity struct to specify the token address and amount.

```
struct EVMTokenAmount { address token; uint256 amount; } NameTypeDescription token address token address on the local chain. amount uint256 Amount of tokens.
```

[Any2EVMMessage](#)

CCIP receivers use this solidity struct to parse the received CCIP message.

```
struct Any2EVMMessage { bytes32 messageId; uint64 sourceChainSelector; bytes sender; bytes data; struct Client.EVMTokenAmount[] destTokenAmounts; } NameTypeDescription messageId bytes32 CCIP messageId, generated on the source chain. sourceChainSelector uint64 Source chain selector. sender bytes Sender address. abi.decode(sender, (address)) if the source chain is an EVM chain. data bytes Payload sent within the CCIP message. destTokenAmounts Client.EVMTokenAmount[] Tokens and their amounts in their destination chain representation.
```

[EVM2AnyMessage](#)

CCIP senders use this solidity struct to build the CCIP message.

```
struct EVM2AnyMessage { bytes receiver; bytes data; struct Client.EVMTokenAmount[] tokenAmounts; address feeToken; bytes extraArgs; } NameTypeDescription receiver bytes Receiver address. Use abi.encode(sender) to encode the address to bytes. data bytes Payload sent within the CCIP message. tokenAmounts Client.EVMTokenAmount[] Tokens and their amounts in the source chain representation. feeToken address Address of feeToken. Set address(0) to pay in native gas tokens such as ETH on Ethereum or MATIC on Polygon. extraArgs bytes Users fill in the EVMExtraArgsV1 struct then encode it to bytes using the \_argsToBytes function
```

[EVM_EXTRA_ARGS_V1_TAG](#)

```
bytes4 EVM_EXTRA_ARGS_V1_TAG
```

[EVMExtraArgsV1](#)

```
struct EVMExtraArgsV1 { uint256 gasLimit; } NameTypeDescription gasLimit uint256 specifies the maximum amount of gas CCIP can consume to execute ccipReceive() on the contract located on the destination blockchain. Read Setting gasLimit for more details.
```

[Functions](#)

[_argsToBytes](#)

function _argsToBytes(struct Client.EVMExtraArgsV1 extraArgs) internal pure returns (bytes bts) It is used to convert the arguments to bytes.

[Parameters](#)

NameTypeDescription extraArgs Client.EVMExtraArgsV1 Extra arguments.

[Return Values](#)

NameTypeDescription bts bytes Encoded extra arguments in bytes.