

# Decision Tree

In this series of tutorial, we delve into the world of traditional machine learning models for ZKML. Despite the hype surrounding advanced AI techniques, traditional ML models often offer superior performance or sufficiently robust results for specific applications. This is particularly true for ZKML use cases, where computational proof costs can be a critical factor. Our aim is to equip you with guides on how to implement machine learning algorithms suitable for Giza platform applications. This includes practical steps for converting your scikit-learn models to the ONNX format, transpiling them to Orion Cairo, and deploying inference endpoints for prediction in AI Action.

In this tutorial you will learn how to use the Giza tools through a Decision Tree model.

## Before Starting

Before we start, ensure you installed the Giza stack, created a user and logged-in.

...

Copy `!pipxinstallgiza-cli# Install the Giza-CLI !pipinstallgiza-actions# Install the AI Actions SDK`

`!gizauserscreate# Create a user !gizauserslogin# Login to your account !gizauserscreate-api-key# Create an API key. We recommend you do this so you don't have to reconnect.`

...

## Create and Train a Decision Tree Model

We'll start by creating a simple decision tree model using Scikit-Learn and train on iris dataset. We will then use [Hummingbirds](#) library to convert the model to torch graphs.

...

Copy `importjson importnumpyasnp fromsklearn.datasetsimportload_iris fromsklearn.model_selectionimporttrain_test_split fromsklearn.treeimportDecisionTreeClassifierasDe fromhummingbird.mlimportconvert importtorch importos`

`iris=load_iris() X,y=iris.data,iris.target X=X.astype(np.float32) X_train,X_test,y_train,y_test=train_test_split(X, y) clr=De() clr.fit(X_train, y_train)`

`model=convert(clr,"torch", X_test[:1]).model`

...

## Convert the Model to ONNX Format

Giza only supports ONNX models so you'll need to convert the model to ONNX format. After the model is trained, you can convert it to ONNX format.

...

Copy `importtorch.onnx`

`input_sample=torch.from_numpy(X_test[:1])`

# Specify the path to save the ONNX model

`onnx_model_path="decision_tree.onnx"`

# Export the model

`torch.onnx.export(model, input_sample, onnx_model_path,# where to save the model export_params=True,# store the trained parameter weights inside the model file opset_version=17,# the ONNX version to export the model to do_constant_folding=True,# whether to execute constant folding for optimization input_names=['input'],# the model's input names output_names=['output'],# the model's output names dynamic_axes={'input': {0:'batch_size'},# variable length axes 'output': {0:'batch_size'}})`

...

Transpile your model to Orion Cairo

We will use Giza-CLI to transpile our ONNX model to Orion Cairo.

...

Copy `!gizatranspiledecision_tree.onnx--output-pathverifiable_dt`

```
[giza][2024-04-0316:03:36.422] No model id provided, checking if model exists ✓  
[giza][2024-04-0316:03:36.425] Model name is: decision_tree [giza][2024-04-  
0316:04:09.291] Model already exists, using existing model ✓ [giza][2024-04-  
0316:04:09.292] Model found with id ->146! ✓ [giza][2024-04-0316:04:09.951]  
Version Created with id ->2! ✓ [giza][2024-04-0316:04:09.952] Sending  
model for transpilation ✓ [giza][2024-04-0316:04:51.488] Transpilation is fully  
compatible. Version compiled and Sierra is saved at Giza ✓  
: Transpiling Model... [giza][2024-04-0316:04:52.201] Downloading model ✓  
[giza][2024-04-0316:04:52.241] model saved at: verifiable_dt
```

...

Deploy an inference endpoint

Now that our model is transpiled to Cairo we can deploy an endpoint to run verifiable inferences. We will use Giza CLI again to run `deploy` an endpoint. Ensure to replace `model-id` and `version-id` with your ids provided during transpilation.

...

Copy `!gizaendpointsdeploy--model-id146--version-id2`

```
■■■■■■■■■■ Creating endpoint!! [giza][2024-04-0316:05:20.152] Endpoint is  
successful ✓ [giza][2024-04-0316:05:20.156] Endpoint created with id ->36 ✓  
[giza][2024-04-03 16:05:20.156] Endpoint created with endpoint URL:  
https://endpoint-raphael-doukhan-146-2-98feddf7-6nn4ryaqca-ew.a.run.app
```

...

Run a verifiable inference in AI Actions

To streamline verifiable inference, you might consider using the endpoint URL obtained after transpilation. However, this approach requires manual serialization of the input for the Cairo program and handling the deserialization process. To make this process more user-friendly and keep you within a Python environment, we've introduced AI Actions—a Python SDK designed to facilitate the creation of ML workflows and execution of verifiable predictions. When you initiate a prediction, our system automatically retrieves the endpoint URL you deployed earlier, converts your input into Cairo-compatible format, executes the prediction, and then converts the output back into a numpy object. More info about [AI Actions here](#).

First ensure you have an AI Actions workspace created. This step grants access to a user-friendly UI dashboard, enabling you to monitor and manage workflows with ease.

...

Copy `!gizaworkspacesget`

## If you haven't set up a workspace yet, you can establish one by executing the command below:

### **`! giza workspaces create`**

```
[giza][2024-04-0311:05:16.115] Retrieving workspace information ✓ [giza]  
[2024-04-0311:05:16.272] ✓ Workspace URL: https://actions-server-raphael-  
doukhan-dblzzhtf5q-ew.a.run.app ✓ { "url":"https://actions-server-raphael-  
doukhan-dblzzhtf5q-ew.a.run.app", "status":"COMPLETED" }
```

...

Now let's run a verifiable inference with AI Actions. To design your workflow in AI Actions, you will need to define your task with `@task` decorator and then action your tasks with `@action` decorator. You can track the progress of your workflow via the workspace URL previously provided.

...

```
Copy from giza_actions.model import GizaModel from giza_actions.action import action from giza_actions.task import task
```

```
MODEL_ID=146# Update with your model ID VERSION_ID=2# Update with your version ID
```

```
@task(name="PredictDTModel") def prediction(input, model_id, version_id): model = GizaModel(id=model_id, version=version_id)
```

```
(result, proof_id) = model.predict( input_feed={'input': input}, verifiable=True, custom_output_dtype="(Tensor, Tensor)" # Decision Tree will always have this output dtype. )
```

```
return result, proof_id
```

```
@action(name="ExecuteCairoDT", log_prints=True) def execution():
```

## The input data type should match the model's expected input

```
input = input_sample.numpy()
```

```
(result, proof_id) = prediction(input, MODEL_ID, VERSION_ID)
```

```
return result, proof_id
```

```
execution()
```

```
...
```

```
...
```

```
Copy 17:13:50.018|INFO|Created flow run 'pistachio-polecat' for flow 'ExecuteCairoDT' 17:13:50.019 | INFO | Action run 'pistachio-polecat' - View at https://actions-server-raphael-doukhan-dblzzhtf5q-ew.a.run.app/flow-runs/flow-run/0a1da6ea-a81a-4976-b605-28c7e425e16b 17:13:50.294|INFO|Action run 'pistachio-polecat' - Created task run 'PredictDTModel-0' for task 'PredictDTModel' 17:13:50.297|INFO|Action run 'pistachio-polecat' - Executing 'PredictDTModel-0' immediately... Starting deserialization process... ✓ Deserialization completed!
```

```
17:13:54.384|INFO|Task run 'PredictDTModel-0' - Finished in state Completed() 17:13:54.514|INFO|Action run 'pistachio-polecat' - Finished in state Completed() ((array([0]), array([[1., 0., 0.]])), '3bb53193c43048b7b47abfefe32b569a')
```

```
...
```

Download the proof

Initiating a verifiable inference sets off a proving job on our server, sparing you the complexities of installing and configuring the prover yourself. Upon completion, you can download your proof.

First, let's check the status of the proving job to ensure that it has been completed.

Remember to substitute `endpoint-id` and `proof-id` with the specific IDs assigned to you throughout this tutorial.

```
...
```

```
Copy !gizaendpointsget-proof--endpoint-id36--proof-id3bb53193c43048b7b47abfefe32b569a
```

```
[giza][2024-03-19 11:51:45.470] Getting proof from endpoint 109 ✓ { "id": 664, "job_id": 831, "metrics": { "proving_time": 15.083126 }, "created_date": "2024-03-19T10:41:11.120310" }
```

```
...
```

Once the proof is ready, you can download it.

```
...
```

```
Copy !gizaendpointsdownload-proof--endpoint-id36--proof-id3bb53193c43048b7b47abfefe32b569a--output-path zkdt.proof
```

```
[giza][2024-03-19 11:55:49.713] Getting proof from endpoint 109 ✓ [giza][2024-03-19 11:55:50.493] Proof downloaded to zkldr.proof ✓
```

```
...
```

[Previous Linear Regression](#) [Next Build a Verifiable Neural Network with Giza Actions](#)

Last updated 16 days ago