eth_getUncleByBlockHashAndIndex

Returns information about a uncle of a block given the block hash and the uncle index position

Parameters

- block hash
- : [Required
-] A string representing the hash (32 bytes) of a block
- uncle index position
- : [Required
-] A hexadecimal equivalent of the integer indicating the uncle's index position.

A block object, or null when no block was found. The block object returned will consist of the following keys and their values:

- The block number.Null
- when the returned block is the pending block.
- : 32 bytes. Hash of the block Null
- when its pending block
- parentHash: 32 bytes. Hash of the parent block.
- : 8 bytes. Hash of the generated proof-of-work.Null when the returned block is the pending block.
- sha3Uncles
- : 32 bytes. The SHA3 of the uncles data in the block.
- logsBloom
- : 256 bytes. The Bloom filter for the logs of the block.Null
- when the returned block is the pending block.
- : 32 bytes. The root of the transaction trie of the block
- : 32 bytes. The root of the final state trie of the block
- : 32 bytes. The root of the receipts trie of the block.

- : 20 bytes. The address of the beneficiary to whom the mining rewards were given. difficulty
- : The hexadecimal of the difficulty for this block
- totalDifficulty
- : The hexadecimal of the total difficulty of the chain until this block.
- extraData
- : The "extra data" field of this block
- size
- : The hexadecimal of the size of this block in bytes.
- gasLimit: Maximum gas allowed in this block.
- gasUsed
- Total used gas by all transactions in this block
- : The unix timestamp for when the block was collated
- uncles : (Array). An array of uncle hashes.

Example

ReplaceYOUR-API-KEY with an API key from yourInfura dashboard .

Request

• cURL

 $curl \ https://blast-mainnet.infura.io/v3/YOUR-API-KEY \ -X \ POST \ -H \ "Content-Type: application/json" \ -d \ '{"jsonrpc":"2.0","method":"eth_getUncleByBlockHashAndIndex","params": ["0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d47d6a5a35","0x0"],"id":1]' \ -d \ '{"jsonrpc":"2.0","method":"eth_getUncleByBlockHashAndIndex","params": ["0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d7d6a5a35","0x0"],"id":1]' \ -d \ '{"jsonrpc":"2.0","method":"eth_getUncleByBlockHashAndIndex","params": ["0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d7d6a5a35","0x0"],"id":1]' \ -d \ '{"jsonrpc":"2.0","method":"eth_getUncleByBlockHashAndIndex","params": ["0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d7d6a5a35","0x0"],"id":1]' \ -d \ '{"jsonrpc":"2.0","method:$

Response

• JSON

Last updatedonApr 19, 2024 Previous eth_getTransactionReceipt Next eth_getUncleByBlockNumberAndIndex