

eth_getStorageAt

Returns the value from a storage position at a given address.

Parameters

- address
- : [Required]
-] A string representing the address (20 bytes) of the storage.
- storage position
- : [Required]
-] A hexadecimal code of the position in the storage.
- block parameter
- : [Required]
-] A hexadecimal block number, or one of the string tagslatest
- ,earliest
- ,pending
- ,safe
- , orfinalized
- . See the [default block parameter](#)
- .

Returns

storage value : A hexadecimal equivalent of the integer indicating the value of the storage position at the provided address.

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#) .

Request

- cURL
- WSS

```
curl https://linea-mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc":"2.0","method":"eth_getStorageAt","params":["0x295a70b2de5e3953354a6a8344e616ed314d7251","0x6661e9d6d8b923d5bbaab1b96e1dd51ff6ea2a93520fdc9eb75d059238b8c5e9","0x65a8db"],"id":1}' wscat -c wss://linea-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc":"2.0","method":"eth_getStorageAt","params":["0x295a70b2de5e3953354a6a8344e616ed314d7251","0x6661e9d6d8b923d5bbaab1b96e1dd51ff6ea2a93520fdc9eb75d059238b8c5e9","0x65a8db"],"id":1}'
```

Response

- JSON

```
{ "jsonrpc": "2.0", "id": 1, "result": "0x0000000000000000000000000000000000000000000000000000000000000000" }
```

Additional notes

Calculating the correct position depends on the storage to retrieve. Consider the following contract deployed at 0x295a70b2de5e3953354a6a8344e616ed314d7251 by address 0x391694e7e0b0cce554cb130d723a9d27458f9298 ,

contract

Storage

```
{ uint pos0 ; mapping ( address
```

=>

```
uint ) pos1 ;
```

function

Storage ()

Last updated on Apr 19, 2024 [Previous](#) [eth_getProof](#) [Next](#) [eth_getTransactionByBlockHashAndIndex](#)