

# Address → Cluster

Get name

GET /v0.1/name/:address

Get the cluster and wallet name based on an address

Name Description address EVM or Solana address Example

...

Copy <https://api.clusters.xyz/v0.1/name/0x5755d1dcea21caa687339c305d143e6e78f96adf>

...

Response

200 404 ...

Copy clusters/main

Copy null

...

Bulk get names

POST /v0.1/name/addresses

Get the cluster and wallet name based on multiple addresses

Name Description POSTbody Array of EVM and or Solana addresses Example

...

Copy `curl -XPOST 'http://api.clusters.xyz/v0.1/name/addresses' --data-raw['0x5755d1dcea21caa687339c305d143e6e78f96adf', '0xccdead94e8cf17de32044d9701c4f5668ad0bef9']`

...

Response

Any addresses not found will have name: null

200 500 ...

Copy `[ { "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "name": "clusters/main" }, { "address": "0xccdead94e8cf17de32044d9701c4f5668ad0bef9", "name": "layerzero/main" } ]`

Copy []

...

[Previous Cluster → Address](#) [Next Cluster → Metadata](#) Last updated 2 days ago On this page \* [Get name](#) \* [Bulk get names](#)