

Voting

After a proposal's deposit reaches the `MinDeposit` value, the voting period opens. Bonded SCRT holders can then cast vote on it:

...

Copy `secretclitxgovvote \ [proposal-id] \ [option] \ [flags]`

...

...

Copy

Example

`secretclitxgovvote 1 yes --from [mykey]`

...

Flags

...

Copy

Flags: `-a`, `--account-number` uint The account number of the signing account (offline mode only) `-b`, `--broadcast-mode` string Transaction broadcasting mode (`sync`|`async`|`block`) (default `"sync"`) `--dry-run` ignore the `--gas` flag and perform a simulation of a transaction, but don't broadcast it `--fee-account` string Fee account pays fees for the transaction instead of deducting from the signer `--fees` string Fee to pay along with transaction; eg: `1.0uscr` `--from` string Name or address of private key with which to sign `--gas` string gas limit to set per-transaction; set to `"auto"` to calculate sufficient gas automatically (default `200000`) `--gas-adjustment` float adjustment factor to be multiplied against the estimate returned by the tx simulation; if the gas limit is set manually this flag is ignored (default `1`) `--gas-prices` string Gas prices in decimal format to determine the transaction fee (e.g. `0.1uscr`) (default `"0.25uscr"`) `--generate-only` Build an unsigned transaction and write it to STDOUT (when enabled, the local Keybase is not accessible) `-h`, `--help` help for vote `--keyring-backend` string Select keyring's backend (`os`|`file`|`kwallet`|`pass`|`test`|`memory`) (default `"os"`) `--keyring-dir` string The client Keyring directory; if omitted, the default 'home' directory will be used `--ledger` Use a connected Ledger device `--node` string : to tendermint rpc interface for this chain (default `"tcp://localhost:26657"`) `--note` string Note to add a description to the transaction (previously `--memo`) `--offline` Offline mode (does not allow any online functionality) `-s`, `--sequence` uint The sequence number of the signing account (offline mode only) `--sign-mode` string Choose sign mode (`direct`|`amino-json`), this is an advanced feature `--timeout-height` uint Set a block timeout height to prevent the tx from being committed past a certain height `-y`, `--yes` Skip tx broadcasting prompt confirmation

...

Last updated 1 year ago On this page Was this helpful? [Edit on GitHub](#) [Export as PDF](#)