starknet addDeployAccountTransaction

Submits a new deploy account transaction.

Parameters

deploy account transaction: [Required] Adeploy account transaction object to deploy a new account contract on StarkNet.

Returns

The result of the transaction submission, including:

- · transaction hash
- : The hash of the deploy account transaction.
- · contract address
- · : The address of the new contract.

Example

ReplaceYOUR-API-KEY with an API key from your dashboard.

Request

cURL

```
curl https://starknet-mainnet.infura.io/v3/YOUR-API-KEY \ -X POST \ -H "Content-Type: application/json" \ -d '{ "jsonrpc": "2.0", "method": "starknet_addDeployAccountTransaction", "params": { "deploy_account_transaction": { "type": "DEPLOY_ACCOUNT", "version": "0x3", "signature": [ "3557065757165699682249469970267166698995647077461960906176449260016084767701", "3202126414680946801789588986259466145787792017299869598314522555275920413944" ], "nonce": "0x7", "contract_address_salt": "0x23371b227eaecd8e8920cd429d2cd0f3fee6abaacca08d3ab82a7cdd", "class_hash": "0x23371b227eaecd8e8920cd429d2cd0f3fee6abaacca08d3ab82a7cdd", "constructor_calldata": [ "0x1", "0x677bb1cdc050e8d63855e8743ab6e09179138def390676cc03c484daf112ba1", "0x362398bec32bc0ebb411203221a35a0301193a96f317ebe5e40be9f60d15320", "0x0", "0x1", "0x1", "0x2b", "0x0" ], "resource_bounds": { "l1_gas": "0x28ed6103d0000", "l2_gas": "0x28ed6103d0000", }, "tip": "0x0", "paymaster_data": [], "nonce_data_availability_mode": "L1", "fee_data_availability_mode": "L1" }, "id": 1 }'
```

Response

JSON

```
 \begin{tabular}{ll} & \begin{tabular}{ll}
```

Last updatedonMay 9, 2024 Previous starknet addDeclareTransaction Next starknet addInvokeTransaction