

bor_getSignersAtHash

Returns all the signers of the block matching the specified block hash.

For Growth and Custom service plans This JSON-RPC method allows a request to be forwarded to a partner service provider if Infura should experience a service issue or outage. See [Failover protection](#) and [Enable API request forwarding](#) for complete details.

If you would like failover protection but don't qualify under your current plan, then either self-upgrade to the Growth plan or contact a sales representative to upgrade to a Custom plan.

Parameters

Hash - hash of a block

Returns

Array of signers for the specified block hash

Example

Request

- cURL
- WSS

```
curl https://polygon-mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc":"2.0","method":"bor_getSignersAtHash","params":["0x29fa73e3da83ddac98f527254fe37002e052725a88904bac14f03e919e1e2876"],"id":1}' wscat -c wss://polygon-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc":"2.0","method":"bor_getSignersAtHash","params":["0x29fa73e3da83ddac98f527254fe37002e052725a88904bac14f03e919e1e2876"],"id":1}'
```

Response

```
{ "jsonrpc": "2.0", "id": 1, "result": [ "0x0375b2fc7140977c9c76d45421564e354ed42277",  
"0x42eefcda06ead475cde3731b8eb138e88cd0bac3", "0x5973918275c01f50555d44e92c9d9b353cadad54",  
"0x7fcd58c2d53d980b247f1612fdb93e9a76193e6", "0xb702f1c9154ac9c08da247a8e30ee6f2f3373f41",  
"0xb8bb158b93c94ed35c1970d610d1e2b34e26652c", "0xf84c74dea96df0ec22e11e7c33996c73fcc2d822" ] }
```

Last updated on Apr 19, 2024 [Previous bor_getRootHash](#) [Next eth_accounts](#)