

Vulcan Network Upgrade (OLD)

Network Upgrade Instructions Fromsecret-1 Tosecret-2

⚠ Please read carefully before you begin the upgrade.

- Network Upgrade Instructions fromsecret-1
- tosecret-2
- Validators
- - Prepare yoursecret-1
- - validator to halt after block #1,246,400
- - Install the new binaries on your SGX machine
- - Migrate your validator's signing key
- - Migrate your validator's wallet
- - Set up your SGX machine and become asecret-2
- - validator
- *
- In case of an upgrade failure
-

Validators

All coordination efforts will be done in the [mainnet-validators](#) channel in the Secret Network Discord.

⚠ Don't delete yoursecret-1 machine, as we might have to relaunch it.

⚠ If your SGX machine has a previoussecretnetwork installation on it (e.g. from the testnet), you will need to remove it before you continue:

...

```
Copy cd~ sudo systemctl stop secret-node secretd unsafe-reset-all secretd reset-enclave secretd init-enclave --reset  
sudo apt purge -y secretnetwork rm -rf ~/.secretcli/ rm -rf ~/.secretd/ rm -rf ~/.sgx_secrets/*
```

...

You're probably familiar with [SGX](#) by now:

- [Setup SGX](#)
- [Verify SGX](#)
-

Prepare Yoursecret-1 Validator To Halt After Block #1,246,400

On the old machine (secret-1):

...

```
Copy perl -i -pe 's/^halt-height = .*/halt-height = 1246400/' ~/.secretd/config/app.toml
```

```
sudo systemctl restart secret-node
```

...

1. Install The New Binaries On Your SGX Machine

On the new SGX machine (secret-2):

...

Copy cd~

```
wget "https://github.com/scrtlabs/SecretNetwork/releases/download/v1.0.0/secretnetwork_1.0.0_amd64.deb"
```

```
echo "87aee80a112f429db0b8b6703b1eba33acceaf08af9e65339d14d92a5186b24 secretnetwork_1.0.0_amd64.deb" | sha256sum --check
```

```
sudoaptinstall-y./secretnetwork_1.0.0_amd64.deb
```

```
secretinit"MONIKER"--chain-idsecret-2
```

...

1. Migrate Your Validator's Signing Key

Copy your ~/.secret/config/priv_validator_key.json from the old machine (secret-1) to the new SGX machine (secret-2) at the same location.

1. Migrate Your Validator's Wallet

Export the self-delegator wallet from the old machine (secret-1) and import to the new SGX machine (secret-2).

On the old machine (secret-1) use `secretcli keys export "YOUR_KEY_NAME"` . On the new SGX machine (secret-2) use `secretcli keys import "YOUR_KEY_NAME" "FROM_FILE_NAME"`

Notes:

1. If you're recovering the wallet use `secretcli keys add "YOUR_KEY_NAME" --recover`
2. you should also use `--hd-path "44'/118'/0'/0/0"`
3. .
4. If the wallet is stored on a Ledger device, use `--legacy-hd-path`
5. when importing it with `secretcli keys add`
6. .
7. .

1. Set Up Your SGX Machine And Become A secret-2 Validator

On the new SGX machine (secret-2):

...

Copy cd~

```
secretinitMONIKER--chain-idsecret-2
```

```
wget -O ~/.secret/config/genesis.json "https://github.com/scribblelabs/SecretNetwork/releases/download/v1.0.0/genesis.json"
```

```
echo "4ca53e34afed034d16464d025291fe16a847c9aca0a259f9237413171b19b4cf .secret/config/genesis.json" | sha256sum --check
```

```
secretvalidate-genesis
```

```
secretinit-enclave
```

```
PUBLIC_KEY=(secretparseattestation_cert.der2>/dev/null|cut-c3-) echoPUBLIC_KEY
```

```
secretconfigchain-idsecret-2 secretconfignodetcp://secret-2.node.enigma.co:26657 secretconfigtrust-nodetrue secretconfigoutputjson secretconfigindenttrue
```

```
secretclitxregisterauth./attestation_cert.der--from"YOUR_KEY_NAME"--gas-prices0.0125uscrt
```

```
SEED=(secretcliqueryregisterseed"PUBLIC_KEY"|cut-c3-) echoSEED
```

```
secretcliqueryregistersecret-network-params
```

```
mkdir-p~/.secret/.node
```

```
secretconfigure-secretnode-master-cert.der"SEED"
```

```
perl -i -pe 's/persistent_peers = ./persistent_peers = "bee0edb320d50c839349224b9be1575ca4e67948\@secret-2.node.enigma.co:26656"/' ~/.secret/config/config.toml
```

```
sudo systemctl enable secret-node
```

```
sudo systemctl start secret-node# (Now your new node is live and catching up)
```

```
secretconfignodetcp://localhost:26657
```

...

Now wait until you're done catching up. This is fast. Once the following command outputstrue you can continue:

...

Copy watch'secretcli status | jq ".sync_info.catching_up == false"

...

Once your node is done catching up, you can unjail your validator:

...

Copy secretclitxslashingunjail--from"YOUR_KEY_NAME"--gas-prices0.0125uscr

...

You're now a validator insecret-2 !

To make sure your validator is unjailed, look for it in here:

...

Copy secretcliqstakingvalidators|jq-r'[] | select(.status == 2) | .description.moniker'

...

([Ref for testnet instructions](#))

In Case Of An Upgrade Failure

If after a few hours the Enigma team announces on the chat that the upgrade failed, we will relaunchsecret-1 .

1. On the old machine (secret-1
2.):
3. ...
4. Copy
5. perl -i -pe 's/^halt-height = */halt-height = 0/' ~/.secretd/config/app.toml
6. as
7. sudo systemctl restart secret-node
8. ...
9. Wait for 67% of voting power to come back online.
- 10.

Last updated5 months ago On this page *[Network Upgrade Instructions From secret-1 To secret-2](#) * [Validators](#) * [Prepare Your secret-1 Validator To Halt After Block #1,246,400](#) * [2. Install The New Binaries On Your SGX Machine](#) * [3. Migrate Your Validator's Signing Key](#) * [4. Migrate Your Validator's Wallet](#) * [5. Set Up Your SGX Machine And Become A secret-2 Validator](#) * [In Case Of An Upgrade Failure](#)

Was this helpful? [Edit on GitHub](#) [Export as PDF](#)