

Nodes

If you are running a full node or a validator node, view the status by typing:

...

Copy `secretcli status`

Use the `-n`, `--node` flag to connect to a specific node (default `"tcp://localhost:26657"`)

...

Example output for `secretcli status | jq` :

...

```
Copy { "NodeInfo":{ "protocol_version":{ "p2p":"8", "block":"11", "app":"0" },
"id":"38bee11836e06fec5cb9b3eb6ca66a44abf6c2ea", "listen_addr":"174.138.172.52:26656", "network":"secret-4",
"version":"0.34.19", "channels":"40202122233038606100", "moniker":"anode1-node02", "other":{ "tx_index":"on",
"rpc_address":"tcp://174.138.172.52:26657" } }, "SyncInfo":{
"latest_block_hash":"8B56C543B4D58378C514EFF0643A9FE392E31E4F35C10E57EF355D422E0BAD6D",
"latest_app_hash":"72286A7DDA4DFC38737DC6B6381235003166C46A99DD77955801660669AC889D",
"latest_block_height":"4060469", "latest_block_time":"2022-06-28T12:10:32.992861612Z",
"earliest_block_hash":"C168FE742EC3DCD6911B31CEE7F0C58EF7621EB85E87193875CD9C2C7E74473C",
"earliest_app_hash":"E3B0C44298FC1C149AFBF4C8996FB92427AE41E4649B934CA495991B7852B855",
"earliest_block_height":"813800", "earliest_block_time":"2021-11-10T15:00:00Z", "catching_up":false }, "ValidatorInfo":{
"Address":"FAABDCF81803E51DE9A7C6EA7447F1D403B50C1F", "PubKey":{ "type":"tendermint/PubKeyEd25519",
"value":"7eb9uBzsF2v83pT9JxTzE2B4cAdHpSfrF/tLUyIQQvU=" }, "VotingPower":"0" } }
```

...

Last updated 1 year ago On this page Was this helpful? [Edit on GitHub](#) [Export as PDF](#)