

# ORA

[ORA](#) is Ethereum's Trustless AI. As a verifiable oracle protocol, ORA brings AI and complex compute onchain. Its main product, Onchain AI Oracle (OAO), integrates AI capabilities directly onchain.

ORA breaks down the limitations of smart contracts by offering verifiable AI inference so that developers can innovate freely.

## OAO quickstart

This quickstart is designed to help you build a smart contract on Arbitrum able to interact with OAO. You can find more details in [our docs Quickstart](#).

### Workflow

1. The user contract sends the AI request to OAO on Arbitrum, by calling `requestCallback`
2. function on the OAO contract.
3. Each AI request will initiate an opML inference.
4. OAO will emit a `requestCallback`
5. event which will be collected by opML node.
6. opML node will run the AI inference, and then upload the result on Arbitrum, waiting for the challenge period. 1. During the challenge period, the opML validators will check the result and challenge it if the submitted result is incorrect.
7.
  1. If the submitted result is successfully challenged by one of the validators, the submitted result will be updated on Arbitrum.
8.
  1. After the challenge period, the submitted result onchain is finalized.
9. When the result is uploaded or updated on Arbitrum, the provided AI inference in opML will be dispatched to the user's smart contract via its specific callback function.

## Integration

### Overview

To integrate with OAO, you will need to write your own contract.

To build with AI models of OAO, we provided an example of contract using [OAO Prompt](#).

### Smart contract integration

1. Inherit `AIOracleCallbackReceiver`
2. in your contract and bind with a specific OAO address:

```
constructor ( IAIOracle _aiOracle )
```

```
AIOracleCallbackReceiver ( _aiOracle )
```

```
{ } 1. Write your callback function to handle the AI result from OAO. Note that only OAO can call this function:
```

```
function
```

```
aiOracleCallback ( uint256 requestId , bytes calldata output , bytes calldata callbackData ) external override  
onlyAIOracleCallback ( ) 1. When you want to initiate an AI inference request, call OAO as follows:
```

```
aiOracle . requestCallback ( modelId , input ,
```

```
address ( this ) , gas_limit , callbackData ) ;
```

## Reference

4 models are available on Arbitrum One: Stable Diffusion (ID: 50), Llama3 8B Instruct (ID: 11), OpenLM Score 7B (ID: 14) and OpenLM Chat 7B (ID: 15).

[Prompt](#) and [SimplePrompt](#) are both example smart contracts interacted with OAO.

For simpler application scenarios (eg. Prompt Engineering based AI like GPTs), you can directly use [Prompt](#) or [SimplePrompt](#).

SimplePrompt saves gas by only emitting the event without storing historical data.

Arbitrum One:

- OAO Proxy: [0x0A0f4321214BB6C7811dD8a71cF587bdaF03f0A0](#)
- Prompt: [0xC20DeDbE8642b77EfDb4372915947c87b7a526bD](#)
- SimplePrompt: [0xC3287BDEF03b925A7C7f54791EDADCD88e632CcD](#)

Arbitrum Sepolia tesnet:

- OAO Proxy: [0x0A0f4321214BB6C7811dD8a71cF587bdaF03f0A0](#)
- Prompt: [0xC3287BDEF03b925A7C7f54791EDADCD88e632CcD](#)
- SimplePrompt: [0xBC24514E541d5CBAAC1DD155187A171a593e5CF6](#)

## Useful links:

- Read [ORA documentation](#)
- [Join our Discord](#)
- where our team can help you
- Follow us on [X](#) [Edit this page](#) Last updated on Jan 27, 2025 [Previous Chronicle](#) [Next How to use Supra price feed oracle](#)