

eth_uninstallFilter

Uninstalls a filter with given ID. This method should always be called when watching is no longer needed. Additionally, filters time out when they aren't requested with [eth_getFilterChanges](#) for a period of time.

Parameters

- filter ID
- : A string denoting the ID of the filter to be uninstalled.

Returns

uninstalled flag : (boolean) true if the filter was successfully uninstalled, otherwise false .

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#) .

Request

- cURL
- WSS

```
curl https://mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d
'{"jsonrpc":"2.0","method":"eth_uninstallFilter","params":["0x10ff0bfba9472c87932c56632eef8f5cc70910e8e71d"],"id":1}'
wscat -c wss://mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc":"2.0","method":"eth_uninstallFilter","params":
["0x10ff0bfba9472c87932c56632eef8f5cc70910e8e71d"],"id":1}'
```

Response

- JSON

```
{ "jsonrpc": "2.0", "id": 1, "result": true }
```

Last updated on Apr 19, 2024 [Previous eth_newPendingTransactionFilter](#) [Next net_listening](#)