PnP No Modal SDK - v6 to v7

Generalâ

web3auth.connectTo()

now returns a provider of typeIProvider â

The new provider object now works with the latest version ofweb3.js

<u>â</u>

With V7, theconnectTo() method now returns a provider of typeIProvider which is a hard-coded provider, ensuring compatibility with the latest version of web3.js. Previously, we had been using a proxy provider i.e.SafeEventEmitterProvider which gave errors with the breaking changes that came with web3.js v4. Remember, you can import the typeIProvider from the@web3auth/base package.

OpenLoginAdapter â

Change in the naming of some whitelabel parameters for OpenLoginAdapter

â

name

andurl are nowappName andappUrl, respectively â

InadapterSettings , thewhitelabel object now acceptsappName andappUrl instead ofname andurl , respectively. This is done to bring consistency to the naming convention.

Light and dark mode is now toggled by themode

parameter instead ofdark .â

mode accepts a string from the following options:auto ,light ordark . This replaces thedark boolean parameter from previous versions.

```
"https://web3auth.io/images/web3auth-logo---Dark.svg", defaultLanguage:
"en",
// en, de, ja, ko, zh, es, fr, pt, nl mode :
"auto",
// whether to enable dark mode. defaultValue: false theme :
{ primary :
"#768729", }, useLogoLoader:
true , } , } , privateKeyProvider , } );
Other changes â
Extra parameters forsolana-provider
andxrpl-provider â
For Solanaâ
For Solana, SolanaWallet in package@web3auth/solana-provider, the request typings require both input and output now
usestring[] when input placeholder is needed
// With V7 const connectionConfig =
await solanaWallet . request < string [],
CustomChainConfig
     ( { method :
"solana_provider_config", params:
[], }); const conn =
new
Connection ( connectionConfig . rpcTarget );
For XRPLâ
For XRPL, after the change of@web3auth/xrpl-provider version to v7, the request typings require both input and output now
so usenever when input or output placeholder is needed
```

```
// With V7 const txSign =
await
this . provider . request < { signature :
string
},
never
      ( { method :
"xrpl_signMessage", params:
{ signature : hexMsg , } , } );
const accounts =
await
this . provider . request < never ,
```

```
string []
     ( { method :
"xrpl_getAccounts", });
wallet-connect-v2-adapter
requires different parametersâ
With the deprecation of@wallet-connect/qr-code-modal
,wallet-connect-v2-adapter now requires@walletconnect/modal â
import
{
WalletConnectModal
}
from
"@walletconnect/modal"; import
{ getWalletConnectV2Settings , WalletConnectV2Adapter , }
from
"@web3auth/wallet-connect-v2-adapter";
const defaultWcSettings =
await
getWalletConnectV2Settings ("eip155", [1], "04309ed1007e77d1f119b85205bb779d",); const walletConnectModal =
new
WalletConnectModal ( { projectId :
"04309ed1007e77d1f119b85205bb779d", }); const walletConnectV2Adapter =
new
WalletConnectV2Adapter ( { adapterSettings :
{ grcodeModal : walletConnectModal ,
... defaultWcSettings . adapterSettings
}, loginSettings:
... defaultWcSettings . loginSettings
```

}, }); Edit this page Previous v7 to v8 Next v5 to v6