

function-tradebysourceamount)

- [Function Arguments](#)
- [Example](#)

tradeBySourceAmount()

The function parameters must include the list of orders (tradeActions) to interact with.

Using the SDK is highly recommended. See [Performing Trades](#) for details.

FunctiontradeBySourceAmount()

This function will trade the exact amount of indicatedsource tokens for as manytarget tokens as possible.

...

```
CarbonController.sol Copy functiontradeBySourceAmount( TokensourceToken, TokentargetToken,
TradeAction[]calldatatradeActions, uint256deadline, uint128minReturn
)externalpayablenonReentrantwhenNotPausedreturns(uint128)
```

...

Function Arguments

Name	Type	Description
sourceToken	Token address	The source token address
targetToken	Token address	The target token address
tradeActions	list	This is a list of TradeAction objects, each of which contain thestrategyId andamount of source tokens to trade into the strategy
deadline	uint256	Unix timestamp after which the transaction will revert
minReturn	uint128	The minimum amount of target tokens that must be received for the transaction to not revert
tradeActionamount		needs to follow the relevant token decimal. tradeBySourceAmount, follows the sourceToken decimals

Example

...

```
Copy tradeBySourceAmount( 0xC02aaA39b223FE8D0A0e5C4F27eAD9083C756Cc2,//source token
0x1F573D6Fb3F13d689FF844B4cE37794d79a7FF1C,//target token [{59, 1600000000000000000}, {72,
3140000000000000000}], //array of tradeActions [{strategyId, amount},{strategyId, amount}...] 1675680190,//deadline
5320000000000000000//minReturn )
```

...

While all required data is available on-chain, it is recommended to use the [Carbon DeFi SDK](#) . To trade directly with the ETH token, use the contract address:0xEeeeeEeeeEeEeeEeEeEeEeEeEeEeEeEeEeE [Previous Trade](#) [Next tradeByTargetAmount\(\)](#) Last updated1 month ago