

# Messages

## Overview

This section provides detailed specifications for the messages within the Admin module of the Neutron network. Messages serve as the primary vehicle for users, administrators, and the [DAO](#) to communicate and propose changes within the Neutron ecosystem. Based on the cosmos-sdk architecture, the Admin module offers a range of standardized message structures for seamless governance and operations.

## MsgDeleteAdmin

Deletes an existing admin from the Neutron network, ensuring that the particular admin no longer has governance rights or permissions.

Parameters:

- creator
- :string
- - The originator or sender of this message. It's usually the address of the entity proposing the removal of the admin.
- admin
- :string
- - The target admin's address to be revoked from its administrative rights.

Response: MsgDeleteAdminResponse

## MsgDeleteAdminResponse

The standard response message after processing MsgDeleteAdmin . If successful, it confirms the deletion of the specified admin.

(No fields)

## MsgAddAdmin

Facilitates the addition of a new admin. This admin, once added, will be endowed with governance and operational rights as per the Neutron network's configuration.

Parameters:

- creator
- :string
- - The initiator or sender of this message. Typically, the address of the entity proposing the addition of a new admin.
- admin
- :string
- - The address of the new admin to be onboarded.

Response: MsgAddAdminResponse

## MsgAddAdminResponse

The definitive response message after processing MsgAddAdmin . A successful response ensures the addition of the specified admin into the Neutron network's governance mechanism.

(No fields)

## MsgSubmitProposalLegacy

Leveraging the legacy mechanisms, this message type is tailored for submitting proposals structured before the sdk-47 update. This ensures backward compatibility and a wider range of proposal support.

Parameters:

- content
- :google.protobuf.Any
- - The intrinsic content of the proposal. Typically aligns with theContent
- interface specifications.
- proposer
- :string
- - The address of the entity submitting the proposal.

Response: MsgSubmitProposalLegacyResponse

## MsgSubmitProposalLegacyResponse

The response message confirming the processing ofMsgSubmitProposalLegacy .

Fields:

- proposal\_id
- :uint64
- - The unique identifier assigned to the submitted proposal. This ID serves as a reference for future operations or queries related to this proposal.

## MsgSubmitProposal

In line with the updates in sdk-47, this message type provides a structure for submitting proposals using the revamped message structures. It encapsulates a diverse array of actions and changes.

Parameters:

- messages
- :Array
- - A collection of arbitrary messages detailing the changes or actions proposed. These messages are executed contingent upon the proposal's approval.
- proposer
- :string
- - The originator's address proposing the changes.

Response: MsgSubmitProposalResponse

## MsgSubmitProposalResponse

The standardized response message post-processingMsgSubmitProposal .

Fields:

- proposal\_id
- :uint64
- - A unique identifier for the newly submitted proposal. It serves as a pivotal reference for all related actions, queries, or updates. [Previous Admin Module Next Overview](#)