

# Phantom Adapter

[@web3auth/phantom-adapter](#)

[â](#)

Phantom adapter allows you to connect with phantom wallet. You can read more about phantom wallet here. (<https://docs.phantom.app/> ).

## Basic Detailsâ

**Adapter Name:**phantom

[â](#)

**Package Name:**[@web3auth/phantom-adapter](#)

[â](#)

**authMode:**DAPP

[â](#)

**chainNamespace:**SOLANA

[â](#)

**Default:**YES

[â](#)

## Installationâ

- npm
- Yarn
- pnpm

npm install --save @web3auth/phantom-adapter yarn add @web3auth/phantom-adapter pnpm add @web3auth/phantom-adapter

## Argumentsâ

- Table
- Interface

Parameter type chainConfig CustomChainConfig clientId? string sessionTime? number web3AuthNetwork? OPENLOGIN\_NETWORK\_TYPE interface

PhantomAdapterOptions

{ chainConfig ? :

CustomChainConfig ; clientId ? :

string ; sessionTime ? :

number ; web3AuthNetwork ? :

OPENLOGIN\_NETWORK\_TYPE ; }

## Custom Chain Configâ

**chainConfig**

[â](#)

warning While you can pass yourchainConfig , it is not required since you can directly pass it over to theWeb3Auth /Web3AuthNoModal configuration while instantiating it.

Read more about it in their respective sections:

- [web3auth/modal](#)
- [web3auth/no-modal](#) warning If you do passchainConfig in an Adapter, it overwrites thechainConfig passed over to theWeb3Auth /Web3AuthNoModal constructor.

## Change Adapter Settings

You can change the adapter settings by calling thesetAdapterSettings() function on the adapter instance.

### Arguments

- Table
- Interface

Parameter type clientId? string sessionTime? number chainConfig? CustomChainConfig web3AuthNetwork? OPENLOGIN\_NETWORK\_TYPE interface

BaseAdapterSettings

{ clientId ? :

string ; sessionTime ? :

number ; chainConfig ? :

CustomChainConfig ; web3AuthNetwork ? :

OPENLOGIN\_NETWORK\_TYPE ; }

## Example

```
import
```

```
{
```

```
PhantomAdapter
```

```
}
```

```
from
```

```
"@web3auth/phantom-adapter" ; const phantomAdapter =
```

```
new
```

```
PhantomAdapter ( { clientId , sessionTime :
```

```
3600 ,
```

```
// 1 hour in seconds web3AuthNetwork :
```

```
"sapphire_mainnet" , chainConfig :
```

```
{ chainNamespace :
```

```
CHAIN_NAMESPACES . SOLANA , chainId :
```

```
"0x1" , rpcTarget :
```

```
"https://rpc.ankr.com/solana" ,
```

```
// This is the public RPC we have added, please pass on your own endpoint while creating an app } , } ) ; web3auth .  
configureAdapter ( phantomAdapter ) ;
```

```
// You can also change the adapter settings by calling the setAdapterSettings() function on the adapter instance.  
phantomAdapter . setAdapterSettings ( { sessionTime :
```

86400 ,

// 1 day in seconds chainConfig :

{ chainNamespace :

CHAIN\_NAMESPACES . SOLANA , chainId :

"0x1" , rpcTarget :

"https://rpc.ankr.com/solana" ,

// This is the public RPC we have added, please pass on your own endpoint while creating an app } , web3AuthNetwork :

"sapphire\_mainnet" , } ) ;[Edit this page](#) [Previous Metamask Wallet](#) [Next Wallet Connect V1](#)