

validateSponsorshipPolicies

Validates a User Operation against an array of [sponsorship policies](#) , and returns an array of sponsorship policies (alongside additional data for each policy) that are willing to sponsor the user operation.

Usage

```
example.ts client.ts ``
```

File example.ts import{ pimlicoPaymasterClient }from"./client"

[illegible]

Returns

- Type:
- `ValidateSponsorshipPoliciesReturnType`

An array of sponsorship policy IDs and (optionally) extra data to be used by front-ends for sponsorship policies that are willing to sponsor the user operation.

...

```
{ sponsorshipPolicyId:string data:{ name:string|null author:string|null icon:string|null description:string|null } }[]
```

...

name (optional)

- Type:
- string | null

The name of the sponsorship policy.

author (optional)

- Type:
- string | null

The author of the sponsorship policy.

icon (optional)

- Type:
- string | null

The icon of the sponsorship policy. The icon must be a data URI as defined in RFC-2397.

description (optional)

- Type:
- string | null

The description of the sponsorship policy.

Parameters

userOperation

- Type:
- UserOperation

The User Operation object.

sponsorshipPolicyIds

- Type:
- `string[]`

An array of sponsorship policy IDs to validate against.

JSON-RPC Method

[pm_validateSponsorshipPolicies](#)