eth_syncing

Returns an object with data about the sync status orfalse.

Parameters

None.

Returns

- · sync status
- : (boolean) Returnsfalse
- · only when not syncing.
- · sync blocks
- :* startingBlock

_

- : A hexadecimal equivalent the integer indicating the block at which the import started (will only be reset after the sync reaches the head).
- currentBlock
- - : A hexadecimal equivalent the integer indicating the current block, same aseth blockNumber
- ۰.

- highestBlock
- _
- : A hexadecimal equivalent the integer indicating the highest block.

Example

ReplaceYOUR-API-KEY with an API key from your Infura dashboard .

Request

- cURL
- WSS

 $curl \ https://linea-mainnet.infura.io/v3/YOUR-API-KEY \ -X \ POST \ -H \ "Content-Type: application/json" \ -d \ '\{"jsonrpc":"2.0","method":"eth_syncing","params": [],"id":1}' \ wscat \ -c \ wss://linea-mainnet.infura.io/ws/v3/YOUR-API-KEY \ -x \ '\{"jsonrpc":"2.0","method":"eth_syncing","params": [],"id":1}'$

Response

JSON

```
{ "jsonrpc": "2.0", "id": 1, "result": false }
```

Last updatedonApr 19, 2024 Previous eth_submitWork Next linea_estimateGas