

# eth\_getTransactionByBlockHashAndIndex

Returns information about a transaction given block hash and transaction index position.

## Parameters

- block hash
- : [Required
- ] A string representing the hash (32 bytes) of a block.
- transaction index position
- : [Required
- ] A hexadecimal of the integer representing the position in the block.

## Returns

A transaction object, or null when no transaction was found. The transaction object will consist of the following keys and their values:

- accessList
- : [optional
- ] A list of addresses and storage keys accessed by the transaction. See [access list transactions](#)
- .
- blockHash
- : 32 bytes. A hash of the block including this transaction.null
- when it's pending.
- blockNumber
- : The number of the block including this transaction.null
- when it's pending.
- chainID
- : [optional
- ] chain ID specifying the network. Returned only for [EIP-1559 transactions](#)
- .
- from
- : 20 bytes. The address of the sender.
- gas
- : Gas provided by the sender.
- gasPrice
- : Gas price provided by the sender in Wei.
- hash
- : 32 bytes. The hash of the transaction.
- input
- : The data sent along with the transaction.
- maxPriorityFeePerGas
- : [optional
- ] Maximum fee, in Wei, the sender is willing to pay per gas above the base fee. See [EIP-1559 transactions](#)
- .
- maxFeePerGas
- : [optional
- ] Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas. See [EIP-1559 transactions](#)
- .
- nonce
- : The number of transactions made by the sender prior to this one.
- r
- : 32 bytes. The ECDSA signaturer
- .
- s
- : 32 bytes. The ECDSA signatures
- .
- to
- : 20 bytes. The address of the receiver.null
- when it's a contract creation transaction.
- transactionIndex
- : The transaction's index position in the block, in hexadecimal.null
- when it's pending.
- type
- : The [transaction type](#)
- .
- v
- : The ECDSA recovery ID.
- value
- : The value transferred in Wei.

## Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#) .

## Request

- cURL
- WSS

```
curl https://zksync-mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc": "2.0", "method": "eth_getTransactionByBlockHashAndIndex", "params": ["0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d47d6a5a35", "0x0"], "id": 1}' wscat -c wss://zksync-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc": "2.0", "method": "eth_getTransactionByBlockHashAndIndex", "params": ["0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d47d6a5a35", "0x0"], "id": 1}'
```

## Response

- JSON

```
{ "id": 1, "jsonrpc": "2.0", "result": { "blockHash": "0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d47d6a5a35", "blockNumber": "0x5bad55", "chainId": "0x1", "from": "0xfbb1b73c4f0bda4f67dca266ce6ef42f520fbb98", "gas": "0x249f0", "gasPrice": "0x174876e800", "hash": "0x8784d99762bccd03b2086eabccee0d77f14d05463281e121a62abfbcf0d2d5f", "input":
```

Last updated on Nov 5, 2024 [Previous](#) [eth\\_getStorageAt](#) [Next](#) [eth\\_getTransactionByBlockNumberAndIndex](#)

Last updated on Nov 5, 2024 [Previous](#) [eth\\_getStorageAt](#) [Next](#) [eth\\_getTransactionByBlockNumberAndIndex](#)