eth_getLogs

Returns an array of all the logs matching the given filter object. See also the belowonstraints section.

Parameters

A filter object containing the following:

- address
- : [optional
- Contract address (20 bytes) or a list of addresses from which logs should originate.
- fromBlock
- :[optional, default is "latest"]
- A hexadecimal block number, or one of the string tagslatest
- .earliest
- ,pending
- .safe
- , orfinalized
- . See thedefault block parameter
- toBlock :[optional, default is "latest"]
- A hexadecimal block number, or one of the string tagslatest
- .earliest
- ,pending
- .safe
- , orfinalized . See thedefault block parameter
- topics
- :[optional]
- Array of 32 bytes DATA topics. Topics are order-dependent. blockhash
- :[optional] Restricts the logs returned to the single block referenced in the 32-byte hashblockHash
- . UsingblockHash
- is equivalent to settingfromBlock
- andtoBlock
- to the block number referenced in theblockHash
- . IfblockHash
- is present in in the filter criteria, then neitherfromBlock
- nortoBlock
- are allowed

Returns

log objects: An array of log objects, or an empty array if nothing has changed since last poll. Log objects contain the following keys and their values:

- : (boolean)true
- when the log was removed, due to a chain reorganization.false
- if it's a valid log
- : Hexadecimal of the log index position in the block.Null
- when it is a pending log. transactionIndex
- : Hexadecimal of the transactions index position from which the log created.Null
- when it is a pending log.
- transactionHash
- : 32 bytes. Hash of the transactions from which this log was created. Null when it is a pending log.
- blockHash
- : 32 bytes. Hash of the block where this log was in.Null
- when it is a pending log.
- blockNumber
- : Block number where this log was in.Null
- when it is a pending log.
- : 20 bytes. Address from which this log originated.
- : Contains one or more 32-bytes non-indexed arguments of the log
- :An array of 0 to 4 indexed log arguments, each 32 bytes. In solidity the first topic is the hash of the signature of the event (e.g. Deposit(address,bytes32,uint256)), except when you declared the event with the anonymous specifier.

Example

ReplaceYOUR-API-KEY with an API key from yourInfura dashboard

Request

curl https://blast-mainnet.infura.io/v3/YOUR-API-KEY\-X POST\-H "Content-Type: application/json"\-d '{"jsonrpc":"2.0","method":"eth_getLogs","params":[{"blockHash": "0x7c5a35e9cb3e8ae0e221ab470abae9d446c3a5626ce6689fc777dcffcab52c70", "topics":["0x241ea03ca20251805084d27d4440371c34a0b85ff108f6bb5611248f73818b80"]}],"id":1}'

Response

JSON

"0x788b1442414cb9c9a36dba2abe250763161a6f6395788a2e808f1b34e92beec1", "transactionIndex": "0x54" }] }

Constraints

The following constraints apply:

To prevent queries from consuming too many resources,eth_getLogs requests are currently limited by three constraints:

• A maximuim of 5,000 parameters in a single request

- A maximum of 10,000 results can be returned by a single query
 Query duration must not exceed 10 seconds

If a query returns too many results or exceeds the max query duration, one of the following errors is returned:

{ "jsonrpc": "2.0", "id": 1, "error": { "code": -32005, "message": "query returned more than 10000 results" } } or

 $\{ \ "isonrpc": "2.0", "id": 1, "error": \{ \ "code": -32005, "message": "query timeout exceeded" \} \} \ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \} \\ If this happens: "query timeout exceeded" \} \\ If this happens: "query timeout exceeded exceed$

- Limit your query to a smaller number of blocks usingfromBlock
 andtoBlock

Last updatedonApr 19, 2024 Previous eth_getCode Next eth_getProof