

eth_getTransactionByHash

Returns information about a transaction for a given hash.

For Growth and Custom service plans This JSON-RPC method allows a request to be forwarded to a partner service provider if Infura should experience a service issue or outage. See [Failover protection](#) and [Enable API request forwarding](#) for complete details.

If you would like failover protection but don't qualify under your current plan, then either self-upgrade to the Growth plan or contact a sales representative to upgrade to a Custom plan.

Parameters

transaction hash : [Required] A string representing the hash (32 bytes) of a transaction.

Returns

A transaction object, or null when no transaction was found. The transaction object will consist of the following keys and their values:

- accessList
- : [optional
-] A list of addresses and storage keys accessed by the transaction. See [access list transactions](#)
- .
- blockHash
- : 32 bytes. A hash of the block including this transaction.null
- when it's pending.
- blockNumber
- : The number of the block including this transaction.null
- when it's pending.
- chainID
- : [optional
-] chain ID specifying the network. Returned only fo [EIP-1559 transactions](#)
- .
- from
- : 20 bytes. The address of the sender.
- gas
- : Gas provided by the sender.
- gasPrice
- : Gas price provided by the sender in Wei.
- hash
- : 32 bytes. The hash of the transaction.
- input
- : The data sent along with the transaction.
- maxPriorityFeePerGas
- : [optional
-] Maximum fee, in Wei, the sender is willing to pay per gas above the base fee. See [EIP-1559 transactions](#)
- .
- maxFeePerGas
- : [optional
-] Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas. See [EIP-1559 transactions](#)
- .
- nonce
- : The number of transactions made by the sender prior to this one.
- r
- : 32 bytes. The ECDSA signaturer
- .
- s
- : 32 bytes. The ECDSA signatures
- .
- to
- : 20 bytes. The address of the receiver.null
- when it's a contract creation transaction.
- transactionIndex
- : The transaction's index position in the block, in hexadecimal.null
- when it's pending.
- type
- : The [transaction type](#)
- .
- v
- : The ECDSA recovery ID.
- value
- : The value transferred in Wei.

Example

ReplaceYOUR-API-KEY with an API key from your [Infura dashboard](#) .

Request

- cURL
- WSS

```
curl https://polygon-mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc":"2.0","method":"eth_getTransactionByHash","params":["0xbb3a336e3f823ec18197f1e13ee875700f08f03e2cab75f0d0b118dabb44cba0"],"id":1}' wscat -c wss://polygon-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc":"2.0","method":"eth_getTransactionByHash","params":["0xbb3a336e3f823ec18197f1e13ee875700f08f03e2cab75f0d0b118dabb44cba0"],"id":1}'
```

Response

- JSON

```
{ "id" : 1, "jsonrpc" : "2.0", "result" : { "blockHash" : "0xb3b20624f8f0f86eb50dd04688409e5cea4bd02d700bf6e79e9384d47d6a5a35", "blockNumber" : "0x5bad55", "chainId" : "0x1", "from" : "0x398137383b3d25c92898c656696e41950e47316b", "gas" : "0x1d45e", "gasPrice" : "0xfa56ea00", "hash" : "0xbb3a336e3f823ec18197f1e13ee875700f08f03e2cab75f0d0b118dabb44cba0", "input" :
```

Last updated on Apr 19, 2024 [Previous eth_getTransactionByBlockNumberAndIndex](#) [Next eth_getTransactionCount](#)

Last updated on Apr 19, 2024 [Previous eth_getTransactionByBlockNumberAndIndex](#) [Next eth_getTransactionCount](#)