

Viewing Deposits and Withdrawals by Address

In this tutorial, you'll learn how to use the [Optimism SDK](#) to view all of the [Standard Bridge](#) deposits and withdrawals triggered by a given address.

Check out the tutorial on [Bridging ERC-20 Tokens With the Optimism SDK](#) to learn how to create deposits and withdrawals.

Dependencies

- [node](#)
- [pnpm](#)

Create a Demo Project

You're going to use the Optimism SDK for this tutorial. Since the Optimism SDK is a [Node.js](#) library, you'll need to create a Node.js project to use it.

Make a Project Folder

```
mkdir  
op-sample-project cd  
op-sample-project
```

Initialize the Project

```
pnpm  
init
```

Install the Optimism SDK

```
pnpm  
add  
@eth-optimism/sdk
```

Install ethers.js

```
pnpm  
add  
ethers@^5
```

Add RPC URLs to Your Environment

You'll be using the `getDepositsByAddress` and `getWithdrawalsByAddress` functions from the Optimism SDK during this tutorial. These functions use event queries to retrieve the deposits and withdrawals made by a given address. Since these functions use large event queries, you'll need to use an RPC provider like [Alchemy](#) that supports indexed event queries. Grab an L1 and L2 RPC URL for Sepolia and OP Sepolia, respectively.

```
export L1_RPC_URL = ...
```

Sepolia RPC URL

```
export L2_RPC_URL = ...
```

OP Sepolia RPC URL

The Optimism SDK may be updated in the future to use a different method of retrieving deposits and

withdrawals under the hood that does not require indexed event queries. This tutorial will be updated to reflect those changes if and when they occur.

Start the Node REPL

You're going to use the Node REPL to interact with the Optimism SDK. To start the Node REPL run the following command in your terminal:

node This will bring up a Node REPL prompt that allows you to run javascript code.

Import Dependencies

You need to import some dependencies into your Node REPL session.

Import the Optimism SDK

```
const
optimism
=
require ( "@eth-optimism/sdk" )
```

Import ethers.js

```
const
ethers
=
require ( "ethers" )
```

Set Session Variables

You'll need a few variables throughout this tutorial. Let's set those up now.

Import RPC URLs

```
const
l1RpcUrl
=
process . env . L1_RPC_URL const
l2RpcUrl
=
process . env . L2_RPC_URL
```

Set the address to query

Here you'll be querying over an address that has already made some deposits and withdrawals. You can replace this address with your own address if you'd like.

```
const
address
=
'0x5A07785F07D8ba8a9e5323181fBDab51FE9a36c3'
```

Create the RPC providers

```

const
I1Provider
=
new
ethers . providers .StaticJsonRpcProvider (I1RpcUrl) const
I2Provider
=
new
ethers . providers .StaticJsonRpcProvider (I2RpcUrl)

```

Create the CrossDomainMessenger

The Optimism SDK exports aCrossChainMessenger class that makes it easy to interact with the Standard Bridge contracts.

Create an instance of theCrossChainMessenger class:

```

const
messenger
=
new
optimism .CrossChainMessenger ({ I1ChainId :
11155111 ,
// 11155111 for Sepolia, 1 for Ethereum I2ChainId :
11155420 ,
// 11155420 for OP Sepolia, 10 for OP Mainnet I1SignerOrProvider : I1Provider , I2SignerOrProvider : I2Provider , })

```

Query for Deposits

You'll first query for all of the deposits made by the target address. TheCrossChainMessenger has a convenient function calledgetDepositsByAddress that makes this easy.

Grab all deposits

```

const
deposits
=
await
messenger .getDepositsByAddress (address)

```

Display the deposits

```

for ( const
deposit
of deposits) { console .log ( '-----' ) console .log ( 'From: ' ,
deposit .from) console .log ( 'To: ' ,
deposit .to) console .log ( 'L1 Token:' ,

```

```

deposit .l1Token) console .log ( 'L2 Token:' ,
deposit .l2Token) console .log ( 'Amount: ' ,
deposit . amount .toString () ) }

```

Query for Withdrawals

You'll next query for all of the withdrawals made by the target address. TheCrossChainMessenger has a convenient function called `getWithdrawalsByAddress` that makes this easy.

Grab all withdrawals

```

const
withdrawals
=
await
messenger .getWithdrawalsByAddress (address)

```

Display the withdrawals

```

for ( const
withdrawal
of withdrawals) { console .log ( '-----' ) console .log ( 'From: ' ,
withdrawal .from) console .log ( 'To: ' ,
withdrawal .to) console .log ( 'L1 Token:' ,
withdrawal .l1Token) console .log ( 'L2 Token:' ,
withdrawal .l2Token) console .log ( 'Amount: ' ,
withdrawal . amount .toString () ) }

```

[Bridging Your Standard ERC-20 Token to OP Mainnet](#)[Tracing Deposits and Withdrawals](#)