

# tensor.and

# tensor.and

...

Copy fnand(self:@Tensor, other:@Tensor)->Tensor;

...

Computes the logical AND of two tensors element-wise. The input tensors must have either:

- Exactly the same shape
- The same number of dimensions and the length of each dimension is either a common length or 1.
- 

## Args

- self
- (@Tensor
- ) - The first tensor to be compared
- other
- (@Tensor
- ) - The second tensor to be compared
- 

## Panics

- Panics if the shapes are not equal or broadcastable
- 

## Returns

A newTensor with the same shape as the broadcasted inputs.

## Examples

...

```
Copy usecore::array::{ArrayTrait,SpanTrait};
```

```
useorion::operators::tensor::{TensorTrait,Tensor,BoolTensor};
```

```
fnand_example()->Tensor { lettensor_1=TensorTrait::new( shape:array![3,3].span(), data:array![false,true,false,false,false,true,true,false,true,false,false,true].span(), );
```

```
lettensor_2=TensorTrait::new( shape:array![3,3].span(), data:array![false,false,true,true,false,true,false,true,false,true,false,true].span(), );
```

```
returntensor_1.and(@tensor_2); }
```

```
[false,false,false,false,false,true,false,false,false,false,false,true]
```

...

[Previous tensor.identity](#) [Next tensor.where](#)

Last updated1 month ago