

Swap automation

Introduction

The following guide demonstrates an automated swapping strategy for a liquidity pool on the Fetch.ai network. It interacts with a liquidity pool contract and performs swaps between two different tokens (atestfet and CW20 tokens) based on specified price thresholds. A mean-reversion strategy expects the prices to return to "normal" levels or a certain moving average following a temporary price spike. We can construct a similar strategy using the Liquidity Pool, where we will set upper and lower bound prices that will trigger a sell and a buy transaction respectively. If the behavior of the LP prices works as expected always returning to a certain moving average, we could profit by selling high and buying low. We will do this by swapping atestfet and CW20 with the Liquidity Pool, we refer to a sell transaction when we sell atestfet and get CW20 tokens, a buy transaction would be exactly the opposite.

Walk-through

1. Let's start by creating a Python script and name it:touch aerial_swap_automation.py
2. Let's then import the needed classes:
3. import
4. argparse
5. from
6. time
7. import
8. sleep
9. from
10. cosmpy
11. .
12. aerial
13. .
14. client
15. import
16. LedgerClient
17. ,
18. NetworkConfig
19. from
20. cosmpy
21. .
22. aerial
23. .
24. contract
25. import
26. LedgerContract
27. from
28. cosmpy
29. .
30. aerial
31. .
32. faucet
33. import
34. FaucetApi
35. from
36. cosmpy
37. .
38. aerial
39. .
40. wallet
41. import
42. LocalWallet
43. We then need to define aswap_native_for_cw20()
44. function which performs a swap from native tokens (atestfet) to CW20 tokens within a liquidity pool:
45. def
46. swap_native_for_cw20
47. (
48. swap_amount
49. ,
50. pair_contract
51. ,

```

52. wallet
53. ):
54. ""
55. Swap Native for cw20.
56. :param swap_amount: swap amount
57. :param pair_contract: pair contract address
58. :param wallet: wallet address
59. ""
60. tx
61. =
62. pair_contract
63. .
64. execute
65. (
66. {
67. "swap"
68. : {
69. "offer_asset"
70. : {
71. "info"
72. : {
73. "native_token"
74. : {
75. "denom"
76. :
77. "atestfet"
78. }},
79. "amount"
80. :
81. str
82. (swap_amount),
83. }
84. }
85. },
86. sender
87. =
88. wallet,
89. funds
90. =
91. str
92. (swap_amount)
93. +
94. "atestfet"
95. ,
96. )
97. print
98. (
99. "swapping native for cw20 tokens"
100. )
101. tx
102. .
103. wait_to_complete
104. ()
105. Within the function, we defined the following parameters:
106.
107.     ◦ swap_amount
108.     ◦ : this parameter specifies the amount of native tokens to be swapped for CW20 tokens.
109.     ◦ pair_contract
110.     ◦ : this parameter represents the contract address of the liquidity pool pair where the swap will occur.
111.     ◦ wallet
112.     ◦ : this parameter represents the wallet address that will perform the swap.
113. The function constructs a transaction to execute the swap operation. Theexecute()
114. method is called on thepair_contract

```

```

114. with a dictionary specifying the"swap"
115. operation. Inside the"swap"
116. operation, theoffer_asset
117. field is set to the following:
118.
    ◦ info
119.
    ◦ : this field specifies that the swap involves native tokens (native_token
120.
    ◦ ) with the denomination"atestfet"
121.
    ◦ .
122.
    ◦ amount
123.
    ◦ : this field specifies the amount of native tokens to be swapped, which is converted to a string.
124. Thesender
125. parameter is set to thewallet
126. address, indicating that the wallet will initiate the swap. Thefunds
127. parameter is set to a string representing the total amount of funds being used for the swap, which includes
    theswap_amount
128. and"atestfet"
129. . Finally, the function waits for the transaction to complete and prints a message indicating that native tokens are being
    swapped for CW20 tokens.
130. We then need to define aswap_cw20_for_native()
131. function which performs a swap from CW20 tokens to native tokens (atestfet) within a liquidity pool:
132. def
133. swap_cw20_for_native
134. (
135. swap_amount
136. ,
137. pair_contract_address
138. ,
139. token_contract
140. ,
141. wallet
142. ):
143. """
144. Swap cw20 for native.
145. :param swap_amount: swap amount
146. :param pair_contract_address: pair contract address
147. :param token_contract: token contract
148. :param wallet: wallet address
149. """
150. tx
151. =
152. token_contract
153. .
154. execute
155. (
156. {
157. "send"
158. : {
159. "contract"
160. : pair_contract_address,
161. "amount"
162. :
163. str
164. (swap_amount),
165. "msg"
166. :
167. "eyJzd2Fwlp7fX0="
168. ,
169. }
170. },
171. wallet,
172. )
173. print

```

```

174. (
175. "swapping cw20 for native tokens"
176. )
177. tx
178. .
179. wait_to_complete
180. ()
181. Within the function, we defined the following parameters:
182.
    ◦ swap_amount
183.
    ◦ : this parameter specifies the amount of CW20 tokens to be swapped for native tokens.
184.
    ◦ pair_contract_address
185.
    ◦ : this parameter represents the contract address of the liquidity pool pair where the swap will occur.
186.
    ◦ token_contract
187.
    ◦ : this parameter represents the contract for the CW20 token.
188.
    ◦ wallet
189.
    ◦ : This parameter represents the wallet address that will perform the swap.
190. The function constructs a transaction to execute the swap operation: theexecute()
191. method is called on the token_contract
192. with a dictionary specifying the "send"
193. operation. Inside this operation, the contract field is set to pair_contract_address
194. , indicating that the CW20 tokens will be sent to the liquidity pool. The amount
195. field is set to the swap_amount
196. , which is converted to a string. The msg
197. field is set to the base64 encoded message "eyJzd2FwIjE7fX0="
198. , which likely contains additional instructions or parameters for the swap. The wallet
199. address is specified as the sender of the transaction. Finally, the function waits for the transaction to complete and
    prints a message indicating that CW20 tokens are being swapped for native tokens.
200. We now would need to proceed by defining a _parse_commandline()
201. function:
202. def
203. _parse_commandline
204. ():
205. """Commandline parser."""
206. parser
207. =
208. argparse
209. .
210. ArgumentParser
211. ()
212. parser
213. .
214. add_argument
215. (
216. "trading_wallet"
217. ,
218. type
219. =
220. int
221. ,
222. nargs
223. =
224. "?"
225. ,
226. default
227. =
228. 1000000
229. ,
230. help
231. =
232. "initial atestfet balance to perform swaps using the liquidity pool"

```

```
233. ,
234. )
235. parser
236. .
237. add_argument
238. (
239. "upper_bound"
240. ,
241. type
242. =
243. int
244. ,
245. nargs
246. =
247. "?"
248. ,
249. default
250. =
251. 20.5
252. ,
253. help
254. =
255. "price upper bound that will trigger a swap from cw20 to native tokens"
256. ,
257. )
258. parser
259. .
260. add_argument
261. (
262. "lower_bound"
263. ,
264. type
265. =
266. int
267. ,
268. nargs
269. =
270. "?"
271. ,
272. default
273. =
274. 19.5
275. ,
276. help
277. =
278. "price lower bound that will trigger a swap from native to cw20 tokens"
279. ,
280. )
281. parser
282. .
283. add_argument
284. (
285. "commission"
286. ,
287. type
288. =
289. int
290. ,
291. nargs
292. =
293. "?"
294. ,
295. default
296. =
297. 0.003
298. ,
299. help
300. =
```

```

301. "LP commission, for terraswap the default is 0.3%"
302. ,
303. )
304. parser
305. .
306. add_argument
307. (
308. "interval_time"
309. ,
310. type
311. =
312. int
313. ,
314. nargs
315. =
316. "?"
317. ,
318. default
319. =
320. 5
321. ,
322. help
323. =
324. "interval time in seconds to query liquidity pool price"
325. ,
326. )
327. return
328. parser
329. .
330. parse_args
331. ()
332. This function is responsible for parsing command line arguments in the script. It uses theargparse.ArgumentParser()
333. class to define and handle the expected command line arguments:
334.
335.     ◦ trading_wallet
336.
337.     ◦ .
338.     ◦ upper_bound
339.
340.     ◦ : this argument specifies the upper price threshold that will trigger a swap from cw20 to native tokens . If not
341.         provided, it defaults to20.5
342.
343.     ◦ .
344.     ◦ lower_bound
345.
346.     ◦ : this argument sets the lower price threshold that will trigger a swap from native to cw20 tokens. It defaults
347.         to19.5
348.
349.     ◦ if not provided.
350.
351.     ◦ commission
352.
353.     ◦ : this argument defines the commission rate for the liquidity pool. The default is0.003
354.
355.     ◦ , representing 0.3%.
356.
357.     ◦ interval_time
358.
359.     ◦ : this argument determines the interval (in seconds) at which the script queries the liquidity pool price. If not
360.         provided, it defaults to5
361.
362.     ◦ seconds.
363.
364. The function then returns an object containing the parsed arguments. These arguments can be accessed later in the

```

```
script to control the behavior of the swap automation.  
350. We are ready to write down ourmain()  
351. function:  
352. def  
353. main  
354. ():  
355. """Run main."""  
356. args  
357. =  
358. _parse_commandline  
359. ()
```

360. Define any wallet

```
361. wallet  
362. =  
363. LocalWallet  
364. .  
365. generate  
366. ()
```

367. Network configuration

```
368. ledger  
369. =  
370. LedgerClient  
371. (NetworkConfig.  
372. latest_stable_testnet  
373. ())
```

374. Add tokens to wallet

```
375. faucet_api  
376. =  
377. FaucetApi  
378. (NetworkConfig.  
379. latest_stable_testnet  
380. ())  
381. wallet_balance  
382. =  
383. ledger  
384. .  
385. query_bank_balance  
386. (wallet.  
387. address  
388. ())  
389. while  
390. wallet_balance  
391. <  
392. (  
393. 10  
394. **  
395. 18  
396. )  
397. :  
398. print  
399. (  
400. "Providing wealth to wallet..."  
401. )  
402. faucet_api  
403. .  
404. get_wealth  
405. (wallet.  
406. address  
407. ())
```

```
408. wallet_balance
409. =
410. ledger
411. .
412. query_bank_balance
413. (wallet.
414. address
415. ())
```

416. **Define cw20, pair and liquidity token contracts**

```
417. token_contract_address
418. =
419. (
420. "fetch1qr8sysnfxmqzu7cu7cq7dsq5g2r0kvkg5e2wl2fnlkqss60hcjsxtljxl"
421. )
422. pair_contract_address
423. =
424. (
425. "fetch1vgnx2d46uvyxr9pc5mktkcvkp4uflyp3j86v68pq4jxdc8j4y0s6ulf2a"
426. )
427. token_contract
428. =
429. LedgerContract
430. (
431. path
432. =
433. None
434. , client
435. =
436. ledger, address
437. =
438. token_contract_address
439. )
440. pair_contract
441. =
442. LedgerContract
443. (
444. path
445. =
446. None
447. , client
448. =
449. ledger, address
450. =
451. pair_contract_address
452. )
```

453. **tokens in trading wallet (currency will vary [atestfet,cw20])**

```
454. currency
455. =
456. "atestfet"
457. tokens
458. =
459. args
460. .
461. trading_wallet
```

462. **Swap thresholds**

```
463. upper_bound
464. =
```



```
465. args
466. .
467. upper_bound
468. lower_bound
469. =
470. args
471. .
472. lower_bound
```

473. **LP commission**

```
474. commission
475. =
476. args
477. .
478. commission
```

479. **Wait time**

```
480. interval
481. =
482. args
483. .
484. interval_time
485. while
486. True
487. :
```

488. **Query LP status**

```
489. pool
490. =
491. pair_contract
492. .
493. query
494. ({
495. "pool"
496. : {}})
497. native_amount
498. =
499. int
500. (pool[
501. "assets"
502. ][
503. 1
504. ][
505. "amount"
506. ])
507. cw20_amount
508. =
509. int
510. (pool[
511. "assets"
512. ][
513. 0
514. ][
515. "amount"
516. ])
517. if
518. currency
519. ==
520. "atestfet"
521. :
```

522. **Calculate received cw20 tokens if atestfet tokens are**

522. **Calculate received CW20 tokens if atestfet tokens are given to LP**

```
523. tokens_out
524. =
525. round
526. (
527. ((cw20_amount
528. *
529. tokens)
530. /
531. (native_amount
532. +
533. tokens))
534. *
535. (
536. 1
537. -
538. commission)
539. )
```

540. **Sell price of atestfet => give atestfet, get cw20**

```
541. sell_price
542. =
543. tokens
544. /
545. tokens_out
546. print
547. (
548. "atestfet sell price: "
549. , sell_price)
550. if
551. sell_price
552. <=
553. lower_bound
554. :
555. swap_native_for_cw20
556. (tokens, pair_contract, wallet)
557. tokens
558. =
559. int
560. (
561. token_contract.
562. query
563. (
564. {
565. "balance"
566. : {
567. "address"
568. :
569. str
570. (wallet.
571. address
572. ())}}
573. )[
574. "balance"
575. ]
576. )
```

577. **Trading wallet currency changed to cw20**

```
578. currency
579. =
580. "CW20"
```

```
581. else
582. :
```

583. **Calculate received atestfet tokens if cw20 tokens are given to LP**

```
584. tokens_out
585. =
586. round
587. (
588. ((native_amount
589. *
590. tokens)
591. /
592. (cw20_amount
593. +
594. tokens))
595. *
596. (
597. 1
598. -
599. commission)
600. )
```

601. **Buy price of atestfet => give cw20, get atestfet**

```
602. buy_price
603. =
604. tokens_out
605. /
606. tokens
607. print
608. (
609. "atestfet buy price: "
610. , buy_price)
611. if
612. buy_price

613.      =

614. upper_bound
615. :
616. swap_cw20_for_native
617. (
618. tokens, pair_contract_address, token_contract, wallet
619. )
620. tokens
621. =
622. tokens_out
```

623. **Trading wallet currency changed to cw20**

```
624. currency
625. =
626. "atestfet"
627. sleep
628. (interval)
629. if
630. name
631. ==
632. "main"
633. :
634. main
635. ()
```

```

636. Within themain()
637. function, the_parse_commandline()
638. function is used to parse command line arguments. It sets various parameters such as the initial trading wallet balance,
    upper and lower price bounds for triggering swaps, liquidity pool commission, and interval time for querying the
    liquidity pool price, and all of these values are store in theargs
639. variable. After this, a new wallet is generated using thegenerate()
640. method of theLocalWallet
641. class, and network configuration is set up using theLedgerClient()
642. class. Tokens are added to the wallet by using the Faucet API. This happens within awhile
643. loop which continues until the wallet balance reaches at least10**18
644. . The wallet balance is retrieved using thequery_bank_balance()
645. . Afterwards, we need to define the addresses of the CW20, pair, and liquidity token contracts, as well as initialise
    various variables based on the command line arguments, including the initial wallet balance,upper_bound
646. andlower_bound
647. price bounds for swaps, LP commission rate, and the interval at which to check the liquidity pool price.
648. We then define a loop (while True
649. ), which:
650.
    ◦ Queries the liquidity pool status (pair_contract.query({"pool": {}})
651.
    ◦ ) to get the current amounts of native tokens (atestfet
652.
    ◦ ) and CW20 tokens.
653.
    ◦ Checks the current currency in the trading wallet (currency
654.
    ◦ ), which can be either native or CW20 tokens.
655.
    ◦ If the currentcurrency
656.
    ◦ isatestfet
657.
    ◦ , it calculates the potential amount of CW20 tokens that would be received if native tokens were given to the
        liquidity pool. This is done based on the ratio of CW20 tokens to the total of native tokens and current wallet
        tokens, with a deduction for the LP commission. It calculates asell_price
658.
    ◦ as the ratio of the current wallet tokens to tokens swapped out.
659.
    ◦ If the sell price is lower than or equal to the specifiedlower_bound
660.
    ◦ , it triggers theswap_native_for_cw20()
661.
    ◦ function, which swaps atestfet tokens for CW20 tokens.
662.
    ◦ After the successful swap, it updates the tokens variable to the new balance of CW20 tokens and changes the
        currency to"CW20"
663.
    ◦ .
664.
    ◦ If the current currency is"CW20"
665.
    ◦ , it calculates the potential amount of atestfet tokens that would be received if CW20 tokens are given to the
        liquidity pool. This is done based on the ratio of native tokens to the total of CW20 tokens and current wallet
        tokens, with a deduction for the LP commission. It calculates abuy_price
666.
    ◦ as the ratio of potential atestfet tokens to the current wallet tokens.
667.
    ◦ If thebuy_price
668.
    ◦ is higher than or equal to the specifiedupper_bound
669.
    ◦ , it triggers theswap_cw20_for_native()
670.
    ◦ function, which swaps CW20 tokens for atestfet tokens.
671.
    ◦ After the successful swap, it updates the tokens variable to the new balance of atestfet tokens and changes the
        currency to"atestfet"
672.

```

- .
- 673.
 - The loop then waits for the specified interval
- 674.
 - before checking the liquidity pool status and performing the next iteration.
- 675. Save the script.

The overall script should be as follows:

```
aerial_swap_automation.py import argparse from time import sleep

from cosmpy . aerial . client import LedgerClient , NetworkConfig from cosmpy . aerial . contract import LedgerContract from
cosmpy . aerial . faucet import FaucetApi from cosmpy . aerial . wallet import LocalWallet

def

swap_native_for_cw20 ( swap_amount ,

pair_contract ,

wallet ): """ Swap Native for cw20.

:param swap_amount: swap amount :param pair_contract: pair contract address :param wallet: wallet address

""" tx = pair_contract . execute ( { "swap" : { "offer_asset" : { "info" : { "native_token" : { "denom" : "atestfet" } } , "amount" : str
(swap_amount) , } } } , sender = wallet , funds = str (swap_amount) +

"atestfet" , ) print ( "swapping native for cw20 tokens" ) tx . wait_to_complete ()

def

swap_cw20_for_native ( swap_amount ,

pair_contract_address ,

token_contract ,

wallet ): """ Swap cw20 for native.

:param swap_amount: swap amount :param pair_contract_address: pair contract address :param token_contract: token
contract :param wallet: wallet address

""" tx = token_contract . execute ( { "send" : { "contract" : pair_contract_address , "amount" : str (swap_amount) , "msg" :
"eyJzd2FwIjp7fX0=" , } } , wallet , ) print ( "swapping cw20 for native tokens" ) tx . wait_to_complete ()

def

_parse_commandline (): """Commandline parser.""" parser = argparse . ArgumentParser ()

parser . add_argument ( "trading_wallet" , type = int , nargs = "?" , default = 1000000 , help = "initial atestfet balance to
perform swaps using the liquidity pool" , ) parser . add_argument ( "upper_bound" , type = int , nargs = "?" , default = 20.5 ,
help = "price upper bound that will trigger a swap from cw20 to native tokens" , ) parser . add_argument ( "lower_bound" ,
type = int , nargs = "?" , default = 19.5 , help = "price lower bound that will trigger a swap from native to cw20 tokens" , )
parser . add_argument ( "commission" , type = int , nargs = "?" , default = 0.003 , help = "LP commission, for terraswap the
default is 0.3%" , ) parser . add_argument ( "interval_time" , type = int , nargs = "?" , default = 5 , help = "interval time in
seconds to query liquidity pool price" , )

return parser . parse_args ()

def

main (): """Run main.""" args =

_parse_commandline ()
```

Define any wallet

wallet

LocalWallet . generate ()

Network configuration

ledger

```
LedgerClient (NetworkConfig. latest_stable_testnet ())
```

Add tokens to wallet

faucet_api

```
FaucetApi (NetworkConfig. latest_stable_testnet ())
```

wallet_balance

```
ledger . query_bank_balance (wallet. address ())
```

```
while wallet_balance < ( 10 ** 18 ) : print ( "Providing wealth to wallet..." ) faucet_api . get_wealth (wallet. address ())  
wallet_balance = ledger . query_bank_balance (wallet. address ())
```

Define cw20, pair and liquidity token contracts

token_contract_address

```
( "fetch1qr8sysnfxmqzu7cu7cq7dsq5g2r0kvkg5e2wl2fnlkqss60hcjsxtljxl" ) pair_contract_address = (  
"fetch1vgnx2d46uvyxr9pc5mktkcvkp4uflp3j86v68pq4jxdc8j4y0s6ulf2a" )
```

token_contract

```
LedgerContract ( path = None , client = ledger, address = token_contract_address ) pair_contract =
```

```
LedgerContract ( path = None , client = ledger, address = pair_contract_address )
```

tokens in trading wallet (currency will vary [atestfet,cw20])

currency

```
"atestfet" tokens = args . trading_wallet
```

Swap thresholds

upper_bound

```
args . upper_bound lower_bound = args . lower_bound
```

LP commission

commission

```
args . commission
```

Wait time

interval

args . interval_time

while

True :

Query LP status

pool

pair_contract . query ({ "pool" : {} }) native_amount =

int (pool["assets"][1]["amount"]) cw20_amount =

int (pool["assets"][0]["amount"])

if currency ==

"atestfet" :

Calculate received cw20 tokens if atestfet tokens are given to LP

tokens_out

round (((cw20_amount * tokens) / (native_amount + tokens)) * (1

- commission))

Sell price of atestfet => give atestfet, get cw20

sell_price

tokens / tokens_out print ("atestfet sell price: " , sell_price) if sell_price <= lower_bound : swap_native_for_cw20 (tokens, pair_contract, wallet) tokens =

int (token_contract. query ({ "balance" : { "address" : str (wallet. address ())} }) ["balance"])

Trading wallet currency changed to cw20

currency

"CW20" else :

Calculate received atestfet tokens if cw20 tokens are given to LP

tokens_out

round (((native_amount * tokens) / (cw20_amount + tokens)) * (1

- commission))

Buy price of atestfet => give cw20, get atestfet

buy_price

tokens_out / tokens print ("atestfet buy price: " , buy_price) if buy_price

= upper_bound : swap_cw20_for_native (tokens, pair_contract_address, token_contract, wallet) tokens = tokens_out

Trading wallet currency changed to cw20

currency

"atestfet"

sleep (interval)

if

name

==

"main" : main ()

Was this page helpful?

[Liquidity pool Installation](#)