

# Notifications Quickstart

[Suggest Edits](#)

This quickstart guide helps you quickly set up notifications for Programmable Wallets. Follow this to configure a subscriber endpoint that sends a notification every time the status of resource changes. This guide focuses on the challenge resource but applies to any resources available in Programmable Wallet Notifications.

## 1. Expose a Subscriber Endpoint

To receive notifications on changes in resource status, you must expose a publicly accessible subscriber endpoint on your side. The endpoint must handle both HEAD and POST requests over HTTPS. To quickly expose an endpoint for testing, we will use [webhook.site](#) in this guide, which allows you to easily inspect, test and automate any incoming HTTPS request or e-mail directly in a web browser. When visiting [webhook.site](#) for the first time, you should see a status message that looks like the following:

Your unique URL (Please copy it from here, not from the address bar!) <https://webhook.site/83fa21a0-f00a-4673-bb50-bcf62c78b1f7>

Record the value of the unique URL .

In the example above, the unique URL is: <https://webhook.site/83fa21a0-f00a-4673-bb50-bcf62c78b1f7> . Use the public-facing URL you receive as you progress throughout this guide.

## 2. Subscribe to Status Notifications

Now that you have a publicly accessible endpoint, you need to register your endpoint as a subscriber to webhook notifications by doing the following:

1. Click Webhooks
2. in your Circle Developer account.
3. Click Add a Webhook
4. in the upper right corner.
5. Enter your endpoint URL from above. It will be similar to the earlier example:
6. <https://webhook.site/83fa21a0-f00a-4673-bb50-bcf62c78b1f7>
7. .
8. Click Add Webhook
9. .
10. At this stage, you should receive a Hello World test notification indicating you have subscribed to your endpoint successfully:

```
JSON {
  "subscriptionId": "00000000-0000-0000-0000-000000000000",
  "notificationId": "00000000-0000-0000-0000-000000000000",
  "notificationType": "webhooks.test",
  "notification": {
    "hello": "world"
  },
  "timestamp": "2023-07-20T16:18:40.816010685Z",
  "version": 2
} Now you have a sample local environment ready to receive transaction and challenge status change notifications!
```

## 3. Initiate a Challenge Flow to Receive a Notification

To observe a notification message on the status of a challenge, initiate the creation of a wallet (for example, by following the [Programmable Wallets User-Controlled Wallets Tutorial](#) for creating a user-controlled wallet).

Once you successfully initiate a challenge payment, you should see a notification message on your local server shell that looks like the following:

Sample Challenge Notification :

```
JSON { "subscriptionId": "a68cd974-d209-46cd-8dbf-b7a081fbd627", "notificationId": "eaa4a4fe-24b8-4329-a4c6-6dfd557dbcb2", "notificationType": "challenges.initialize", "notification": { "id": "9c0a1991-735a-5140-8996-7b95720c5e55", "userId": "2a054cd1-3124-4aa7-b1f0-86c4a4df995c", "type": "INITIALIZE", "status": "COMPLETE", "correlationIds": [ "01890792-a199-77bc-b005-b229f81824fa" ], "errorCode": 0, "errorMessage": "" }, "timestamp": "2023-06-29T14:33:17.785131449Z", "version": 2 }
```

## 4. Digital Signature Verification

1. Every webhook notification is digitally signed by an asymmetric key. In the headers of each webhook, you can find:1. X-Circle-Signature
- 2.
3. 1. : a header containing the digital signature generated by Circle
4. 1. X-Circle-Key-Id
1. : a header containing the UUID you need to retrieve the relevant public key

# Headers

X-Circle-Key-Id: "879dc113-5ca4-4ff7-a6b7-54652083fcf8"  
X-Circle-Signature: "MEYCIQCA9EvPbdEJiy7Cw0eY+KQZA/oFi5ZEInPs8CYpyaJexglhAKIRnDz9QRQmFKx8QFrvawp+8b9Bs2dQ03xD+XaWWDE" 1. Using the X-Circle-Key-Id value, query the following endpoint to retrieve the public key and algorithm used to sign the message:[GET /v2/notifications/publicKey/{keyId}](#)  
cURL

## Replace {YOUR\_API\_KEY} with your API key

## Replace {PUBLIC\_KEY\_ID} with your public key id

curl --request GET --url 'https://api.circle.com/v2/notifications/publicKey{PUBLIC\_KEY\_ID}' --header 'accept: application/json' --header 'authorization: Bearer ENV\_API\_KEY:ID:SECRET' \ If successful, you will receive a response with the following shape

```
Response Body {
  "data": {
    "id": "879dc113-5ca4-4ff7-a6b7-54652083fcf8",
    "algorithm": "ECDSA_SHA_256",
    "publicKey": "MFkwEwYHKoZIzj0DAQcDQgAEsI76SPBZJemW0mJNN4KTvYkLT8b0T4UGhFhzNk3Jfqt6iuPILQLq533FelXwczJbg2U1PHTvQTK7qOQnDL2Tg==",
    "createDate": "2023-06-28T21:47:35.107250Z"
  } } 1. Use the public key and algorithm to verify the integrity of the webhook's payload against the signature found in 2. X-Circle-Signature 3. .
```

Note: Please make sure the webhook notification is properly formatted JSON string prior to verifying it

Response Body { "subscriptionId": "890a8cae-46bd-40ad-bd7f-2e49b8dea9da", "notificationId": "0bdc3e4b-5070-4530-8ed4-2e2e4c9fd2f0", "notificationType": "webhooks.test", "notification": { "hello": "world" }, "timestamp": "2023-07-12T04: 02: 28.555562821Z", "version": 2 } The following code sample demonstrates how to verify the X-Circle-Signature :

```
Python Node.js
Java import base64 import json

from cryptography.exceptions import InvalidSignature
from cryptography.hazmat.primitives import hashes, serialization
from cryptography.hazmat.primitives.asymmetric import ec
```

## Load the public key from the base64 encoded string

```
public_key_base64 = "MFkwEwYHKoZIzj0CAQYIKoZIzj0DAQcDQgAEsI76SZPBjemW0mJNN4KTvYkLT8bOT4UGhFhzNk3fJqf6iuPILQLQ533FeIXwcZJbjg2U1PHTvQTK7qOQnDL2Tg=="
public_key_bytes = base64.b64decode(public_key_base64)
public_key = serialization.load_der_public_key(public_key_bytes)
```

## Load the signature you want to verify

```
signature_base64 = "MEQCIBlJPX7t0FDOcozsRK6qlQwik5Fq6mhAtCSSgIB/yQO7AiB9U5lVpdufKvPhk3cz4TH2t5MP7ArnmPRBmhPztpsIFQ==" signature_bytes = base64.b64decode(signature_base64)
```

## Load and format the message you want to verify

```
message = {"in": {"subscriptionId": "00000000-0000-0000-0000-000000000000"}, "notificationId": "00000000-0000-0000-0000-000000000000", "notificationType": "webhooks.test", "notification": {"hello": "world"}}, "timestamp": "2024-01-26T18:22:19.779834211Z", "version": "2"} json_data = json.loads(message) formatted_json = json.dumps(json_data, separators=(',', ':'))
```

## Verify the signature

```
try: public_key.verify( signature_bytes, formatted_json.encode(), ec.ECDSA(hashes.SHA256()) ) print("Signature is valid.") except InvalidSignature: print("Signature is invalid.") const asn1 = require('asn1.js'); const base64url = require('base64url'); const crypto = require('crypto'); const jwkToPem = require('jwk-to-pem');
```

```
// Define the EC public key ASN.1 syntax const EC_PUBLIC_KEY = asn1.define('ECPublicKey', function () { this.seq().obj( this.key('algorithm').seq().obj( this.key('id').objid(), this.key('namedCurve').objid() ), this.key('publicKey').bitstr() ) });
```

```

// Load the public key from the base64 encoded string
const publicKeyBase64 =
'MfKwEwYHKoZlJ0CAQYIkoZlJ0DAQcDQgAESI76SPBJemW0mJNN4KTvYkLT8bOT4UGhFzNk3Jqf6iulPILQq533FelXwczJbg2U1PHTvQTK7qOQnDL2Tg==';
const publicKeyDer =
base64url.toBuffer(publicKeyBase64);
const publicKeyAsn1 = EC_PUBLIC_KEY.decode(publicKeyDer, 'der');
const publicKeyJwk = { kty: 'EC', crv: 'P-256', x: publicKeyAsn1.publicKey.data.slice(1, 33).toString('base64'), y: publicKeyAsn1.publicKey.data.slice(33).toString('base64') };
const publicKeyPem = jwkToPem(publicKeyJwk);

```

```
// Load the signature you want to verify const signatureBase64 = 'MEQCIBlJPX7i0FD0cozsrK6qIQwik5Fq6mhAtCSSgIB/yQO7AiB9U5lVpdufKvPhk3cz4TH2f5MP7ArnmPRBmhPztplsIFQ=='; const signatureBytes = base64url.toBuffer(signatureBase64);
```

```
// Load and format the message you want to verify
const message = '{"subscriptionId":"00000000-0000-0000-0000-000000000000","notificationId":"00000000-0000-0000-0000-000000000000","notificationType":"webhooks.test","notification":{"hello":"world"},"timestamp":"2024-01-26T18:22:19.779834211Z","version":"2"}';
const jsonData = JSON.parse(message);
const formattedJson = JSON.stringify(jsonData, null, 0);
```

```
// Verify the signature const verify = crypto.createVerify("SHA256"); verify.update(formattedJson); verify.end();
```

```
const isSignatureValid = verify.verify(publicKeyPerin, signatureBytes); if (isSignatureValid) { console.log('Signature is valid.')} else { console.log('Signature is invalid.')} package com.circle.webhook;
```

```
import java.nio.charset.StandardCharsets; import java.security.InvalidKeyException; package com.circle.webhook;
```

```
import com.fasterxml.jackson.core.JsonProcessingException; import com.fasterxml.jackson.databind.JsonNode; import com.fasterxml.jackson.databind.ObjectMapper;
```

```
import java.nio.charset.StandardCharsets; import java.security.InvalidKeyException; import java.security.KeyFactory; import java.security.NoSuchAlgorithmException; import java.security.PublicKey;
import java.security.Signature; import java.security.SignatureException; import java.security.spec.InvalidKeySpecException; import java.security.spec.X509EncodedKeySpec; import java.util.Base64;
```

```
public class CircleSignature { public static void main(String[] args) throws NoSuchAlgorithmException, InvalidKeySpecException, InvalidKeyException, SignatureException, JsonProcessingException {  
    // Load the public key from the base64 encoded string String publicKeyBase64 =  
    "MFkwEwYHKoZIzj0CAQYIKoZIzj0DAQcDQgAEsI76SZPBjemW0mJNN4KTvYkLT8bOT4UGhFhzNk3fJq6iuiPILQk533FelXwczJbg2U1PHTvQTK7qOQNDL2Tg=="; byte[] publicKeyBytes =  
    Base64.getDecoder().decode(publicKeyBase64); X509EncodedKeySpec keySpec = new X509EncodedKeySpec(publicKeyBytes); KeyFactory keyFactory = KeyFactory.getInstance("EC"); PublicKey  
    publicKey = keyFactory.generatePublic(keySpec);
```

```
// Load the signature you want to verify
String signatureBase64 = "MEQCIBJXPX7i0FD0CoczRK6qIqWiks5Fq6mhAtCSSgJB/yQO7AiB9U5iVpduflKvPhK3cz4TH25iMP7ArnmPRBmhPztpslFQ==";
byte[] signatureBytes = Base64.getDecoder().decode(signatureBase64);
```

```
// Load and format the message you want to verify
String message = "\n{\"subscriptionId\":\"000000000-0000-0000-000000000000\",\"notificationId\":\"00000000-0000-0000-000000000000\",\"notificationType\":\"webhooks.test\",\"notification\":{\"hello\":\"world\"},\"timestamp\":\"2024-01-26\"}";
ObjectMapper objectMapper = new ObjectMapper();
JsonNode jsonData = objectMapper.readTree(message);
String formattedJson = objectMapper.writeValueAsString(jsonData);
```

```
// Verify the signature
Signature signature = Signature.getInstance("SHA256withECDSA");
signature.initVerify(publicKey);
signature.update(formattedJson.getBytes(StandardCharsets.UTF_8));
```

```
boolean isValidSignature = signature.verify(signatureBytes);
if (isValidSignature) {
    System.out.println("Signature is valid.");
} else {
    System.out.println("Signature is invalid.");
}
```

}

## 5. IP Accesslist Check

To ensure the security of your integration, only trust Circle webhook notifications from the following IP addresses.

54.243.112.156

100.24.191.35

54.165.52.248

54.87.106.46 Updated 10 days ago

What's Next Congratulations, you have received your first notification for a Programmable Wallets challenge! [Notification Flows](#) \* [Table of Contents](#) \* [1. Expose a Subscriber Endpoint](#) \* [2. Subscribe to Status Notifications](#) \* [3. Initiate a Challenge Flow to Receive a Notification](#) \* [4. Digital Signature Verification](#) \* [5. IP Accesslist Check](#)