

Multisig Transactions

Multisig transactions require signatures of multiple private keys, typically owned by multiple parties. A multisig transaction is initiated by any key holder, and at least one of them would need to import other parties' public keys into their Keybase and generate a multisig public key to finalize and broadcast multisig transactions.

Show Multisig Address

When a new multisig public key `test_multisig` is stored its address will be the signer of multisig transactions:

...

Copy `secretcli` keys show `test_multisig -a`

```
secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6
```

...

View Multisig Threshold

You may also view multisig threshold, pubkey constituents and respective weights by viewing the JSON output of the key:

...

Copy `secretcli` `keyshowtest_multisig--pubkey`

You will see the output of the pubkey, look or "threshold"

```
{["@type":"/cosmos.crypto.multisig.LegacyAminoPubKey","threshold":2,"public_keys":[{"@type":"/cosmos.crypto.secp256k1.PubKey","key":"AiXwUPtWtJqxKZq/BjKi+7EFhqR2Aj9QT94IFzb5Ednp"}],{"@type":"/cosmos.crypto.secp256k1.PubKey","key":"A7QMHOt+yLGddDxey51QLofwsTJWfqyzYmNOB9L1Oz1S"}],{"@type":"/cosmos.crypto.secp256k1.PubKey","key":"A0QMBqFY4J39i6NrH4qR5uOEnyytpkyeWFg/e0sPd8NJ"}]}' mnemonic:""
```

...

The `-p` flag can be used interchangeably with the `--pubkey` flag to only show the output of pubkey information.

...

Copy `secretcli` keys show `test_multisig -p`

...

Initiate Multisig Transaction

General usage of the `secretcli` for sending transactions uses the follow format:

...

Copy `secretclitxbanksend` `[from_key_or_address] [to_address] [amount] [flags]`

...

Note: To be able to correctly test multisig transactions you will need tokens owned by the multisig wallet [Get testnet tokens using the faucet](#).

The first step to create a multisig transaction is to initiate it on behalf of the multisig address created above using the following command:

...

Copy `secretclitxbanksend` `secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6#Fromaddress secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs#Toaddress 1000uscr#Amountbeingsent --generate-only>unsignedTx.json#` Json for account owner signing

...

...

Copy

unsignedTx.json file contents

```
{ "body":{ "messages":[{" @type":"/cosmos.bank.v1beta1.MsgSend", "from_address":"secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6", "to_address":"secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs", "amount":[{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"1000" } ] }, {" @type":"/cosmos.bank.v1beta1.MsgSend", "from_address":"secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6", "to_address":"secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs", "amount":[{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"1000" } ] }, {" @type":"/cosmos.bank.v1beta1.MsgSend", "from_address":"secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6", "to_address":"secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs", "amount":[{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"1000" } ] } ], "memo":"","timeout_height":"0", "extension_options":{ }, "non_critical_extension_options":{ }, "auth_info":{" @type":"/cosmos.auth.v1beta1.AuthInfo", "signer_infos":[{" @type":"/cosmos.auth.v1beta1.SignerInfo", "public_key":{" @type":"/cosmos.crypto.multisig.LegacyAminoPubKey", "threshold":2, "public_keys":[{" @type":"/cosmos.crypto.secp256k1.PubKey", "key":"A7QMHOt+yLGddDxey51QLofwsTJWfqyzYmNOB9L1Oz1S"}] }, "fee":{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"50000" } }, "gas_limit":"200000", "payer":"","granter":"" } ], "signatures":[] } # Notice that none of the multisig owners have signed yet
```

...

Signing Multisig Transactions

The file `unsignedTx.json` contains the unsigned transaction encoded in JSON. `key1` can now sign the transaction with its own private key:

...

Copy `secretclitxsign` `unsignedTx.json --multisig=test_multisig --from=key1 --output-document=key1Signature.json --chain-id=pulsar-3` # This is the testnet chain-id

...

After generating the `key1Signature.json` file, other wallets making up the multisig need to use the `unsignedTx.json` to generate their own individual signed json files:

...

Copy `secretcli tx sign` `unsignedTx.json --multisig=test_multisig --from=key2 --output-document=key2Signature.json --chain-id=pulsar-3`

...

Since the 'k' value of `test_multisig` is set to 2, a third signature from the final key making up the wallet (`key3`) is not required to officially sign and broadcast the multisig transaction. Any the key holders of the multisig can now generate the multisig transaction by combining the required signature files:

...

Copy `secretclitxmulsign` `unsignedTx.json test_multisig key1Signature.json key2Signature.json>signedTx.json`

...

...

Copy

signedTx.json contents

```
{ "body":{ "messages":[{" @type":"/cosmos.bank.v1beta1.MsgSend", "from_address":"secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6", "to_address":"secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs", "amount":[{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"1000" } ] }, {" @type":"/cosmos.bank.v1beta1.MsgSend", "from_address":"secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6", "to_address":"secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs", "amount":[{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"1000" } ] }, {" @type":"/cosmos.bank.v1beta1.MsgSend", "from_address":"secret1zy90yjysn579l65sj643tphq4pem6ufkl0djd6", "to_address":"secret1kcy20p0cs2wakeqz00xgs5m0cmj65283xqmvfs", "amount":[{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"1000" } ] } ], "memo":"","timeout_height":"0", "extension_options":{ }, "non_critical_extension_options":{ }, "auth_info":{" @type":"/cosmos.auth.v1beta1.AuthInfo", "signer_infos":[{" @type":"/cosmos.auth.v1beta1.SignerInfo", "public_key":{" @type":"/cosmos.crypto.multisig.LegacyAminoPubKey", "threshold":2, "public_keys":[{" @type":"/cosmos.crypto.secp256k1.PubKey", "key":"A7QMHOt+yLGddDxey51QLofwsTJWfqyzYmNOB9L1Oz1S"}] }, "fee":{" @type":"/cosmos.bank.v1beta1.Coin", "denom":"uscr", "amount":"50000" } }, "gas_limit":"200000", "payer":"","granter":"" } ], "signatures":[{" @type":"/cosmos.crypto.secp256k1.RecoverySig", "signature":"A7QMHOt+yLGddDxey51QLofwsTJWfqyzYmNOB9L1Oz1S"}] }
```

```
"@type":"/cosmos.crypto.secp256k1.PubKey", "key":"A2wRQgUwB6BMLcoa9acVrZ56EydgQMb0hJS1Fq6/nLPs" }, { "@type":"/cosmos.crypto.secp256k1.PubKey",
"key":"Ax112MHj4ZEPJd0eWlu25bNoTH6XyhY5MdsUlqut3Fv" }, { "@type":"/cosmos.crypto.secp256k1.PubKey", "key":"AzkEF0QT7qTvl/W3lO5lPQMUa9sR7Z29b4TT6k0Lo8Qe" } ] }, "mode_info":{
"multi":{"bitarray":{"extra_bits_stored":3, "elems":{"wA==" }, "mode_infos":[{"single":{"mode":"SIGN_MODE_LEGACY_AMINO_JSON" } }, { "single":{"mode":"SIGN_MODE_LEGACY_AMINO_JSON"
}}} ] }, "sequence":"0" }, "fee":{"amount":[{"denom":"uscr", "amount":"50000" } ], "gas_limit":"200000", "payer":"","granter":"" }, "signatures":[
"CkAJd+gSCrcPd8hIX2YT68bCALTi8+Rk0AVUGnMK7QAuFmrr2uACK9q2u4Qij49BXL6LaXEhZkUXFc3aCkMxmJFCkCEeY7AGFowB+GIBiZkEUsJg/RjM/cvqt/JvBcSYwDiS2EAMBMGItZNP/WdRX1f
]]}
...

```

Broadcasting Multisig Transactions

The transaction can now be broadcast to the network using the signed.json file:

...

Copy secretcltxbroadcastsignedTx.jshon

...

After executing the above command an output will be generated containing information about the transaction:

...

```
Copy { "height":"0", "txhash":"52A1CB5C4049023A14616462A37A419240EBE99E7C941B7E9E17BD32FE92B134", "codespace":"sdk", "code":19, "data":"","raw_log":"","logs":[], "info":"","
"gas_wanted":"0", "gas_used":"0", "tx":null, "timestamp":"","events":[] }
```

...

Broadcasted transactions can be viewed online using a Secret Network block explorer by searching for the transaction has (txhash). For example, the testnet transaction above can be viewed [here](#) .

Last updated9 months ago On this page * [Show Multisig Address](#) * [View Multisig Threshold](#) * [Initiate Multisig Transaction](#) * [Signing Multisig Transactions](#) * [Broadcasting Multisig Transactions](#)

Was this helpful? [Edit on GitHub](#) [Export as PDF](#)