

seid query dex list-short-book

Lists all of a short book's information for a given contract address and pair specified by price denom and asset denom.

Usage: `seid query dex list-short-book [contract address] [price denom] [asset denom] [flags]`

Flags: `--count-total` count total number of records in list-short-book [contract address] [price denom] [asset denom] to query for `--height` int Use a specific height to query state at (this can error if the node is pruning state) `-h, --help` help for list-short-book `--limit` uint pagination limit of list-short-book [contract address] [price denom] [asset denom] to query for (default 100) `--node` string : to Tendermint RPC interface for this chain (default "tcp://localhost:26657") `--offset` uint pagination offset of list-short-book [contract address] [price denom] [asset denom] to query for `-o, --output` string Output format (text|json) (default "text") `--page` uint pagination page of list-short-book [contract address] [price denom] [asset denom] to query for. This sets offset to a multiple of limit (default 1) `--page-key` string pagination page-key of list-short-book [contract address] [price denom] [asset denom] to query for `--reverse` results are sorted in descending order

Global Flags: `--chain-id` string The network chain ID `--home` string directory for config and data (default "~/.sei") `--log_format` string The logging format (json|plain) `--log_level` string The logging level (trace|debug|info|warn|error|fatal|panic) `--trace` print out full stack trace on errors Last updated on July 1, 2024 [list-long-book params](#)