Example Nginx config

Here is an examplenginx.conf for Loadbalancing on Nginx:

...

Copy userwww-data; worker_processes auto;#Relevant to handle as many connections as the server config could, is correlated to number of cores in the CPU

https://nginx.org/en/docs/ngx_core_module.html#worker_processes

error_log/var/log/nginx/error.logwarn; pid/var/run/nginx.pid;

events{ worker_connections1024;#Relevant to handle as many connections as the server config could

clients = worker_processes * worker_connections

}#https://nginx.org/en/docs/ngx_core_module.html#worker_connections

http{

large_client_header_buffers4128k; server_names_hash_bucket_size128;

maprequest_uri short_uri { "~^(.{0,50})"1; defaultrequest_uri; }

 $mapremote_addr \ anonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ note that \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ noth \ nonymized_addr \ \{ \ \sim (?P\ d+.\ d+).\ d+.ip.0.0; \ \sim (?P[^:]+:[^:]+): ip::; \\ noth \ nonymized_addr \ nony$

IP addresses to not anonymize (such as your server)

127.0.0.1remote_addr; ::1 remote_addr;

w.x.y.z remote addr;

a::c:d::e:f remote_addr;

default0.0.0.0; }

}

log_formatcombined_log'anonymized_addr - remote_user [time_local] ' "short_uri" status body_bytes_sent ' "http_referer" "http_user_agent"; access_log/var/log/nginx/access.log combined_log;

 $limit_req_zone binary_remote_addr\ zone = mylimit: 1 M\ rate = 70 r/s; \ limit_reqzone = mylimit\ burst = 9000\ nodelay; \\$

WSS compatibility config

maphttp_upgrade connection_upgrade { defaultupgrade; "close; }

Upstream group

upstreamgrpc_stream { least_conn;#Redirect requests to the server with least number of active connections serverXXX.XXX.XXXX.XXX.9091 max_fails=1000fail_timeout=30s; serverXXX.XXX.XXX.XXX.9091 max_fails=1000fail_timeout=30s; serverXXX.XXX.XXX.XXX.9091 max_fails=1000fail_timeout=30s;

upstreamIcd_stream { least_conn;#Redirect requests to the server with least number of active connections serverXXX.XXX.XXXX.XXX.1317 max_fails=1000fail_timeout=30s; serverXXX.XXX.XXX.XXX.1317 max_fails=1000fail_timeout=30s; serverXXX.XXX.XXX.XXX.1317 max_fails=1000fail_timeout=30s; }

server{ listen80; server_namerpc.YOUR_URL;

location/ { if(request_method='OPTIONS') { return204; }

add_header'Access-Control-Allow-Origin'"http_origin"always; add_header'Access-Control-Allow-Credentials"true'always; add_header'Access-Control-Allow-Headers'* always; add_header'Access-Control-Allow-Methods"GET, POST, OPTIONS'; proxy_passhttp://rpc_stream; proxy_set_headerHost host; proxy_set_headerX-Real-IP remote_addr; proxy_set_headerX-Forwarded-For proxy_add_x_forwarded_for; proxy_set_headerX-Forwarded-Proto scheme; proxy_set_headerUpgrade http_upgrade;#WSS compatibility config proxy_set_headerConnection

```
connection upgrade;#WSS compatibility config }
server{ listen26657; server namerpc.YOUR URL;
location/ { if(request method='OPTIONS') { return204; }
add_header'Access-Control-Allow-Origin""http_origin"always; add_header'Access-Control-Allow-Credentials"true'always; add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Credentials
Control-Allow-Headers'* always; add_header'Access-Control-Allow-Methods"GET, POST, OPTIONS';
proxy_passhttp://rpc_stream; proxy_set_headerHost host; proxy_set_headerX-Real-IP remote_addr; proxy_set_headerX-Forwarded-For
proxy_add_x_forwarded_for; proxy_set_headerX-Forwarded-Proto scheme; proxy_set_headerUpgrade http_upgrade;#WSS compatibility config
proxy set headerConnection connection upgrade;#WSS compatibility config } }
server{ listen80; server_namegrpc.YOUR_URL;
location/ { if(request method='OPTIONS') { return204; }
add header'Access-Control-Allow-Origin"http origin"always; add header'Access-Control-Allow-Credentials"true'always; add header'Access-Control-Allow-Origin"http origin"always; add header'Access-Control-Allow-Origin"http origin"http origin"http://www.origin.
Control-Allow-Headers'* always; add_header'Access-Control-Allow-Methods"GET, POST, OPTIONS';
proxy_passhttp://grpc_stream; proxy_set_headerHost host; proxy_set_headerX-Real-IP remote_addr; proxy_set_headerX-Forwarded-For
proxy_add_x_forwarded_for; proxy_set_headerX-Forwarded-Proto scheme; proxy_set_headerUpgrade http_upgrade;#WSS compatibility config
proxy_set_headerConnection connection_upgrade;#WSS compatibility config }
}
server{ listen9091; server_namegrpc.YOUR_URL;
location/ { if(request_method='OPTIONS') { return204; }
add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Credentials"true'always; add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Origin"http_origin"always; add_header'Access-Control-Allow-Origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin"http_origin
Control-Allow-Headers'* always; add_header'Access-Control-Allow-Methods"GET, POST, OPTIONS';
proxy passhttp://grpc stream; proxy set headerHost host; proxy set headerX-Real-IP remote addr; proxy set headerX-Forwarded-For
proxy_add_x_forwarded_for; proxy_set_headerX-Forwarded-Proto scheme; proxy_set_headerUpgrade http_upgrade;#WSS compatibility config
proxy_set_headerConnection connection_upgrade;#WSS compatibility config } }
server{ listen1317; server_namelcd.YOUR_URL; location/ { if(request_method='OPTIONS') { return204; }
proxy hide header'Access-Control-Allow-Origin'; proxy hide header'Access-Control-Allow-Credentials'; proxy hide header'Access-Control-Allow-Origin'; proxy hide header'Access-Control-Allow-Credentials'; proxy hide header'Access-Control-Allow-Origin'; proxy hide header'Ac
Allow-Headers'; proxy_hide_header'Access-Control-Allow-Methods';
add_header'Access-Control-Allow-Origin' always; add_header'Access-Control-Allow-Credentials"true'always; add_header'Access-Control-Allow-Origin' always; add_header' a
Headers' always; add_header'Access-Control-Allow-Methods'* always;
proxy_passhttp://lcd_stream; proxy_set_headerHost host; proxy_set_headerX-Real-IP remote_addr; proxy_set_headerX-Forwarded-For
proxy_add_x_forwarded_for; proxy_set_headerX-Forwarded-Proto scheme; proxy_set_headerUpgrade http_upgrade;#WSS compatibility config
proxy_set_headerConnection connection_upgrade;#WSS compatibility config }
}
server{ listen80; server_namelcd.YOUR_URL; location/ {
if(request_method='OPTIONS') { return204; }
proxy hide header'Access-Control-Allow-Origin'; proxy hide header'Access-Control-Allow-Credentials'; proxy hide header'Access-Control-Allow-Origin'; proxy hide header'Access-Control-Allow-Credentials'; proxy hide header'Access-Control-Allow-Origin'; proxy hide header'Ac
Allow-Headers'; proxy_hide_header'Access-Control-Allow-Methods';
add header'Access-Control-Allow-Origin' always; add header'Access-Control-Allow-Credentials"true'always; add header'Access-Control-Allow-Origin' always; add header' always al
Headers' always; add_header'Access-Control-Allow-Methods'* always;
proxy_passhttp://lcd_stream; proxy_set_headerHost host; proxy_set_headerX-Real-IP remote_addr; proxy_set_headerX-Forwarded-For
proxy_add_x_forwarded_for; proxy_set_headerX-Forwarded-Proto scheme; proxy_set_headerUpgrade http_upgrade;#WSS compatibility config
proxy_set_headerConnection connection_upgrade;#WSS compatibility config } }
server{ listen127.0.0.1:80; server_name127.0.0.1; location/nginx_status { stub_statuson; allow127.0.0.1; denyall; } }
}
```

Last updated11 days ago On this page Was this helpful? Edit on GitHub Export as PDF