

# Configuration

The router is accepts configuration using the config file `config.json` in the root directory of the [elocker-compose repo](#).

The JSON schema accepts the following keys:

- `redis`
- `:Required`
- . Object containing the following keys to configure an external redis instance:
  - - `host`
  - - `:Required`
  - - . The hostname of the redis instance.
  - - `port`
  - - `:Required`
  - - . The port of the redis instance.
  - \*
- `server`
- `:Required`
- . Object containing the following keys to configure the HTTP server:
  - - `adminToken`
  - - `:Required`
  - - . Secret token used to authenticate admin requests.
  - - `port`
  - - `:Optional`
  - - . The port the router will listen on. Defaults to 8080
  - - .
  - - `host`
  - - `:Optional`
  - - . The host the router will listen on. Defaults to 0.0.0.0
  - - .
  - \*
- `web3SignerUrl`
- `:Recommended`
- . The URL for a running [Web3Signer](#)
- instance. This is the recommended approach to private key storage.
- `mnemonic`
- `:Optional, Discouraged`
- . The mnemonic used to generate the private key. Using the mnemonic directly in the config file is unsafe and not recommended.
- `chains`
- `:Required`
- . The chain configuration. A JSON object with the following keyed by Domain IDs with the following object schema as value:
  - - `providers`
  - - `:Required`
  - - . An array of providers URLs for a chain. Use a minimum of 1 URL, but additional URLs provide more fallback protection against provider issues.
-

- assets
- 
- :Required
- 
- . An array of assets. Each asset is a JSON object with the following keys:
- 
- - assetId
- 
- - :Required
- 
- - . The asset ID (ERC20 token address). This needs to represent the "local" asset which is the Connex bridge minted asset.
- 
- - name
- 
- - :Required
- 
- - . The Asset Name.

- 
- \*
  - network
  - :Required
  - .mainnet
  - ortestnet
  - .
  - environment
  - :Optional
  - .production
  - orstaging
  - .mainnet
  - network config will always beproduction
  - .
  - logLevel
  - :Optional
  - . The log level. Defaults toinfo
  - . Acceptsdebug
  - ,info
  - ,warn
  - ,error
  - ,fatal
  - ,trace
  - ,silent
  - .
  - sequencerUrl
  - :Optional
  - . The URL for the sequencer. Only used to override defaults.
  - cartographerUrl
  - :Optional
  - . The URL for the cartographer. Only used to override defaults.
  -

## Example Configuration File

These are example RPC URLs. Please get your own RPC URLs!

...

```
Copy { "chains":{ "1634886255":{ "assets":[ { "address":"0x8c556cF37faa0eeDAC7aE665f1Bb0FbD4b2eae36",
"name":"USDC" }, { "address":"0x2983bf5c334743Aa6657AD70A55041d720d225dB", "name":"WETH" } ], "providers":[
"https://arb-mainnet.g.alchemy.com/v2/...", "https://rpc.ankr.com/arbitrum" ] }, "1869640809":{ "assets":[ {
"address":"0x67E51f46e8e14D4E4cab9dF48c59ad8F512486DD", "name":"USDC" }, {
"address":"0xbAD5B3c68F855EaEcE68203312Fd88AD3D365e50", "name":"WETH" } ], "providers":[ "https://opt-
```

```
mainnet.g.alchemy.com/v2/...", "https://rpc.ankr.com/optimism" ] }, "1886350457":{ "assets":[ {
"address":"0xF96C6d2537e1af1a9503852eB2A4AF264272a5B6", "name":"USDC" }, {
"address":"0x4b8BaC8Dd1CAA52E32C07755c17eFadE6A0bbD0", "name":"WETH" } ], "providers":[ "https://polygon-
mainnet.g.alchemy.com/v2/...", "https://rpc.ankr.com/polygon" ] }, "6450786":{ "assets":[ {
"address":"0x5e7D83dA751F4C9694b13aF351B30aC108f32C38", "name":"USDC" }, {
"address":"0xA9CB51C666D2AF451d87442Be50747B31BB7d805", "name":"WETH" } ], "providers":[ "https://bsc-
dataseed1.binance.org", "https://bsc-dataseed2.binance.org", "https://rpc.ankr.com/bsc" ] }, "6648936":{ "assets":[ {
"address":"0xA0b86991c6218b36c1d19D4a2e9Eb0cE3606eB48", "name":"USDC" }, {
"address":"0xC02aaA39b223FE8D0A0e5C4F27eAD9083C756Cc2", "name":"WETH" } ], "providers":[ "https://eth-
mainnet.alchemyapi.io/v2/...", "https://rpc.ankr.com/eth" ] }, "6778479":{ "assets":[ {
"address":"0x44CF74238d840a5fEBB0eAa089D05b763B73faB8", "name":"USDC" }, {
"address":"0x538E2dDbfDf476D24cCb1477A518A82C9EA81326", "name":"WETH" } ], "providers":[
"https://rpc.gnosischain.com", "https://rpc.ankr.com/gnosis" ] } }, "environment":"production", "logLevel":"debug",
"messageQueue":{"uri":"amqp://guest:guest@rabbitmq:5672"}, "redis":{"host":"redis", "port":6379}, "server":{"
"adminToken":"supersecret"}, "web3signer":"http://signer:9000", "network":"mainnet" }
```

...

[Previous Reference](#) Last updated 29 days ago On this page [Edit on GitHub](#)